- GB (RL) M

Page 1 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Acid Shampoo A

Art.: 311999

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Vehicle cleansing

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna

Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26 info@koch-chemie.com www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

(RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)

+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Eye Dam. 1 H318-Causes serious eye damage.

Aquatic Chronic 3 H412-Harmful to aquatic life with long lasting effects.

Met. Corr. 1 H290-May be corrosive to metals.

Skin Corr. 1 H314-Causes severe skin burns and eye damage.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

®®™M

Page 2 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999



Danger

H412-Harmful to aquatic life with long lasting effects. H290-May be corrosive to metals. H314-Causes severe skin burns and eye

P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.

P301+P330+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P390-Absorb spillage to prevent material damage.

Methanesulphonic acid Myristyl dimethyl aminoxide Phosphoric acid

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3 2 Miytures

Phosphoric acid	Substance for which an EU exposure limit value
r nosphone acid	applies.
Devictuation number (DEACH)	01-2119485924-24-XXXX
Registration number (REACH)	
Index	015-011-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	231-633-2
CAS	7664-38-2
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Met. Corr. 1, H290
factors	Acute Tox. 4, H302
	Skin Corr. 1B, H314
	Eye Dam. 1, H318
Specific Concentration Limits and ATE	Skin Corr. 1B, H314: >=25 %
	Skin Irrit. 2, H315: >=10 %
	Eye Dam. 1, H318: >=25 %
	Eye Irrit. 2, H319: >=10 %
	ATE (oral): 500 mg/kg

- GB (RL) M

Page 3 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

Methanesulphonic acid	
Registration number (REACH)	01-2119491166-34-XXXX
Index	607-145-00-4
EINECS, ELINCS, NLP, REACH-IT List-No.	200-898-6
CAS	75-75-2
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Met. Corr. 1, H290
factors	Acute Tox. 4, H302
	Acute Tox. 4, H312
	Skin Corr. 1B, H314
	Eye Dam. 1, H318
	STOT SE 3, H335
Specific Concentration Limits and ATE	ATE (oral): 648,7 mg/kg
	ATE (dermal): 1100 mg/kg

2-Butoxyethanol	Substance for which an EU exposure limit value
	applies.
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	203-905-0
CAS	111-76-2
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 3, H331
factors	Acute Tox. 4, H302
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
Specific Concentration Limits and ATE	ATE (oral): 1200 mg/kg
•	ATE (as inhalation, Aerosol): 0,5 mg/l/4h
	ATE (as inhalation, Vapours): 3 mg/l

Myristyl dimethyl aminoxide	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	222-059-3
CAS	3332-27-2
content %	2,5-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H302
factors	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 2, H411
Specific Concentration Limits and ATE	ATE (oral): 500 mg/kg

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

- GB (RL M

Page 4 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately and call a doctor. Have Data Sheet available. Cauterizations not treated lead to wounds difficult to heal.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Corrosive burns on skin as well as mucous membrane possible.

Risk of serious damage to eyes.

Corneal damage.

Danger of blindness.

pain in the mouth and throat

stomach pain

Oesophageal perforation

Gastric perforation

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of phosphorus

Oxides of sulphur

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

- GB (RL) M

Page 5 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

Keep unprotected persons away. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

Neutralising is possible (only from a specialist).

Diluting with water is possible.

Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Handle and open container with care.

There should be an eyewash station and safety shower located near the area of use.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with alkalis.

Acid-resistant floor necessary.

Do not use acid sensitive materials.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries.

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

®®®M.M. Page 6 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024 Acid Shampoo A

Phosphoric acid Area of application

Consumer

Exposure route /

Human - inhalation

Environmental compartment

Acid Shampoo A	
Art.: 311999	
Dhambaia	
© Chemical Name Phosphoric :	
WEL-TWA: 1 mg/m3 (WEL-TWA, EU)	WEL-STEL: 2 mg/m3 (WEL-STEL, EU)
Monitoring procedures:	- INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air)
	- OSHA ID-111 (Phosphoric Acid in Workplace Atmospheres)
BMGV:	- OSHA ID-165SG (Acid Mist In Workplace Atmospheres) - 1985 Other information:
BIVIGV	Other information
Chemical Name Phosphoric	acid
OELV-8h: 1 mg/m3 (OELV-8h, EU)	OELV-15min: 2 mg/m3 (OELV-15min, EU)
Monitoring procedures:	- INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air)
	- OSHA ID-111 (Phosphoric Acid in Workplace Atmospheres)
	- OSHA ID-165SG (Acid Mist In Workplace Atmospheres) - 1985
BLV:	Other information: IOELV
M Chemical Name Phosphoric	arid
OELV-8h: 1 mg/m3 (OELV-8h, EU)	OELV-ST: 2 mg/m3 (OELV-ST, EU)
Monitoring procedures:	- INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air)
	- OSHA ID-111 (Phosphoric Acid in Workplace Atmospheres)
	- OSHA ID-165SG (Acid Mist In Workplace Atmospheres) - 1985
BMGV:	Other information:
© Chemical Name 2-Butoxyeth	anol
WEL-TWA: 25 ppm (123 mg/m3) (WEL-TWA	
20 ppm (98 mg/m3) (EU)	EU)
Monitoring procedures:	- Compur - KITA-190 U(C) (548 873)
	DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) -
	- 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)
	- NIOSH 1403 (ALCOHOLS IV) - 2003
	- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
DMOV/ 040 mm allowtown and in a sid/mal area	- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990
BMGV: 240 mmol butoxyacetic acid/mol crea	tinine in urine, post shift (BMGV) Other information: Sk (WEL)
Chemical Name 2-Butoxyeth	anol
OELV-8h: 20 ppm (98 mg/m3) (OELV-8h, EU) OELV-15min: 50 ppm (246 mg/m3) (OELV
	15min, EU)
Monitoring procedures:	- Compur - KITA-190 U(C) (548 873)
	DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) -
	- 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)
	- NIOSH 1403 (ALCOHOLS IV) - 2003
	- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
	- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990
BLV: 200 mg/g creatinine (Butoxyacetic acid	
OELV-8h: 20 ppm (98 mg/m3) (OELV-8h, EU	
Monitoring procedures:	- Compur - KITA-190 U(C) (548 873)
	DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) -
	- 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)
	- NIOSH 1403 (ALCOHOLS IV) - 2003
	- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
BMOV 040	- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990
BMGV: 240 mmol butoxyacetic acid/mol crea	tinine in urine, post shift (BMGV) Other information: Skin

Effect on health

Long term, local

effects

Descripto

DNEL

Value

0,73

Unit

mg/m3

Note

-GB (RL M)-

Page 7 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004 Valid from: 11.03.2024

Valid from: 11.03.2024 PDF print date: 15.03.2024

Consumer	Human - inhalation	Short term, local effects	DNEL	2	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	4,57	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,36	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	2,92	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10,7	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,012	mg/l	
	Environment - marine		PNEC	0,0012	mg/l	
	Environment - water,		PNEC	0,12	mg/l	
	sporadic (intermittent)					
	release					
	Environment - sediment,		PNEC	0,0251	mg/kg	
	freshwater					
	Environment - soil		PNEC	0,00183	mg/kg	
	Environment - sewage		PNEC	100	mg/l	
	treatment plant					
	Environment - sediment,		PNEC	0,0044	mg/kg	
	marine					
Consumer	Human - dermal	Long term, systemic	DNEL	8,33	mg/kg	
		effects				
Consumer	Human - inhalation	Long term, systemic	DNEL	1,44	mg/m3	
		effects				
Consumer	Human - inhalation	Short term, systemic	DNEL	1,44	mg/m3	
		effects				
Consumer	Human - inhalation	Long term, local	DNEL	0,42	mg/m3	
		effects				
Consumer	Human - oral	Long term, systemic	DNEL	8,33	mg/kg	
		effects				
Workers / employees	Human - inhalation	Long term, systemic	DNEL	6,76	mg/m3	
		effects				
Workers / employees	Human - inhalation	Long term, local	DNEL	0,7	mg/m3	
		effects				
Workers / employees	Human - dermal	Long term, systemic	DNEL	19,44	mg/kg	
		effects				

2-Butoxyethanol							
Area of application Exposure route / Effect on health Descripto Value Unit							
	Environmental		r				
	compartment						
	Environment - freshwater		PNEC	8,8	mg/l		
	Environment - marine		PNEC	0,88	mg/l		
	Environment - sediment,		PNEC	34,6	mg/kg dw		
	freshwater						
	Environment - soil		PNEC	2,8	mg/kg dw		

- GB (RL M)-

Page 8 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004 Valid from: 11.03.2024

Valid from: 11.03.2024 PDF print date: 15.03.2024

	Environment - sewage treatment plant		PNEC	463	mg/l
	Environment - sediment, marine		PNEC	3,46	mg/kg dw
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l
	Environment - soil		PNEC	2,33	mg/kg
	Environment - oral (animal feed)		PNEC	20	mg/kg
Consumer	Human - inhalation	Long term, local effects	DNEL	123	mg/m3
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d
Consumer Human - inhalation		Short term, systemic effects	DNEL	426	mg/m3
Consumer	sumer Human - oral		DNEL	13,4	mg/kg bw/d
Consumer	Human - inhalation	Short term, local effects	DNEL	147	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3

Myristyl dimethyl amin	oxide					
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,034	mg/l	
	Environment - marine		PNEC	0,003	mg/l	
	Environment - sediment,		PNEC	5,24	mg/kg dry	
	freshwater				weight	
	Environment - sediment,		PNEC	0,524	mg/kg dry	
	marine				weight	
	Environment - soil		PNEC	1,02	mg/kg dry	
					weight	
	Environment - sewage		PNEC	24	mg/l	
	treatment plant					
	Environment - oral (animal		PNEC	1,1	mg/kg	
	feed)				bw/day	
	Environment - sporadic		PNEC	0,034	mg/l	
	(intermittent) release					
Consumer	Human - inhalation	Long term, systemic	DNEL	1,53	mg/m3	
		effects				
Consumer	Human - dermal	Long term, systemic	DNEL	5,5	mg/kg	
		effects			bw/day	
Consumer	Human - oral	Long term, systemic	DNEL	0,44	mg/kg	
		effects			bw/day	

- GB (RL M)-

Page 9 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Workers / employees	Human - inhalation	Long term, systemic	DNEL	6,2	mg/m3
		effects			
Workers / employees	Human - dermal	Long term, systemic	DNEL	11	mg/kg
		effects			bw/day

- United Kingdom | WEL-TWA = Workplace Exposure Limit Long-term exposure limit 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).
- Ireland/Éire | OELV-8h = Occupational Exposure Limit Value 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | OELV-15min = Occupational Exposure Limit Value 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
- | BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)):
 ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of
 Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational
 Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European
 Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and
 Safety Executive (HSE), UK.
- (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- | Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |
- Malta | OELV-8h = Occupational Exposure Limit Value 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
- (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE).

- GB (RL) M

Page 10 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

| OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom). (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

If applicable

Face protection (EN 166).

Skin protection - Hand protection:

Use acid resistant protective gloves (EN ISO 374).

If applicable

Protective gloves in butyl rubber (EN ISO 374).

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Acid-resistant protection clothing (EN 13034)

Respiratory protection:

Normally not necessary.

- GB (RL) M

Page 11 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Liquid

Yellow

Characteristic

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

There is no information available on this parameter.

Lower explosion limit:

Upper explosion limit:

There is no information available on this parameter.

Auto-ignition temperature:

There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

pH:

Kinematic viscosity: There is no information available on this parameter.

Solubility: Soluble

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 1,09 g/l

Relative vapour density:

There is no information available on this parameter.

Particle characteristics: Does not apply to liquids.

9.2 Other information

Corrosive to metals: There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity

Product corrodes metals.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Avoid contact with strong alkalis (exothermic reaction possible).

Avoid contact with certain metals e.g. aluminium (development of hydrogen gas possible).

10.4 Conditions to avoid

See also section 7.

None known

10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with certain metals e.g. aluminium.

Avoid contact with acid sensitive materials.

- GB (RL) M

Page 12 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Possibly more information on h	ieaith ellects,	see Section	Z. I (Classification	on).		
Art.: 311999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	500	mg/kg			
Acute toxicity, by oral route:	LD50	300-2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Skin corrosion/irritation:				Rabbit		Skin Corr. 1B
Serious eye damage/irritation:				Rabbit		Eye Dam. 1
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative

(B) (R) (M)

Page 13 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004 Valid from: 11.03.2024

PDF print date: 15.03.2024 Acid Shampoo A Art.: 311999

Symptoms:		respiratory
		distress,
		vomiting,
		coughing,
		collapse,
		cramps,
		mucous
		membrane
		irritation, shock

Methanesulphonic acid Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	648,7	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	The toxicity is determined by the corrosivity of the product.
Acute toxicity, by oral route:	ATE	648,7	mg/kg			oo p. oaao
Acute toxicity, by dermal route:	ATE	1100	mg/kg			
Acute toxicity, by dermal route:	LD50	>1000-<2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	The toxicity is determined by the corrosivity of the product.
Acute toxicity, by inhalation:	LC50	1,1-1,4	mg/l/6h	Rat		•
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Skin Corr. 1B
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizisin
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity:	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Develop mental Toxicity Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1805	mg/kg	Rat	5 /	
Symptoms:						asthmatic symptoms, respiratory distress, burning of the membranes of the nose and throat, cornea opacity, coughing, headaches, dizziness, nausea and vomiting.

2-Butoxyethanol									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	ATE	1200	mg/kg						
Acute toxicity, by dermal	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute				
route:					Dermal Toxicity)				

(B) (R) (M)

Page 14 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004 Valid from: 11.03.2024

PDF print date: 15.03.2024 Acid Shampoo A Art.: 311999

Acute toxicity, by inhalation:	ATE	3	mg/l			Vapours
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Aerosol
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL	Skin Irrit. 2, Product removes fat.
				D 11.	IRRITATION/CORRO SION)	F 1 " 0
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	720	mg/kg bw/d		,	
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	
Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousn
						s, annoyance coughing, headaches, gastrointestin disturbances, insomnia,
						mucous membrane irritation, dizziness, nausea

- GB (RL M)-

Page 15 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

Specific target organ toxicity -	NOAEL	<69	mg/kg	Rat	OECD 408 (Repeated
repeated exposure (STOT-			bw/d		Dose 90-Day Oral
RE), oral:					Toxicity Study in
					Rodents)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>300-2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	ATE	500	mg/kg		Ciai rexiety)	
Skin corrosion/irritation:	7112	000	mg/kg	Rabbit	OECD 404 (Acute	Irritant
				1100011	Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Risk of serious
damage/irritation:					Eye	damage to
9					Irritation/Corrosion)	eyes.
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	_
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:				Mammalian	Regulation (EC)	Negative
					440/2008 B.17 (IN	
					VITRO MAMMALIAN	
					CELL GENE	
					MUTATION TESTS	
					USING HPRT +	
					XPRT GENES)	
Germ cell mutagenicity:				Mouse	OECD 478 (Genetic	Negative
					Toxicology - Rodent	
					dominant Lethal Test)	
Carcinogenicity:				Rat	OECD 451	Negative
					(Carcinogenicity	
					Studies)	
Specific target organ toxicity -	NOEL	100	mg/kg	Rat	OECD 422	Negative
repeated exposure (STOT-			bw/d		(Combined Repeated	
RE), oral:					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
			<u> </u>		Test)	
Specific target organ toxicity -				Mouse	OECD 411	Negative
repeated exposure (STOT-					(Subchronic Dermal	
RE), dermal:					Toxicity - 90-day	
					Study)	

11.2. Information on other hazards

Acid Shampoo A Art.: 311999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

- GB (RL) M

Page 16 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Acid Shampoo A Art.: 311999				,	,		
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	·						n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							The
degradability:							surfactant(s)
							contained in
							this mixture
							complies(compl
							y) with the
							biodegradability
							criteria as laid
							down in
							Regulation
							(EC)
							No.648/2004
12.3. Bioaccumulative							on detergents.
potential:							n.u.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-
							elimination
							degree(complex
							ing organic
							substance)>=
Oth on information	AOV			0/			80%/28d: n.a.
Other information:	AOX			%			According to
							the recipe, contains no
							AOX.
							AUX.

Phosphoric acid									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:	LC50	96h	3,0 - 3,25	mg/l	Lepomis macrochirus				
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)			
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)			

- GB (RL M)-

Page 17 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

12.2. Persistence and				Not relevant for
degradability:				inorganic
				substances.

Methanesulphonic aci				_			
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	73	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	70	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	96h	7,2-20	mg/l	Selenastrum	OECD 201	
					capricornutum	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		10d	84	%		OECD 301 F	
degradability:						(Ready	
						Biodegradability -	
						Manometric	
						Respirometry	
40.0 Danistana and		00-1	00.400	0/		Test)	D 101.
12.2. Persistence and		28d	90-100	%		OECD 301 A	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						DOC Die-Away	
12.3. Bioaccumulative	Log Pow		-2,38			Test)	Not to be
	Log Pow		-2,36				
potential:							expectedcaculat
Taxiaity ta baataria	EC50	20min	. 1000		activated aludge	OECD 209	ed
Toxicity to bacteria.	EC30	30111111	>1000	mg/i	activated sludge		
						, ,	
Toxicity to bacteria:	ECSU	30min	>1000	mg/l	activated sludge	(Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

2-Butoxyethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204	
						(Fish, Prolonged	
						Toxicity Test -	
						14-Day Study)	
12.1. Toxicity to	EC50	48h	1550	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211	
daphnia:						(Daphnia magna	
						Reproduction	
						Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	

- GB (RL M)

Page 18 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004 Valid from: 11.03.2024

Valid from: 11.03.2024 PDF print date: 15.03.2024

12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	95	%		OECD 301 E	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Modified OECD	
12.2. Persistence and		204	. 00	0/		Screening Test) OECD 302 B	Deadily
		28d	>99	%			Readily
degradability:						(Inherent Biodegradability -	biodegradable
						Zahn-	
						Wellens/EMPA	
						Test)	
12.3. Bioaccumulative potential:	BCF		3,2				Slight
12.3. Bioaccumulative	Log Pow		0,81			OECD 107	Not to be
potential:						(Partition	expected
						Coefficient (n-	
						octanol/water) -	
						Shake Flask	
40.4 Malatita da anti-	11 (11		0.00000	-4*0/		Method)	
12.4. Mobility in soil:	H (Henry)		0,00000	atm*m3/ mol			
12.5. Results of PBT			10	11101			No PBT
and vPvB assessment							substance, No
							vPvB
							substance
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1-10	mg/l	Brachydanio rerio	OECD 203	
						(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	>1-10	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	>0,1-1	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and						OECD 301 D	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Closed Bottle	
						Test)	
12.2. Persistence and		28d	67,5	%	activated sludge	OECD 301 B	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Co2 Evolution	
						Test)	
12.3. Bioaccumulative potential:	Log Pow		2,7				calculated value
12.3. Bioaccumulative							Not to be
potential:							expected
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

KochChemie⁶ ExcellenceForExperts.

GB (RL) M

Page 19 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU) 20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1760

14.2. UN proper shipping name:

UN 1760 CORROSIVE LIQUID, N.O.S. (PHOSPHORIC ACID, METHANESULFONIC ACID)

14.3. Transport hazard class(es):

14.4. Packing group: Ш

14.5. Environmental hazards: Not applicable

Tunnel restriction code: Ε Classification code: C9 LQ: 1 L Transport category:

Transport by sea (IMDG-code)

14.1. UN number or ID number: 1760

14.2. UN proper shipping name:

UN 1760 CORROSIVE LIQUID, N.O.S. (PHOSPHORIC ACID, METHANESULFONIC ACID)

14.3. Transport hazard class(es): 14.4. Packing group: Ш

14.5. Environmental hazards: Not applicable

IMDG Code segregation group 1 - Acids

Marine Pollutant: Not applicable EmS: F-A, S-B

Segregation:

Transport by air (IATA)

14.1. UN number or ID number: 1760

14.2. UN proper shipping name:

UN 1760 Corrosive liquid, n.o.s. (PHOSPHORIC ACID, METHANESULFONIC ACID)

14.3. Transport hazard class(es): 8 14.4. Packing group: Ш

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.











- GB (RL) M

Page 20 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

5 %

REGULATION (EC) No 648/2004

5 % or over but less than 15 % phosphates less than 5 % cationic surfactants

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Dam. 1, H318	Classification based on the pH value.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Met. Corr. 1, H290	Classification based on test data.
Skin Corr. 1, H314	Classification based on the pH value.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

- GB (RL M)

Page 21 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

H411 Toxic to aquatic life with long lasting effects.

Eye Dam. — Serious eye damage

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Met. Corr. — Substance or mixture corrosive to metals Skin Corr. — Skin corrosion

Acute Tox. — Acute toxicity - oral Acute Tox. — Acute toxicity - dermal

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Acute Tox. — Acute toxicity - inhalation

Skin Irrit. — Skin irritation Eye Irrit. — Eye irritation

Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

_GB (RL M)-

Page 22 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight mg/kg wwt mg/kg wet weight

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

-GB (RL M)-

Page 23 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0005

Replacing version dated / version: 20.11.2023 / 0004

Valid from: 11.03.2024 PDF print date: 15.03.2024

Acid Shampoo A Art.: 311999 Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90 © by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.