- GB (RL M)

Page 1 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Cabriodach-Versiegelung

Art.: 234412

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Impregnation agent for convertible tops

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna

Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26

info@koch-chemie.com www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

(RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)

+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.

Skin Irrit. 2 H315-Causes skin irritation.

And The Local Manufacture 1

Asp. Tox. 1 H304-May be fatal if swallowed and enters airways.

STOT SE 3 H336-May cause drowsiness or dizziness.

Aquatic Chronic 2 H411-Toxic to aquatic life with long lasting effects.

- GB (RL) M

Page 2 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

Aerosol 1 H222-Extremely flammable aerosol.

Aerosol 1 H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



H319-Causes serious eye irritation. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Caution! You must comply! Damage to health possible due to inhaling! Only use outdoors or in well-ventilated rooms! Spray only for a few seconds! Spray leather and textile products only outdoors and let them air well! Keep away from children! Propan-2-ol

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C6, isoalkanes, <5% n-hexane Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Propan-2-ol		
Registration number (REACH)	01-2119457558-25-XXXX	
Index	603-117-00-0	
EINECS, ELINCS, NLP, REACH-IT List-No.	200-661-7	
CAS	67-63-0	

- GB (RL M)-

Page 3 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Eye Irrit. 2, H319
	STOT SE 3. H336

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
Registration number (REACH)	01-2119484651-34-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	931-254-9
CAS	(64742-49-0)
content %	10-<15
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%	
aromatics	
Registration number (REACH)	01-2119471843-32-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	927-241-2
CAS	
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 3, H226
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 3, H412

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119475515-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	927-510-4
CAS	
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Heptane	Substance for which an EU exposure limit value
	applies.
Registration number (REACH)	
Index	601-008-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	205-563-8
CAS	142-82-5
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Methylcyclohexane	
Registration number (REACH)	
Index	601-018-00-7
EINECS, ELINCS, NLP, REACH-IT List-No.	203-624-3

GB (RL M)-

Page 4 of 44 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

CAS	108-87-2
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Isopropyl acetate	
Registration number (REACH)	01-2119537214-46-XXXX
Index	607-024-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	203-561-1
CAS	108-21-4
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 2, H225
	Eye Irrit. 2, H319
	STOT SE 3, H336

n-butyl acetate	Substance for which an EU exposure limit value
	applies.
Registration number (REACH)	01-2119485493-29-XXXX
Index	607-025-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	204-658-1
CAS	123-86-4
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 3, H226
	STOT SE 3, H336

Cyclohexane	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119463273-41-XXXX
Index	601-017-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-806-2
CAS	110-82-7
content %	<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

2-methylhexane	Substance for which an EU exposure limit value applies.			
Registration number (REACH)				
Index	601-008-00-2			
EINECS, ELINCS, NLP, REACH-IT List-No.	209-730-6			
CAS	591-76-4			
content %	<2,5			
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225			
factors	Skin Irrit. 2, H315			
	STOT SE 3, H336			
	Asp. Tox. 1, H304			
	Aquatic Acute 1, H400 (M=1)			
	Aquatic Chronic 1, H410 (M=1)			

3-methylhexane	Substance for which an EU exposure limit value
o moury moxano	Cubotance for Willow all Lo exposure mint value
	applies
	applies.

- GB (RL) M)-

Page 5 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Registration number (REACH)	
Index	601-008-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	209-643-3
CAS	589-34-4
content %	<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119486291-36-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	926-605-8
CAS	
content %	<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 2, H225
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Cyclopentane	
Registration number (REACH)	
Index	601-030-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	206-016-6
CAS	287-92-3
content %	<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 2, H225
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 3, H412

2,3-dimethylpentane	Substance for which an EU exposure limit value		
	applies.		
Registration number (REACH)			
Index	601-008-00-2		
EINECS, ELINCS, NLP, REACH-IT List-No.	209-280-0		
CAS	565-59-3		
content %	<1		
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225		
factors	Skin Irrit. 2, H315		
	STOT SE 3, H336		
	Asp. Tox. 1, H304		
	Aquatic Acute 1, H400 (M=1)		
	Aquatic Chronic 1, H410 (M=1)		

n-hexane	Substance for which an EU exposure limit value applies.		
Registration number (REACH)			
Index	601-037-00-0		
EINECS, ELINCS, NLP, REACH-IT List-No.	203-777-6		
CAS	110-54-3		
content %	<1		

- GB (RL M)-

Page 6 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

OL 15 (1 D L 1 (50) 4070/0000 (OLD) M	Flore Lie 0 11005
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Skin Irrit. 2, H315
	Repr. 2, H361f
	STOT SE 3, H336
	STOT RE 1, H372 (nervous system)
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

3-ethylpentane	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-008-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	210-529-0
CAS	617-78-7
content %	<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

- GB (RL) M

Page 7 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

eyes, reddened watering eyes Coughing Headaches Dizziness

mental confusion

drying of the skin.

Dermatitis (skin inflammation)

Nausea Vomiting

Danger of aspiration.

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

Danger of bursting (explosion) when heated

Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

- GB (RL M)-

Page 8 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Observe special storage conditions.

Do not store with flammable or self-igniting materials.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well-ventilated place.

Store cool.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

© Chemical Name	Propan-2-ol		
WEL-TWA: 400 ppm (999 mg/m	13)	WEL-STEL: 500 ppm (1250 mg/m3)	
Monitoring procedures:	-	Draeger - Alcohol 25/a i-Propanol (81 01 631)	
	-	Compur - KITA-122 SA(C) (549 277)	
	-	- Compur - KITA-150 U (550 382)	
		DFG (D) (Loesungsmittelgemische), DFG (E) (Solvent	mixtures 6) - 2013, 2002 -
	-	 EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) 	
	-	- NIOSH 1400 (ALCOHOLS I) - 1994	
	-	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (S	CREENING)) - 1996

GB (RL) M Page 9 of 44 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 12.03.2025 / 0004 Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung Art.: 234412 Draeger - Alcohol 100/a (CH 29 701) BMGV: ---Other information: Chemical Name Propan-2-ol OELV-15min: 400 ppm OELV-8h: 200 ppm Draeger - Alcohol 25/a i-Propanol (81 01 631) Monitoring procedures: Compur - KITA-122 SA(C) (549 277) Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtures 6) - 2013, 2002 -EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) NIOSH 1400 (ALCOHOLS I) - 1994 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 Draeger - Alcohol 100/a (CH 29 701) BLV: 40 mg/l (acetone, U, d) (ACGIH-BEI) Other information: Skin Chemical Name Hydrocarbons, C6, isoalkanes, <5% n-hexane WEL-TWA: 800 mg/m3 WEL-STEL: ------Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BMGV: ---Other information: (OEL acc. to RCPmethod, paragraphs 84-87, EH40) Chemical Name Hydrocarbons, C6, isoalkanes, <5% n-hexane OELV-8h: 100 ppm (573 mg/m3) ("Stoddard OELV-15min: solvent", [White spirit]) Draeger - Hydrocarbons 0,1%/c (81 03 571) Monitoring procedures: Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BLV: ---Other information: ---[⊕] Chemical Name Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics WEL-TWA: 800 mg/m3 WEL-STEL: Draeger - Hydrocarbons 0,1%/c (81 03 571) Monitoring procedures: Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BMGV: ---(OEL acc. to RCP-Other information: method, paragraphs 84-87, EH40) Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics OELV-8h: 100 ppm (573 mg/m3) ("Stoddard OELV-15min: solvent", [White spirit]) Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BLV: ---Other information: © Chemical Name Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics WEL-TWA: 800 mg/m3 WEL-STEL: Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BMGV: ---Other information: (OEL acc. to RCPmethod, paragraphs 84-87, EH40) Chemical Name Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics OELV-8h: 100 ppm (573 mg/m3) ("Stoddard OELV-15min: solvent", [White spirit]) Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BLV: ---Other information: © Chemical Name Heptane

KochChemie[®] ExcellenceForExperts.

GB (RL) (M Page 10 of 44 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 12.03.2025 / 0004 Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung Art.: 234412 WEL-TWA: 2085 mg/m3 (500 ppm) (WEL-TWA. WEL-STEL: ---Monitoring procedures: Compur - KITA-113 SB(C) (549 368) INSHT MTA/MA-029/A92 (Determination of aliphatic hydrocarbons (n-hexane, nheptane, n-octane, n-nonane) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 51-1 (2004)NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 2004 Other information: ---BMGV: --- Chemical Name Heptane OELV-15min: OELV-8h: 500 ppm (2085 mg/m3) (OELV-8h, Monitoring procedures: Compur - KITA-113 SB(C) (549 368) INSHT MTA/MA-029/A92 (Determination of aliphatic hydrocarbons (n-hexane, nheptane, n-octane, n-nonane) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 51-1 (2004)NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 2004 BLV: ---Other information: IOELV M Chemical Name Heptane OELV-8h: 500 ppm (2085 mg/m3) (OELV-8h, OELV-ST: ---EU) Monitoring procedures: Compur - KITA-113 SB(C) (549 368) INSHT MTA/MA-029/A92 (Determination of aliphatic hydrocarbons (n-hexane, nheptane, n-octane, n-nonane) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 51-1 NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 2004 BMGV: ---Other information: Chemical Name Methylcyclohexane WEL-TWA: 800 mg/m3 (>=C7 cycloalkanes) WEL-STEL: ---Monitoring procedures: Compur - KITA-113 SB(C) (549 368) NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 BMGV: ---Other information: Chemical Name Methylcyclohexane OELV-8h: 400 ppm (1600 mg/m3) OELV-15min: ---Compur - KITA-113 SB(C) (549 368) Monitoring procedures: NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 BLV: ---Other information: © Chemical Name Isopropyl acetate WEL-STEL: 200 ppm (849 mg/m3) WEL-TWA: ---Monitoring procedures: Compur - KITA-111 U (549 178) Compur - KITA-139 SB(C) (549 731) NIOSH 1454 (Isopropyl acetate) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 14-4 (2004) NIOSH 1460 (ISOPROPYL ACETATE) - 2003 BMGV: ---Other information: --- Chemical Name Isopropyl acetate OELV-8h: 100 ppm OELV-15min: 150 ppm Monitoring procedures: Compur - KITA-111 U (549 178) Compur - KITA-139 SB(C) (549 731) NIOSH 1454 (Isopropyl acetate) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 14-4 (2004) NIOSH 1460 (ISOPROPYL ACETATE) - 2003 BLV: ---Other information: ---

KochChemie[®] ExcellenceForExperts.

^{®®} № M — — — Page 11 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 12.03.2025 / 0004 Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung Art.: 234412 **Chemical Name** n-butyl acetate WEL-TWA: 150 ppm (724 mg/m3) (WEL-TWA), WEL-STEL: 200 ppm (966 mg/m3) (WEL-STEL), 50 ppm (241 mg/m3) (EU) 150 ppm (723 mg/m3) (EU) Monitoring procedures: Compur - KITA-138 U (548 857) Compur - KITA-139 SB(C) (549 731) NIOSH 1450 (ESTERS 1) - 2003 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007 Other information: ---BMGV: --- Chemical Name n-butyl acetate OELV-8h: 50 ppm (241 mg/m3) (OELV-8h, EU) OELV-15min: 150 ppm (723 mg/m3) (OELV-15min, EU) Monitoring procedures: Compur - KITA-138 U (548 857) Compur - KITA-139 SB(C) (549 731) NIOSH 1450 (ESTERS 1) - 2003 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007 Other information: IOELV BLV: ---M Chemical Name n-butyl acetate OELV-8h: 50 ppm (241 mg/m3) (OELV-8h, EU) OELV-ST: 150 ppm (723 mg/m3) (OELV-ST, EU) Compur - KITA-138 U (548 857) Monitoring procedures: Compur - KITA-139 SB(C) (549 731) NIOSH 1450 (ESTERS 1) - 2003 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007 BMGV: ---Other information: ---© Chemical Name Cyclohexane WEL-TWA: 350 mg/m3 (100 ppm) (WEL-TWA), WEL-STEL: 1050 mg/m3 (300 ppm) 700 mg/m3 (200 ppm) (EU) Draeger - Cyclohexane 40/a (81 03 671) Monitoring procedures: Compur - KITA-115 S (551 133) NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 OSHA 1022 (Cyclohexane) - 2018 BMGV: ---Other information: --- Chemical Name Cyclohexane OELV-8h: 200 ppm (700 mg/m3) (OELV-8h, EU) OELV-15min: Draeger - Cyclohexane 40/a (81 03 671) Monitoring procedures: Compur - KITA-115 S (551 133) NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 OSHA 1022 (Cyclohexane) - 2018 BLV: ---Other information: IOELV M Chemical Name Cyclohexane OELV-8h: 200 ppm (700 mg/m3) (OELV-8h, EU) OELV-ST: ---Draeger - Cyclohexane 40/a (81 03 671) Monitoring procedures: Compur - KITA-115 S (551 133) NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 OSHA 1022 (Cyclohexane) - 2018 BMGV: ---Other information: --- Chemical Name 2-methylhexane WEL-STEL: ---WEL-TWA: 1200 mg/m3 (>=C7 normal and branched chain alkanes) Draeger - Hydrocarbons 0,1%/c (81 03 571) Monitoring procedures: Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) Other information: ---BMGV: ---

GB (RL) (M

Page 12 of 44 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 12.03.2025 / 0004 Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung Art.: 234412 **Chemical Name** 2-methylhexane OELV-8h: 100 ppm (573 mg/m3) ("Stoddard OELV-15min: --solvent", [White spirit]) Draeger - Hydrocarbons 0,1%/c (81 03 571) Monitoring procedures: Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BLV: ---Other information: --- Chemical Name 3-methylhexane WEL-STEL: ---WEL-TWA: 1200 mg/m3 (>=C7 normal and branched chain alkanes) Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BMGV: ---Other information: ---Chemical Name 3-methylhexane OELV-8h: 100 ppm (573 mg/m3) ("Stoddard OELV-15min: --solvent", [White spirit]) Draeger - Hydrocarbons 0,1%/c (81 03 571) Monitoring procedures: Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BLV: ---Other information: --- Chemical Name Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane WEL-TWA: 350 mg/m3 (cyclohexane) WEL-STEL: ---Draeger - Hydrocarbons 0,1%/c (81 03 571) Monitoring procedures: Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BMGV: ---Other information: --- Chemical Name Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane OELV-8h: 100 ppm (573 mg/m3) ("Stoddard OELV-15min: solvent", [White spirit]) Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BLV: ---Other information: Chemical Name Cyclopentane WEL-TWA: 1800 mg/m3 (C5-C6 cycloalkanes) WEL-STEL: ---Draeger - Hydrocarbons 0,1%/c (81 03 571) Monitoring procedures: Draeger - Hydrocarbons 2/a (81 03 581) BMGV: ---Other information: (OEL acc. to RCPmethod, paragraphs 84-87, EH40) Chemical Name Cyclopentane OELV-8h: 600 ppm (1720 mg/m3) OELV-15min: ---Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) BLV: ---Other information: ---Chemical Name
2,3-dimethylpentane WEL-TWA: 1200 mg/m3 (>=C7 normal and WEL-STEL: branched chain alkanes) Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581) Compur - KITA-187 S (551 174) BMGV: ---Other information: ---Chemical Name 2,3-dimethylpentane OELV-8h: 100 ppm (573 mg/m3) ("Stoddard OELV-15min: --solvent", [White spirit]) Monitoring procedures: Draeger - Hydrocarbons 0,1%/c (81 03 571) Draeger - Hydrocarbons 2/a (81 03 581)

GB (RL) (M Page 13 of 44 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 12.03.2025 / 0004 Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung Art.: 234412 Compur - KITA-187 S (551 174) BLV: ---Other information: ©B Chemical Name n-hexane WEL-TWA: 72 mg/m3 (20 ppm) (WEL-TWA, EU) WEL-STEL: Draeger - Hexane 10/a (81 03 681) Monitoring procedures: Compur - KITA-113 SA (549 350) Compur - KITA-113 SB (549 368) Compur - KITA-113 SC (503 787) DFG Meth. Nr. 1 (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtures 1) -2014. 2002 DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2014 DFG Meth. Nr. 6 (D) (Loesungsmittelgemische) - 2014 INSHT MTA/MA-029/A92 (Determination of aliphatic hydrocarbons (n-hexane, nheptane, n-octane, n-nonane) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 26-1 (2004)NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 OSHA PV2248 (n -Hexane) - 1995 BMGV: ---Other information: ---Chemical Name n-hexane OELV-8h: 20 ppm (72 mg/m3) (OELV-8h, EU) OELV-15min: ---Monitoring procedures: Draeger - Hexane 10/a (81 03 681) Compur - KITA-113 SA (549 350) Compur - KITA-113 SB (549 368) Compur - KITA-113 SC (503 787) DFG Meth. Nr. 1 (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtures 1) -2014, 2002 DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2014 DFG Meth. Nr. 6 (D) (Loesungsmittelgemische) - 2014 INSHT MTA/MA-029/A92 (Determination of aliphatic hydrocarbons (n-hexane, nheptane, n-octane, n-nonane) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 26-1 NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 OSHA PV2248 (n - Hexane) - 1995 BLV: 0,4 mg/l (2,5-Hexanedion in urine, end of shift at end of workweek) Other information: Skin, IOELV (ACGIH-BEI) Chemical Name n-hexane OELV-8h: 20 ppm (72 mg/m3) (OELV-8h, EU) OELV-ST: Draeger - Hexane 10/a (81 03 681) Monitoring procedures: Compur - KITA-113 SA (549 350) Compur - KITA-113 SB (549 368) Compur - KITA-113 SC (503 787) DFG Meth. Nr. 1 (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtures 1) -2014, 2002 DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2014 DFG Meth. Nr. 6 (D) (Loesungsmittelgemische) - 2014 INSHT MTA/MA-029/A92 (Determination of aliphatic hydrocarbons (n-hexane, nheptane, n-octane, n-nonane) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 26-1 NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003

NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996

OELV-8h: 250 ppm

BLV: ---

Monitoring procedures:

GB (RL) (M Page 14 of 44 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 12.03.2025 / 0004 Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung Art.: 234412 NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 OSHA PV2248 (n - Hexane) - 1995 BMGV: ---Other information: Chemical Name 3-ethylpentane WEL-TWA: 1200 mg/m3 (>=C7 normal and WEL-STEL: --branched chain alkanes) Monitoring procedures: Other information: BMGV: © Chemical Name 3-ethylpentane OELV-8h: 100 ppm (573 mg/m3) ("Stoddard OELV-15min: --solvent", [White spirit]) Monitoring procedures: BLV: Other information: © Chemical Name Butane WEL-STEL: 750 ppm (1810 mg/m3) WEL-TWA: 600 ppm (1450 mg/m3) Monitoring procedures: Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993 Other information: BMGV: ---Chemical Name Butane OELV-8h: ---OELV-15min: 1000 ppm ---Compur - KITA-221 SA (549 459) Monitoring procedures: OSHA PV2010 (n-Butane) - 1993 BLV: ---Other information: Chemical Name Propane WEL-TWA: 1000 ppm (ACGIH) WEL-STEL: ------Monitoring procedures: Compur - KITA-125 SA (549 954) OSHA PV2077 (Propane) - 1990 BMGV: ---Other information: Chemical Name Isobutane WEL-TWA: 1000 ppm (EX) (ACGIH) WEL-STEL: ---Compur - KITA-113 SB(C) (549 368) Monitoring procedures: BMGV: Other information: Chemical Name Isobutane OELV-15min: 1000 ppm OELV-8h: Compur - KITA-113 SB(C) (549 368) Monitoring procedures: Other information: (RL) Chemical Name But-1-ene OELV-15min: ---OELV-8h: 250 ppm Monitoring procedures: Draeger - Olefine 0,05%/a Butylene (CH 31 201) Draeger - Olefine 0,05%/a Propylene (CH 31 201) BLV: ---Other information: Chemical Name Butene, mixed-1-and-2-isomers

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	

Draeger - Olefine 0,05%/a Butylene (CH 31 201) Draeger - Olefine 0,05%/a Propylene (CH 31 201) ---

Other information:

OELV-15min:

- GB (RL M)-

Page 15 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

	Environment - sediment, freshwater		PNEC	552	mg/kg dw
	Environment - sediment,		PNEC	552	mg/kg dw
	marine Environment - soil		PNEC	28	mg/kg dw
	Environment - sewage treatment plant		PNEC	2251	mg/l
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l
	Environment - oral (animal feed)		PNEC	160	mg/kg feed
Consumer	Human - dermal	Long term, systemic effects	DNEL	319	mg/kg bw/day
Consumer	Human - inhalation	Long term, systemic effects	DNEL	89	mg/m3
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	888	mg/kg bw/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	500	mg/m3

Hydrocarbons, C6, isoalkanes, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m3	

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	46	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	46	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	77	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics							
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note	
	Environmental		r				
	compartment						

- GB (RL M)-

Page 16 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Consumer	Human - oral	Long term, systemic	DNEL	149	mg/kg	
		effects			bw/day	
Consumer	Human - dermal	Long term, systemic	DNEL	149	mg/kg	
		effects			bw/day	
Consumer	Human - inhalation	Long term, systemic	DNEL	447	mg/m3	
		effects				
Workers / employees	Human - dermal	Long term, systemic	DNEL	300	mg/kg	
		effects			bw/day	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	2085	mg/m3	
		effects				

Heptane							
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	447	mg/m3		
Consumer	Human - dermal	Long term, systemic effects	DNEL	149	mg/kg bw/d		
Consumer	Human - oral	Long term, systemic effects	DNEL	149	mg/kg bw/d		
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2085	mg/m3		
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/d		

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r ·			
	compartment					
	Environment - freshwater		PNEC	0,22	mg/l	
	Environment - marine		PNEC	0,022	mg/l	
	Environment - soil		PNEC	0,35	mg/kg bw/d	
	Environment - sewage treatment plant		PNEC	190	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg body weight/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	26	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	252	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	420	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	43	mg/kg body weight/day	

n-butyl acetate							
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note	
	Environmental		r				
	compartment						
	Environment - freshwater		PNEC	0,18	mg/l		
	Environment - marine		PNEC	0,018	mg/l		

- GB (RL M)-

Page 17 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 $\,/\,0003$

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

	Environment - periodic release		PNEC	0,36	mg/l
	Environment - sediment, freshwater		PNEC	0,981	mg/kg
	Environment - sediment, marine		PNEC	0,0981	mg/kg
	Environment - soil		PNEC	0,0903	mg/kg
	Environment - sewage treatment plant		PNEC	35,6	mg/l
Consumer	Human - dermal	Long term, systemic effects	DNEL	6	mg/kg
Consumer	Human - inhalation	Short term, systemic effects	DNEL	300	mg/m3
Consumer	Human - inhalation	Long term, systemic effects	DNEL	35,7	mg/m3
Consumer	Human - dermal	Short term, systemic effects	DNEL	6	mg/kg bw/day
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/day
Consumer	Human - oral	Short term, systemic effects	DNEL	2	mg/kg bw/day
Consumer	Human - inhalation	Short term, local effects	DNEL	300	mg/m3
Consumer	Human - inhalation	Long term, local effects	DNEL	35,7	mg/m3
Workers / employees	Human - dermal	Long term, local effects	DNEL	11	mg/kg body weight/day
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	600	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	300	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/d
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	11	mg/kg bw/day
Workers / employees	Human - inhalation	Short term, local effects	DNEL	600	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	300	mg/m3

Cyclohexane						
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	44,7	μg/l	
	Environment - marine		PNEC	4,47	μg/l	
	Environment - water,		PNEC	0,9	μg/l	
	sporadic (intermittent)					
	release					
	Environment - sediment,		PNEC	3,6	mg/kg dry	
	freshwater				weight	
	Environment - soil		PNEC	0,694	mg/kg dry	
					weight	
	Environment - sewage		PNEC	3,24	mg/l	
	treatment plant					
	Environment - sediment,		PNEC	0,36	mg/kg	
	marine					
Consumer	Human - inhalation	Short term, systemic	DNEL	412	mg/m3	
		effects				

-GB (RL M)-

Page 18 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Consumer	Human - inhalation	Short term, local effects	DNEL	412	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	1186	mg/kg body weight/day
Consumer	Human - inhalation	Long term, systemic effects	DNEL	206	mg/m3
Consumer	Human - oral	Long term, systemic effects	DNEL	59,4	mg/kg body weight/day
Consumer	Human - inhalation	Long term, local effects	DNEL	206	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	700	mg/m3
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	700	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	700	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2016	mg/kg body weight/day
Workers / employees	Human - inhalation	Long term, local effects	DNEL	700	mg/m3

Hydrocarbons, C6-C7, is	soalkanes, cyclics, <5% n-h	nexane				
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/kg	

n-hexane							
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	16	mg/m3		
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,3	mg/kg bw/day		
Consumer	Human - oral	Long term, systemic effects	DNEL	4	mg/kg bw/day		
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	75	mg/m3		
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day		

- GB (RL) (M)

Page 19 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	1,38	mg/l	
	Environment - marine		PNEC	1,38	mg/l	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	860	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	860	mg/m3	

- United Kingdom | WEL-TWA = Workplace Exposure Limit Long-term exposure limit 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
- (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.
- Ireland/Éire | OELV-8h = Occupational Exposure Limit Value 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | OELV-15min = Occupational Exposure Limit Value 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- | BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)):
 | ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of
 | Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational
 | Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European
 | Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and
 | Safety Executive (HSE), UK.
- (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- | Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Skin = Can be absorbed through skin. Asphx = asphyxiant. Sens = The substance can cause sensitisation. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.
- (EÚ) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance

- GB (RL) M

Page 20 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

- Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom). (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE), (EU15) = Substantial contribution to the total body burden via dermal exposure possible.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0.4

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

KochChemie⁶ **ExcellenceForExperts.**

GB (RL) M

Page 21 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Colourless Odour: Ester

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: -44,5 °C (The boiling point of the mixture was not tested, but

complies with the ingredient with the lowest value.)

Flammability: Does not apply to aerosols. Lower explosion limit: 0,6 Vol-% Upper explosion limit: 12 Vol-%

-97 °C (The flash-point of the mixture was not tested, but Flash point:

complies with the ingredient with the lowest value.) Auto-ignition temperature: Does not apply to aerosols.

There is no information available on this parameter. Decomposition temperature:

рН: Mixture is non-soluble (in water).

<=20,5 mm2/s (40°C)

Kinematic viscosity:

Insoluble

Does not apply to mixtures.

2,5-4,0 bar 0,65 g/ml

Does not apply to aerosols. Does not apply to aerosols.

9.2 Other information

Relative vapour density:

Particle characteristics:

Density and/or relative density:

No information available at present.

Partition coefficient n-octanol/water (log value):

SECTION 10: Stability and reactivity

10.1 Reactivity

Solubility:

Vapour pressure:

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

- GB (RL M

Page 22 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Cabriodach-Versiegelung						
Art.: 234412						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	-					n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	12800-13900	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	> 25	mg/l/6h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Acute toxicity, by inhalation:	LC50	46600	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Irrit. 2
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	

- GB (RL M)

Page 23 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Chinese hamster
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	500	mg/kg/d	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative (oral, 7 weeks)
Reproductive toxicity:	NOAEL	853	mg/kg bw/d	Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Negative
Reproductive toxicity:	NOAEL	400	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336, May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Specific target organ toxicity - repeated exposure (STOT- RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT- RE), inhalat.:	NOAEL	5000	ppm	Rat	,	Vapours (OECD 451)
Aspiration hazard: Symptoms:						No breathing difficulties, unconsciousnes s, vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes

Hydrocarbons, C6, isoalkanes, <5% n-hexane							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute		
					Oral Toxicity)		
Acute toxicity, by dermal	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute		
route:					Dermal Toxicity)		
Acute toxicity, by inhalation:	LC50	259354	mg/m3	Rat	OECD 403 (Acute	Vapours	
					Inhalation Toxicity)		
Skin corrosion/irritation:						Skin Irrit. 2	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin	
sensitisation:					Sensitisation - Local	contact)	
					Lymph Node Assay)		

- GB (RL M)-

Page 24 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Reproductive toxicity:	NOAEC	10560	mg/m3	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	
Aspiration hazard:						Asp. Tox. 1
Symptoms:						drowsiness, unconsciousnes s, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4	Rat	OECD 403 (Acute	Analogous
			h		Inhalation Toxicity)	conclusion,
						Maximum
						achievable
						concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
					•	cause skin
						dryness or
						cracking.
Serious eye				Rabbit	OECD 405 (Acute	Mild irritant
damage/irritation:					Eye	(Analogous
Ğ					Irritation/Corrosion)	conclusion)
Serious eye				Rabbit	OECD 405 (Acute	Mild irritant,
damage/irritation:					Eye	Analogous
Ğ					Irritation/Corrosion)	conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
3 ,				typhimurium	Reverse Mutation	
				71	Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative,
5 ,					Mammalian `	Analogous
					Chromosome	conclusion
					Aberration Test)	
Germ cell mutagenicity:				Mouse	OECD 474	Negative,
5					(Mammalian	Analogous
					Erythrocyte	conclusion
					Micronucleus Test)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative,
					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion

- GB (RL M)-

Page 25 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025

PDF print date: 12.03.2025 Cabriodach-Versiegelung

Germ cell mutagenicity:	Rat	OECD 478 (Genetic Negative Toxicology - Rodent Analogo dominant Lethal Test) conclusi	us
Germ cell mutagenicity:		OECD 479 (Genetic Toxicology - In Vitro Analogo Sister Chromatid Exchange assay in Mammalian Cells)	e, ous ionChin nster
Carcinogenicity:	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies) Negative Analogo conclusi	us
Reproductive toxicity:	Rat	OECD 414 (Prenatal Negative Developmental Analogo Toxicity Study) conclusi	ous ion
Reproductive toxicity:	Rat	OECD 415 (One- Generation Analogo Reproduction Toxicity conclusi Study)	ous
Specific target organ toxicity - single exposure (STOT-SE):		May cau drowsine dizzines	ess or
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) No indic of such a effect., Analogo conclusi	an
Specific target organ toxicity - repeated exposure (STOT- RE), inhalat.:	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study) Vapours indicatio such an Analogo conclusi	ons of effect., ous
Aspiration hazard:		Yes	
Symptoms:		drowsine unconso s, heart/cir disorde headach cramps, drowsine mucous membra irritation dizzines nausea	ciousnes rculatory rs, nes, ess, ane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute		
					Oral Toxicity)		
Acute toxicity, by dermal	LD50	>2800-3100	mg/kg	Rabbit	OECD 402 (Acute		
route:					Dermal Toxicity)		
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Vapours	
					Inhalation Toxicity)		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Irritant	
					Dermal		
					Irritation/Corrosion)		
Aspiration hazard:						Yes	

Page 26 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

Symptoms:		diarrhoea,
		headaches,
		dizziness,
		nausea and
		vomiting.

Heptane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>29,29	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					,	Irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Aspiration hazard:					,	Yes
Symptoms:						drowsiness, unconsciousnes s, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Skin corrosion/irritation:	'					Irritant
Serious eye						Mild irritant
damage/irritation:						
Aspiration hazard:						Yes
Symptoms:						eyes,
•						reddened,
						drowsiness,
						unconsciousne
						s, diarrhoea,
						coughing,
						collapse,
						headaches.
						cramps,
						stomach pain,
						fatigue,
						mucous
						membrane
						irritation,
						dizziness,
						nausea and
						vomiting.

Isopropyl acetate

- GB (RL M)-

Page 27 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Endpoint	Value	Unit	Organism	Test method	Notes
LD50	6750	mg/kg	Rat		
LD50	>20000	mg/kg	Rabbit		
LC50	68-136	mg/l	Rat		
					Repeated exposure may cause skin dryness or cracking.
			Rabbit		Irritant
			Guinea pig		Not sensitizising
				OECD 471 (Bacterial Reverse Mutation Test)	Negative
				,	No
					lack of appetite, eyes, reddened, drowsiness, unconsciousnes s, cornea opacity, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and
	LD50	LD50 6750 LD50 >20000	LD50 6750 mg/kg LD50 >20000 mg/kg	LD50 6750 mg/kg Rat LD50 >20000 mg/kg Rabbit LC50 68-136 mg/l Rat Rabbit	LD50 6750 mg/kg Rat

n-butyl acetate	T =	T			T =	T
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10760-13100	mg/kg	Rat	OECD 423 (Acute	Female
					Oral Toxicity - Acute	
					Toxic Class Method)	
Acute toxicity, by dermal	LD50	>17600	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>21,1	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
						cause skin
						dryness or
						cracking.
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:				Mouse	OECD 474	Negative
•					(Mammalian	
					Erythrocyte	
					Micronucleus Test)	

- GB (RL M)-

Page 28 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Reproductive toxicity:	NOAEC	9640	mg/m3		OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):					Study)	May cause drowsiness or dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg	Rat	Regulation (EC) 440/2008 B.26 (SUB- CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS))	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	500	ppm	Rat		
Symptoms:						unconsciousnes s, headaches, mucous membrane irritation, dizziness, nausea and vomiting.

Cyclohexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	14	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - single exposure (STOT-SE):	LOAEL	0,09	mg/l			May cause drowsiness or dizziness.
Aspiration hazard:						Yes

- GB (RL M)-

Page 29 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Symptoms:			lack of
			appetite,
			abdominal
			pain,
			drowsiness,
			unconsciousnes
			s, coughing,
			collapse,
			headaches,
			cramps,
			gastrointestinal
			disturbances,
			drowsiness,
			mucous
			membrane
			irritation,
			dizziness,
			nausea and
			vomiting.

Hydrocarbons, C6-C7, isoalk Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	16750	mg/kg	Rat	OECD 401 (Acute	Analogous
					Oral Toxicity)	conclusion
Acute toxicity, by dermal	LD50	3350	mg/kg	Rabbit	OECD 402 (Acute	Analogous
route:					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	> 20	mg/l/4h	Rat	OECD 403 (Acute	Vapours,
					Inhalation Toxicity)	Analogous
						conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
damago, imationi					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin
sensitisation:				Mouse	Sensitisation - Local	contact)
sensitisation.						Contact)
Corm call mutageniaitus				Salmonella	Lymph Node Assay) OECD 471 (Bacterial	Negotivo
Germ cell mutagenicity:						Negative
				typhimurium	Reverse Mutation	
				_	Test)	
Germ cell mutagenicity:				Rat	OECD 475	Negative
					(Mammalian Bone	
					Marrow Chromosome	
					Aberration Test)	
Carcinogenicity:					OECD 451	Negative
					(Carcinogenicity	
					Studies)	
Reproductive toxicity:					OECD 414 (Prenatal	Negative
'					Developmental	
					Toxicity Study)	
Specific target organ toxicity -					. charif clady)	May cause
single exposure (STOT-SE):						drowsiness or
single exposure (or or see).						dizziness.
Specific target organ toxicity -	NOAEC	10,504	mg/l	Rat	OECD 413	Vapours,
	INUAEC	10,304	mg/i	nal	(Subchronic Inhalation	
repeated exposure (STOT-						Analogous
RE), inhalat.:					Toxicity - 90-Day	conclusion
A : C					Study)	
Aspiration hazard:						Yes

-GB (RL M)-

Page 30 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Symptoms:		respiratory
		distress, drying
		of the skin.,
		drowsiness,
		annoyance,
		heart/circulatory
		disorders,
		coughing,
		headaches,
		cramps,
		drowsiness,
		mucous
		membrane
		irritation,
		dizziness,
		nausea and
		vomiting.

Cyclopentane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Skin corrosion/irritation:						Not irritant
Serious eye						Not irritant
damage/irritation:						
Respiratory or skin						Not sensitizising
sensitisation:						
Symptoms:						respiratory
						distress,
						unconsciousnes
						s, coughing,
						headaches,
						dizziness,
						nausea and
						vomiting.

n-hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	16000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	171,6	mg/l/1h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousnes s, blisters, cornea opacity, coughing, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, watering eyes, nausea

3-ethylpentane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

-GB (RL M)-

Page 31 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 $\,/\,0003$ Valid from: 12.03.2025

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Aspiration hazard:			Yes
Symptoms:			unconsciousnes
			s, vomiting,
			headaches,
			dizziness,
			nausea

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousnes, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye						Not irritant
damage/irritation:						
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	

- GB (RL M)-

Page 32 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT- RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	
Aspiration hazard: Symptoms:						No breathing difficulties, unconsciousnes s, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	
Aspiration hazard:						No

- GB (RL M)-

Page 33 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

Commentance		
Symptoms:		unconsciousnes
		s, frostbite,
		headaches,
		· ·
		cramps,
		dizziness,
		nausea and
		vomiting.

11.2. Information on other hazards

Cabriodach-Versiegelung	g					
Art.: 234412	_					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-
							elimination
							degree(complex
							ing organic
							substance)>=
							80%/28d: No
Other information:	AOX			%			According to
							the recipe,
							contains no
							AOX.

Propan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		

- GB (RL) (M)

Page 34 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	Slight
12.3. Bioaccumulative potential:	BCF		3,2				Low
12.4. Mobility in soil:	Koc		1,1				Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other organisms:	IC50	3d	2104	mg/l	Lactuca sativa		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,3	g/g			
Other information:	BOD		1171	mg/g			

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	4,09	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	EC50	96h	18,27	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	7,14	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	13,56	mg/l	Pseudokirchnerie Ila subcapitata	QSAR	
12.1. Toxicity to algae:	ErL50	72h	55	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable (Analogous conclusion), Analogous conclusion

- GB (RL M)

Page 35 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003 Valid from: 12.03.2025

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

12.3. Bioaccumulative	Log Kow	4		
potential:				
12.5. Results of PBT				No PBT
and vPvB assessment				substance, No
				vPvB
				substance

Hydrocarbons, C9-C10), n-alkanes, iso	alkanes,	cyclics, <2		ics		
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>10- <30	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute	
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,182	mg/l	Oncorhynchus mykiss	Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,317	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EL50	48h	>22- <46	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	<1	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50		>1000	mg/l	Pseudokirchnerie Ila subcapitata		
12.2. Persistence and degradability:		28d	89	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.2. Persistence and degradability:	ThOD	28d	53-55	%		,	Biodegradable
12.3. Bioaccumulative potential:	Log Pow		4-5,7				
12.4. Mobility in soil:							Product floats on the water surface.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l			
Water solubility:			~ 0,04	g/l			Insoluble20°C

Hydrocarbons, C7, n-	alkanes, isoalka	nes, cycl	ics				
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>13,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	1,534	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

- GB (RL M)-

Page 36 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

12.1. Toxicity to algae:	EC50	72h	29	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	6,3	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	98	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Heptane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	5,738	mg/l	Oncorhynchus mykiss		ASTM D1345
12.1. Toxicity to daphnia:	EC50	48h	0,64	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	1,5	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	4,338	mg/l	Pseudokirchnerie		
					lla subcapitata		
12.2. Persistence and degradability:		10d	70	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		4,5				
12.4. Mobility in soil:	H (Henry)		208678	Pa*m3/m ol			
12.4. Mobility in soil:	Koc		2,38				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EL50	48h	22,6	mg/l	Pseudomonas putida		
Other information:	BOD5	5d	55	%			
Other information:	ThOD		3500	mg/g			
Other information:	BOD	5d	1920	mg/g			

Methylcyclohexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2,07	mg/l	Oryzias latipes	OECD 203	
						(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	24h	0,326	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	0,134	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	

Isopropyl acetate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

- GB (RL M)

Page 37 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

12.1. Toxicity to fish:	LC50	48h	265	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	24h	4150	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	IC5	8d	165	mg/l	Scenedesmus quadricauda		
12.3. Bioaccumulative potential:	Log Pow		1,03				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC5	16h	190	mg/l	Pseudomonas putida		
Other information:	COD		1670	mg/g	·		
Water solubility:			18,9	g/l			

n-butyl acetate Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
							Notes
12.1. Toxicity to fish:	LC50	96h	18	mg/l	Pimephales	OECD 203	
					promelas	(Fish, Acute	
10.1 T : 11.1	5050	401	1.1		D	Toxicity Test)	
12.1. Toxicity to	EC50	48h	44	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to	NOEC/NOEL	21d	23	mg/l	Daphnia magna	OECD 211	
daphnia:						(Daphnia magna	
						Reproduction	
						Test)	
12.1. Toxicity to algae:	EC50	72h	397	mg/l	Scenedesmus	OECD 201	
					subspicatus	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	83	%		OECD 301 D	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Closed Bottle	
						Test)	
12.3. Bioaccumulative	Log Pow		2,3			OECD 117	Low
potential:						(Partition	
						Coefficient (n-	
						octanol/water) -	
						HPLC method)	
12.5. Results of PBT						,	No PBT
and vPvB assessment							substance, No
							vPvB
							substance
Toxicity to bacteria:	EC50		356	mg/l			Tetrahymena
•							pyriformis

Cyclohexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

- GB (RL M)

Page 38 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

12.1. Toxicity to fish:	LC50	96h	4,53	mg/l	Pimephales	OECD 203	
					promelas	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	0,9	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
40.4 T ::: 1	1.050	701	0.047	//	011 11 1	Test)	
12.1. Toxicity to algae:	LC50	72h	9,317	mg/l	Chlorella vulgaris	0707 001 7	
12.2. Persistence and		28d	77	%		OECD 301 F	
degradability:						(Ready	
						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
12.2. Persistence and	DOC	28d	9	%			Not readily
degradability:	<u> </u>						biodegradable
12.3. Bioaccumulative	Log Pow		3,44				A notable
potential:							biological
							accumulation
							potential has to
							be expected
							(LogPow > 3).
Toxicity to bacteria:	EC50	5min	200	mg/l	Photobacterium		
					phosphoreum		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	12	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	2,187	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOELR	21d	3,818	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	30	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	ErL50	72h	55	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Cyclopentane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l			
12.1. Toxicity to daphnia:	EC50	48h	10,5	mg/l	Daphnia magna		

- GB (RL M)-

Page 39 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2,5	mg/l	Pimephales promelas	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	EC50	48h	2,1	mg/l	Daphnia magna		References
12.3. Bioaccumulative potential:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, N vPvB substan

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28		_		A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and							Readily
degradability:							biodegradable
12.3. Bioaccumulative							A notable
potential:							biological
							accumulation
							potential is not
							to be expected
							(LogPow 1-3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

- GB (RL) (M)

Page 40 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

Classification code:

5F
LQ:
1 L
Transport category:
2

Transport by sea (IMDG-code)

14.1. UN number or ID number:

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: environmentally hazardous

Marine Pollutant: Yes
EmS: F-D, S-U

Transport by air (IATA)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name: UN 1950 Aerosols, flammable

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards: environmentally hazardous

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments







- GB (RL) M

Page 41 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Cyclohexane

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

	<u>,, , </u>		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for	referred to in Article 3(10) for
		the application of - Lower-tier	the application of - Upper-tier
		requirements	requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity
			(tonnes) for the	(tonnes) for the
			application of - Lower-	application of - Upper-
			tier requirements	tier requirements
18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

~ 99,2 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

3, 8, 11, 12

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

- GB (RL) M

Page 42 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H361f Suspected of damaging fertility.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Aquatic Acute — Hazardous to the aquatic environment - acute

Repr. — Reproductive toxicity

STOT RE — Specific target organ toxicity - repeated exposure

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

KochChemie°

ExcellenceForExperts.

- GB (RL M)-

Page 43 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of

substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight mg/kg wwt mg/kg wet weight

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSHNational Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

-GB (RL M)-

Page 44 of 44

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 12.03.2025 / 0004

Replacing version dated / version: 03.12.2024 / 0003

Valid from: 12.03.2025 PDF print date: 12.03.2025 Cabriodach-Versiegelung

Art.: 234412

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning

the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.