KochChemie®
ExcellenceForExperts.

GB IRL M

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 09.12.2024 / 0006
Replacing version dated / version: 11.03.2024 / 0005
Valid from: 09.12.2024
PDF print date: 09.12.2024
Construction Cleaner CTH
Art.: 414999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Construction Cleaner CTH
Art.: 414999

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:
Cleaner

Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH
Einsteinstrasse 42
59423 Unna
Telefon: +49 (0) 2303 / 9 86 70 - 0
Fax: +49 (0) 2303 / 9 86 70 - 26
info@koch-chemie.com
www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:
IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:
+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Acute Tox.	4	H302-Harmful if swallowed.
STOT SE	3	H335-May cause respiratory irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Met. Corr.	1	H290-May be corrosive to metals.

Skin Corr.	1	H314-Causes severe skin burns and eye damage.

2.2 Label elements
Labeling according to Regulation (EC) 1272/2008 (CLP)

Danger

H332-Harmful if inhaled. H302-Harmful if swallowed. H335-May cause respiratory irritation. H290-May be corrosive to metals. H314-Causes severe skin burns and eye damage.

P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P390-Absorb spillage to prevent material damage.

2-Butoxyethanol
Potassium hydroxide
Ethanolamine
Hexyl D-glucoside

2.3 Other hazards
The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances
n.a.
3.2 Mixtures

Potassium hydroxide	
Registration number (REACH)	01-2119487136-33-XXXX
Index	019-002-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	215-181-3
CAS	1310-58-3
content %	20-<30
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Met. Corr. 1, H290 Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318

Specific Concentration Limits and ATE	Skin Corr. 1A, H314: >=5 % Skin Corr. 1B, H314: >=2 % Skin Irrit. 2, H315: >=0,5 % Eye Irrit. 2, H319: >=0,5 % ATE (oral): 333 mg/kg

Ethanolamine	**Substance for which an EU exposure limit value applies.**
Registration number (REACH)	01-2119486455-28-XXXX
Index	603-030-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	205-483-3
CAS	141-43-5
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Specific Concentration Limits and ATE	STOT SE 3, H335: >=5 % ATE (oral): 1089 mg/kg ATE (dermal): 1015 mg/kg ATE (as inhalation, Dusts or mist): 1,5 mg/l/4h ATE (as inhalation, Vapours): 11 mg/l/4h

2-Butoxyethanol	**Substance for which an EU exposure limit value applies.**
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	203-905-0
CAS	111-76-2
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 3, H331 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Specific Concentration Limits and ATE	ATE (oral): 1200 mg/kg ATE (as inhalation, Aerosol): 0,5 mg/l/4h ATE (as inhalation, Vapours): 3 mg/l

Hexyl D-glucoside	
Registration number (REACH)	01-2119492545-29-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	259-217-6
CAS	54549-24-5
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.
The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation
Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.

Skin contact
Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.
Cauterizations not treated lead to wounds difficult to heal.

Eye contact
Remove contact lenses.
Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.
Protect uninjured eye.
Follow-up examination by an ophthalmologist.

Ingestion
Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed
If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.
Corrosive burns on skin as well as mucous membrane possible.
Necrosis
Risk of serious damage to eyes.
Corneal damage.
Danger of blindness.
Pain in the mouth and throat
Gastrointestinal disturbances
Oesophageal perforation

4.3 Indication of any immediate medical attention and special treatment needed
Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing media
Adapt to the nature and extent of fire.
Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media
High volume water jet

5.2 Special hazards arising from the substance or mixture
In case of fire the following can develop:
Oxides of carbon
Oxides of nitrogen
Toxic gases

5.3 Advice for firefighters
For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Keep unprotected persons away.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.
Fill the absorbed material into lockable containers.
Neutralising is possible (only from a specialist).
Diluting with water is possible.
Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Avoid contact with eyes or skin.
Handle and open container with care.
There should be an eyewash station and safety shower located near the area of use.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Do not store with acids.
Do not use alkali sensitive materials.
Store at room temperature.
Store in a dry place.

7.3 Specific end use(s)

No information available at present.
Observe the instructions for good working practice and the recommendations for risk assessment.
Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,
depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

GB **Chemical Name**	Potassium hydroxide	
WEL-TWA: ---	WEL-STEL: 2 mg/m3	---
Monitoring procedures:	ISO 15202 (Workplace air - Determination of metals and metalloids in airborne particulate matter by Inductively Coupled Plasma Atomic Emission - Spectrometry), Part 1-3 - 2012(Part 1), 2012(Part 2), 2004 (Part 3) - NIOSH 7401 (Alkaline dusts) - 1994 OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 44-5 - (2004)	
BMGV: ---	Other information: ---	

IRL **Chemical Name**	Potassium hydroxide	
OELV-8h: ---	OELV-15min: 2 mg/m3	---
Monitoring procedures:	ISO 15202 (Workplace air - Determination of metals and metalloids in airborne particulate matter by Inductively Coupled Plasma Atomic Emission - Spectrometry), Part 1-3 - 2012(Part 1), 2012(Part 2), 2004 (Part 3) - NIOSH 7401 (Alkaline dusts) - 1994 OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 44-5 - (2004)	
BLV: ---	Other information: ---	

GB **Chemical Name**	Ethanolamine	
WEL-TWA: 1 ppm (2,5 mg/m3) (WEL-TWA, EU)	WEL-STEL: 3 ppm (7,6 mg/m3) (WEL-STEL, EU)	---
Monitoring procedures:	- Compur - KITA-224 SA (548 634) - NIOSH 2007 (Aminoethanol compounds) - 1994 - NIOSH 3509 (Aminoethanol COMPOUNDS II) - 1994 OSHA PV2111 (Ethanolamine) - 1988 - EU project BC/CEN/ENTR/000/2002-16 - card 49-5 (2004)	
BMGV: ---	Other information: Sk (WEL, EU)	

IRL **Chemical Name**	Ethanolamine	
OELV-8h: 1 ppm (2,5 mg/m3) (OELV-8h, EU)	OELV-15min: 3 ppm (7,6 mg/m3) (OELV-15min, EU)	---
Monitoring procedures:	- Compur - KITA-224 SA (548 634) - NIOSH 2007 (Aminoethanol compounds) - 1994 - NIOSH 3509 (Aminoethanol COMPOUNDS II) - 1994 OSHA PV2111 (Ethanolamine) - 1988 - EU project BC/CEN/ENTR/000/2002-16 - card 49-5 (2004)	
BLV: ---	Other information: Sk (IOELV, EU)	

M **Chemical Name**	Ethanolamine	
OELV-8h: 1 ppm (2,5 mg/m3) (OELV-8h, EU)	OELV-ST: 3 ppm (7,6 mg/m3) (OELV-ST, EU)	---
Monitoring procedures:	- Compur - KITA-224 SA (548 634) - NIOSH 2007 (Aminoethanol compounds) - 1994 - NIOSH 3509 (Aminoethanol COMPOUNDS II) - 1994 OSHA PV2111 (Ethanolamine) - 1988 - EU project BC/CEN/ENTR/000/2002-16 - card 49-5 (2004)	
BMGV: ---	Other information: Skin	

GB **Chemical Name**	2-Butoxyethanol	
WEL-TWA: 25 ppm (123 mg/m3) (WEL-TWA), 20 ppm (98 mg/m3) (EU)	WEL-STEL: 50 ppm (246 mg/m3) (WEL-STEL, EU)	---
Monitoring procedures:	- Compur - KITA-190 U(C) (548 873) DFG Meth.-Nr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990	

BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Sk (WEL)

IRL	Chemical Name	2-Butoxyethanol	
OELV-8h: 20 ppm (98 mg/m3) (OELV-8h, EU)	OELV-15min: 50 ppm (246 mg/m3) (OELV-15min, EU)	---	
Monitoring procedures:	- Compur - KITA-190 U(C) (548 873) DFG Meth.-Nr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990		
BLV: 200 mg/g creatinine (Butoxyacetic acid (BAA) in urine, h) (ACGIH-BEI)		Other information: Sk, IOELV	

M	Chemical Name	2-Butoxyethanol	
OELV-8h: 20 ppm (98 mg/m3) (OELV-8h, EU)	OELV-ST: 50 ppm (246 mg/m3) (OELV-ST, EU)	---	
Monitoring procedures:	- Compur - KITA-190 U(C) (548 873) DFG Meth.-Nr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990		
BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)		Other information: Skin	

Potassium hydroxide

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	

Ethanolamine

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,07	mg/l	
	Environment - marine		PNEC	0,007	mg/l	
	Environment - periodic release		PNEC	0,028	mg/l	
	Environment - sediment, freshwater		PNEC	0,357	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,0357	mg/kg dry weight	
	Environment - soil		PNEC	1,29	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,18	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,28	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3	mg/kg bw/day	

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,51	mg/m3	

2-Butoxyethanol						
Area of application	**Exposure route / Environmental compartment**	**Effect on health**	**Descriptor**	**Value**	**Unit**	**Note**
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3	

Hexyl D-glucoside						
Area of application	**Exposure route / Environmental compartment**	**Effect on health**	**Descriptor**	**Value**	**Unit**	**Note**
	Environment - freshwater		PNEC	0,176	mg/l	
	Environment - marine		PNEC	0,018	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	

	Environment - sediment, marine		PNEC	0,722	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,072	mg/kg dry weight	
	Environment - soil		PNEC	0,654	mg/kg dry weight	
Consumer	Human - dermal	Long term, systemic effects	DNEL	357000	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	124	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	35,7	mg/kg body weight/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	595000	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	420	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

IRL - Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
| OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
| BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)): ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and Safety Executive (HSE), UK.

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
| Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

M - Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
| OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom).
(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
| Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method , account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE), (EU15) = Substantial contribution to the total body burden via dermal exposure possible. |

8.2 Exposure controls
8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. EN 14042.
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment
General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).
According to operation.

Face protection (EN 166).

Skin protection - Hand protection:
Use alkali resistant protective gloves (EN ISO 374).
If applicable
Protective nitrile gloves (EN ISO 374).
Minimum layer thickness in mm:
0,7
Permeation time (penetration time) in minutes:
>= 480
Protective hand cream recommended.
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.
Filter A P2 (EN 14387), code colour brown, white
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls
No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light brown
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	14
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Soluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,25 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Corrosive to metals: There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity
Product corrodes metals.

10.2 Chemical stability
Stable with proper storage and handling.

10.3 Possibility of hazardous reactions
Avoid contact with strong acids (exothermic reaction possible).
Avoid contact with certain metals e.g. aluminium (development of hydrogen gas possible).

10.4 Conditions to avoid
None known

10.5 Incompatible materials
Avoid contact with strong acids.
Avoid contact with strong oxidizing agents.
Avoid contact with alkali sensitive materials.
Avoid contact with certain metals e.g. aluminium.

10.6 Hazardous decomposition products
See also section 5.2
No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Possibly more information on health effects, see Section 2.1 (classification).

Construction Cleaner CTH
Art.: 414999

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1128,17	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	18,64	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	2,94	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Potassium hydroxide

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	333-388	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	1 week observation
Acute toxicity, by oral route:	ATE	333	mg/kg			

Skin corrosion/irritation:					OECD 431 (In Vitro Skin Corrosion - Human Skin Model Test)	Corrosive
Skin corrosion/irritation:						Skin Corr. 1A
Serious eye damage/irritation:						Eye Dam. 1
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Corrosive
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising
Germ cell mutagenicity:					in vivo	Negative
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative

Ethanolamine

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1089	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	ATE	1089	mg/kg			
Acute toxicity, by dermal route:	ATE	1015	mg/kg			
Acute toxicity, by dermal route:	LD50	1015	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	2504	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	1,49	mg/l/4h	Rat		Vapours, Maximum achievable concentration.
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Dusts or mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	300	mg/kg bw/d	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	10	mg/m3	Rat	OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	

Symptoms:						ataxia, respiratory distress, drowsiness, coughing, mucous membrane irritation, nausea

2-Butoxyethanol						
Toxicity / effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	ATE	3	mg/l			Vapours
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Aerosol
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	720	mg/kg bw/d			
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	
Aspiration hazard:						No

Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness, nausea

Hexyl D-glucoside						
Toxicity / effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative

11.2. Information on other hazards

Construction Cleaner CTH Art.: 414999						
Toxicity / effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Construction Cleaner CTH Art.: 414999							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.

12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: No
Other information:	AOX			%			According to the recipe, contains no AOX.

Potassium hydroxide							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to fish:	LC50	96h	80	mg/l	Gambusia affinis		
12.1. Toxicity to fish:	LC50	24h	165	mg/l	Poecilia reticulata		
12.1. Toxicity to daphnia:	EC50	48h	40,4	mg/l	Ceriodaphnia spec.		
12.2. Persistence and degradability:							Not relevant for inorganic substances.

12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
Toxicity to bacteria:	EC50	15min	22	mg/l	Photobacterium phosphoreum		

Ethanolamine							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to fish:	LC50	96h	170	mg/l	Carassius auratus		
12.1. Toxicity to fish:	NOEC/NOEL	42d	1,2	mg/l	Oryzias latipes	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	349	mg/l	Cyprinus caprio	92/69/EC	
12.1. Toxicity to fish:	NOEC/NOEL	30d	1,2	mg/l	Oryzias latipes	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	105	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	27,34	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,85	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	2,5	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOAEC	72h	1	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	22	mg/l	Scenedesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:	DOC	21d	> 90	%	activated sludge	OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	96	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.2. Persistence and degradability:		21d	>90	%		OECD 302 A (Inherent Biodegradability - Modified SCAS Test)	Readily biodegradable

12.3. Bioaccumulative potential:	BCF		< 100				Slight
12.3. Bioaccumulative potential:	Log Pow		(-2,3) - (-1,31)			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	SlightpH 6,8 - 7,3, 25 °C
12.4. Mobility in soil:	pOC		0-50				High
12.4. Mobility in soil:	Koc		1,17				estimated
12.4. Mobility in soil:	H (Henry)		0,000037	Pa*m3/mol			estimated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	EC50	16h	110	mg/l	Pseudomonas putida	DIN 38412 T.8	
Toxicity to bacteria:	EC20	30min	> 1000	mg/l	activated sludge	ISO 8192	
Other organisms:	EC50	28d	2500	mg/kg dw			Folsomia candida
Other organisms:	EC50	14d	2939	mg/kg dw			Hordeum vulgare
Other organisms:	EC50	21d	1817	mg/kg dw			Elymus lanceolatus
Other organisms:	EC50	21d	1290	mg/kg dw			Medicago sativa (Alfalfa)
Other information:	BOD	5d	800	mg/g			
Toxicity to annelids:	EC50	>60d	4033	mg/kg dw		OECD 207 (Earthworm, Acute Toxicity Tests)	Eisenia andrei, 63d

2-Butoxyethanol							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	

12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,2				Slight
12.3. Bioaccumulative potential:	Log Pow		0,81			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Not to be expected
12.4. Mobility in soil:	H (Henry)		0,0000016	atm*m3/mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

Hexyl D-glucoside

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	180	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:		28d	71	%	activated sludge	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		1,72-1,77				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	4h	>1000	mg/l	activated sludge		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:
The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
20 01 29 detergents containing hazardous substances
Recommendation:
Sewage disposal shall be discouraged.
Pay attention to local and national official regulations.
E.g. suitable incineration plant.
E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.
Empty container completely.
Uncontaminated packaging can be recycled.
Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1760
14.2. UN proper shipping name:	
UN 1760 CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE, ETHANOLAMINE)	
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	E
Classification code:	C9
LQ:	1 L
Transport category:	2

Transport by sea (IMDG-code)

14.1. UN number or ID number:	1760
14.2. UN proper shipping name:	
UN 1760 CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE, ETHANOLAMINE)	
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
14.5. Environmental hazards:	Not applicable
Marine Pollutant:	Not applicable
EmS:	F-A, S-B
Segregation:	-

Transport by air (IATA)

14.1. UN number or ID number:	1760
14.2. UN proper shipping name:	
UN 1760 Corrosive liquid, n.o.s. (POTASSIUM HYDROXIDE, ETHANOLAMINE)	
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
14.5. Environmental hazards:	Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.

Danger code and packing code on request.
Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 27 %

REGULATION (EC) No 648/2004
5 % or over but less than 15 %
non-ionic surfactants

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment
A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8
Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Acute Tox. 4, H302	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification based on the pH value.
Met. Corr. 1, H290	Classification based on test data.
Skin Corr. 1, H314	Classification based on the pH value.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.
H314 Causes severe skin burns and eye damage.
H290 May be corrosive to metals.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H412 Harmful to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - inhalation
Acute Tox. — Acute toxicity - oral

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
Eye Dam. — Serious eye damage
Met. Corr. — Substance or mixture corrosive to metals
Skin Corr. — Skin corrosion
Acute Tox. — Acute toxicity - dermal
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Skin Irrit. — Skin irritation
Eye Irrit. — Eye irritation

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
mg/kg bw mg/kg body weight
mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
mg/kg dw mg/kg dry weight
mg/kg wwt mg/kg wet weight
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.
These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90