

Page 1 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 11.03.2024 / 0003
Replacing version dated / version: 05.12.2022 / 0002
Valid from: 11.03.2024
PDF print date: 15.03.2024
Eulex V
Art.: 364999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Eulex V
Art.: 364999

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Cleaner

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH
Einsteinstrasse 42
59423 Unna
Telefon: +49 (0) 2303 / 9 86 70 - 0
Fax: +49 (0) 2303 / 9 86 70 - 26
info@koch-chemie.com
www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	3	H226-Flammable liquid and vapour.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H226-Flammable liquid and vapour. H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273-Avoid release to the environment.
 P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting.
 P405-Store locked up.
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	
Registration number (REACH)	01-2119471991-29-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	923-037-2
CAS	---
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

1-methoxy-2-propanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119457435-35-XXXX
Index	603-064-00-3
EINECS, ELINCS, NLP, REACH-IT List-No.	203-539-1
CAS	107-98-2
content %	1-<10

Page 3 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 11.03.2024 / 0003
Replacing version dated / version: 05.12.2022 / 0002
Valid from: 11.03.2024
PDF print date: 15.03.2024
Eulex V
Art.: 364999

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors

Flam. Liq. 3, H226
STOT SE 3, H336

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.
The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Nausea
vomiting

Danger of aspiration.
oedema of the lungs
Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.
Gastric lavage (stomach washing) only under endotracheal intubation.
Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Toxic gases
Danger of bursting (explosion) when heated
Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

Page 4 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 11.03.2024 / 0003
Replacing version dated / version: 05.12.2022 / 0002
Valid from: 11.03.2024
PDF print date: 15.03.2024
Eulex V
Art.: 364999

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Keep unprotected persons away.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Keep away from sources of ignition - Do not smoke.
Take measures against electrostatic charging, if appropriate.
Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Observe special storage conditions.
Under all circumstances prevent penetration into the soil.
Do not store with flammable or self-igniting materials.

GB IRL M

Page 5 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

Protect from direct sunlight and warming.
 Store in a well-ventilated place.
 Store cool.
 Store in a dry place.

7.3 Specific end use(s)

No information available at present.
 Observe the instructions for good working practice and the recommendations for risk assessment.
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,
 depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1200 mg/m³

GB	Chemical Name	Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	
	WEL-TWA: 1200 mg/m ³	WEL-STEL: ---	---
	Monitoring procedures:	- Compur - KITA-187 S (551 174)	
	BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

IRL	Chemical Name	Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	
	OELV-8h: 100 ppm (573 mg/m ³) ("Stoddard solvent", [White spirit])	OELV-15min: ---	---
	Monitoring procedures:	- Compur - KITA-187 S (551 174)	
	BLV: ---	Other information: ---	

GB	Chemical Name	1-methoxy-2-propanol	
	WEL-TWA: 100 ppm (375 mg/m ³) (WEL-TWA, EU)	WEL-STEL: 150 ppm (560 mg/m ³) (WEL-STEL), 150 ppm (568 mg/m ³) (EU)	---
	Monitoring procedures:	INSHT MTA/MA-017/A89 (Determination of glycol ethers (1-methoxy-2-propanol, 2-ethoxyethanol) in air - Charcoal tube method / Gas chromatography) - 1989 - - EU project BC/CEN/ENTR/000/2002-16 card 12-1 (2004) - NIOSH 2554 (GLYCOL ETHERS) - 2003 - OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993	
	BMGV: ---	Other information: Sk (WEL)	

IRL	Chemical Name	1-methoxy-2-propanol	
	OELV-8h: 100 ppm (375 mg/m ³) (Propylene glycol monomethyl ether) (OELV-8h, EU)	OELV-15min: 150 ppm (568 mg/m ³) (Propylene glycol monomethyl ether) (OELV-15min, EU)	---
	Monitoring procedures:	INSHT MTA/MA-017/A89 (Determination of glycol ethers (1-methoxy-2-propanol, 2-ethoxyethanol) in air - Charcoal tube method / Gas chromatography) - 1989 - - EU project BC/CEN/ENTR/000/2002-16 card 12-1 (2004) - NIOSH 2554 (GLYCOL ETHERS) - 2003 - OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993	
	BLV: ---	Other information: IOELV	

M	Chemical Name	1-methoxy-2-propanol	
	OELV-8h: 100 ppm (375 mg/m ³) (OELV-8h, EU)	OELV-ST: 150 ppm (568 mg/m ³) (OELV-ST, EU)	---
	Monitoring procedures:	INSHT MTA/MA-017/A89 (Determination of glycol ethers (1-methoxy-2-propanol, 2-ethoxyethanol) in air - Charcoal tube method / Gas chromatography) - 1989 - - EU project BC/CEN/ENTR/000/2002-16 card 12-1 (2004) - NIOSH 2554 (GLYCOL ETHERS) - 2003 - OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993	
	BMGV: ---	Other information: Skin	

1-methoxy-2-propanol

Page 6 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - periodic release		PNEC	100	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	41,6	mg/kg dw	
	Environment - sediment, marine		PNEC	4,17	mg/kg dw	
	Environment - soil		PNEC	2,47	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	33	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	78	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	553,5	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,9	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	183	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	369	mg/m3	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	3,3	mg/kg	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	183	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	553,5	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	553,5	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

IRL - Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force

of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
| OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)): ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and Safety Executive (HSE), UK.

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

Ⓜ - Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
| OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom). (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE). |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2024 / 0003

Replacing version dated / version: 05.12.2022 / 0002

Valid from: 11.03.2024

PDF print date: 15.03.2024

Eulex V

Art.: 364999

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Mild
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	23-60 °C
Auto-ignition temperature:	There is no information available on this parameter.

Page 9 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<=20,5 mm ² /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,75 g/cm ³
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Eulex V

Art.: 364999

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.

Page 10 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m ³ /8 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Aspiration hazard:						Yes

1-methoxy-2-propanol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	Regulation (EC) 440/2008 B.3 (ACUTE TOXICITY (DERMAL))	
Acute toxicity, by inhalation:	LC0	>7000	ppmV/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Not irritant
Serious eye damage/irritation:				Rabbit	Regulation (EC) 440/2008 B.5 (ACUTE EYE IRRITATION/CORROSION)	Not irritant

Page 11 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

Respiratory or skin sensitisation:				Guinea pig	Regulation (EC) 440/2008 B.6 (SKIN SENSITISATION)	Not sensitizing
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Symptoms:						drowsiness, unconsciousness, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

11.2. Information on other hazards

Eulex V Art.: 364999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Eulex V Art.: 364999							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Page 12 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

Other information:							DOC-elimination degree (complexing organic substance) \geq 80%/28d: n.a.
Other information:	AOX			%			According to the recipe, contains no AOX.

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL0	96h	1000	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,192	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EL0	48h	1000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,025	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL0	72h	1000	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	31,3	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable.
Toxicity to bacteria:	EC50		1 - 10	mg/l			
Water solubility:							Insoluble

1-methoxy-2-propanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	6812	mg/l	Leuciscus idus	DIN 38412 T.15	
12.1. Toxicity to fish:	LC50	96h	20800	mg/l	Pimephales promelas		ASTM
12.1. Toxicity to fish:	LC50	96h	\geq 1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna		
12.1. Toxicity to algae:	IC50	72h	>1000	mg/l	Pseudokirchneriella subcapitata		

Page 13 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

12.2. Persistence and degradability:		28d	90	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		--0,49				Not to be expected
12.3. Bioaccumulative potential:	BCF		<100				Low
12.4. Mobility in soil:	Koc		0,2-1				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

14 06 03 other solvents and solvent mixtures

20 01 13 Solvents

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

Page 14 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

14.1. UN number or ID number: 1993
 14.2. UN proper shipping name:
 UN 1993 FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-PROPANOL, HYDROCARBONS, C10-C12)
 14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 14.5. Environmental hazards: environmentally hazardous
 Tunnel restriction code: D/E
 Classification code: F1
 LQ: 5 L
 Transport category: 3



Transport by sea (IMDG-code)

14.1. UN number or ID number: 1993
 14.2. UN proper shipping name:
 UN 1993 FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-PROPANOL, HYDROCARBONS, C10-C12)
 14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 14.5. Environmental hazards: environmentally hazardous
 Marine Pollutant: Yes
 EmS: F-E, S-E
 Segregation: -



Transport by air (IATA)

14.1. UN number or ID number: 1993
 14.2. UN proper shipping name:
 UN 1993 Flammable liquid, n.o.s. (1-METHOXY-2-PROPANOL, HYDROCARBONS, C10-C12)
 14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 100 %

REGULATION (EC) No 648/2004

Page 15 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.03.2024 / 0003
 Replacing version dated / version: 05.12.2022 / 0002
 Valid from: 11.03.2024
 PDF print date: 15.03.2024
 Eulex V
 Art.: 364999

30 % and more
 aliphatic hydrocarbons

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 3, H226	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.
 H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid
 Asp. Tox. — Aspiration hazard
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

Page 16 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 11.03.2024 / 0003
Replacing version dated / version: 05.12.2022 / 0002
Valid from: 11.03.2024
PDF print date: 15.03.2024
Eulex V
Art.: 364999

AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
mg/kg bw mg/kg body weight
mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
mg/kg dw mg/kg dry weight
mg/kg wwt mg/kg wet weight
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development

Page 17 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 11.03.2024 / 0003
Replacing version dated / version: 05.12.2022 / 0002
Valid from: 11.03.2024
PDF print date: 15.03.2024
Eulex V
Art.: 364999

org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.