(BR) (M)

Page 1 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Felgenreiniger extrem Art.: 187999

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Cleaner Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26 info@koch-chemie.com www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

(RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT SE	3	H335-May cause respiratory irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Met. Corr.	1	H290-May be corrosive to metals.
Skin Corr.	1	H314-Causes severe skin burns and eye damage.

2.2 Label elements

6B (R) (M)

Page 2 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

Labeling according to Regulation (EC) 1272/2008 (CLP)



H335-May cause respiratory irritation. H290-May be corrosive to metals. H314-Causes severe skin burns and eye damage.

P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P390-Absorb spillage to prevent material damage.

Hydrochloric acid 2-Propylheptanol, ethoxylated

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

J.2 WIALUICS	Substance for which an EU exposure limit value
Hydrochloric acid	•
	applies.
Registration number (REACH)	01-2119484862-27-XXXX
Index	017-002-01-X
EINECS, ELINCS, NLP, REACH-IT List-No.	231-595-7
CAS	7647-01-0
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Skin Corr. 1B, H314
factors	Eye Dam. 1, H318
	STOT SE 3, H335
Specific Concentration Limits and ATE	Met. Corr. 1, H290: >=0,1 %
	Skin Corr. 1B, H314: >=25 %
	Skin Irrit. 2, H315: >=10 %
	Eye Irrit. 2, H319: >=10 %
	STOT SE 3, H335: >=10 %
2-Propylheptanol, ethoxylated	
Registration number (REACH)	
Index	

GB (RL M

Page 3 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	160875-66-1
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H302
factors	Eye Dam. 1, H318
Specific Concentration Limits and ATE	Eye Dam. 1, H318: >10 %
	ATE (oral): 700 mg/kg

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Cauterizations not treated lead to wounds difficult to heal.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye. Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Corrosive burns on skin as well as mucous membrane possible.

Risk of serious damage to eyes. Danger of blindness. Ingestion: Pain in the mouth and throat Oesophageal perforation

Gastric perforation

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

GB (RL M

Page 4 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

In case of fire the following can develop: Oxides of carbon Hydrogen chloride Toxic gases 5.3 Advice for firefighters

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Neutralising is possible (only from a specialist).

Diluting with water is possible.

Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations Ensure good ventilation.

Ensure good ventilation.

Avoid inhalation of the vapours. Avoid contact with eyes or skin.

Handle and open container with care.

There should be an eyewash station and safety shower located near the area of use.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

6B (RL M

Page 5 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Do not use acid sensitive materials. Acid-resistant floor necessary. Do not store with alkalis. Store at room temperature. Store in a dry place.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment. Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

	Hydrochloric acid
WEL-TWA: HCl 1 ppm (2 mg/m3 aerosol mists) (WEL-TWA), 5 ppm	
Monitoring procedures:	 Draeger - Hydrochloric Acid 0,2/a (81 03 481) Draeger - Hydrochloric Acid 1/a (CH 29 501) Draeger - Hydrochloric Acid 50/a (67 28 181) Compur - KITA-173 SA (548 980) Compur - KITA-173 SB (548 998) DFG (D), DFG (E) (Volatile inorganic acids) - 1997 - EU project BC/CEN/ENTR/000/2002-16 card 93-1 (2004) INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air)
	- OSHA ID-174SG (Hydrogen chloride in workplace atmospheresw) - 1986
BMGV:	Other information:
Chemical Name	Hydrochloric acid
Chemical Name OELV-8h: HCl 5 ppm (8 mg/m3)	
Monitoring procedures: BLV:	 Draeger - Hydrochloric Acid 0,2/a (81 03 481) Draeger - Hydrochloric Acid 1/a (CH 29 501) Draeger - Hydrochloric Acid 50/a (67 28 181) Compur - KITA-173 SA (548 980) Compur - KITA-173 SB (548 998) DFG (D), DFG (E) (Volatile inorganic acids) - 1997 - EU project BC/CEN/ENTR/000/2002-16 card 93-1 (2004) INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air) OSHA ID-174SG (Hydrogen chloride in workplace atmospheresw) - 1986
Chemical Name	Hydrochloric acid
OELV-8h: 5 ppm (8 mg/m3) (OEI Monitoring procedures:	V-8h, EU)OELV-ST: 10 ppm (15 mg/m3) (OELV-ST, EU)Draeger - Hydrochloric Acid 0,2/a (81 03 481)Draeger - Hydrochloric Acid 1/a (CH 29 501)Draeger - Hydrochloric Acid 50/a (67 28 181)Compur - KITA-173 SA (548 980)Compur - KITA-173 SB (548 998)DFG (D), DFG (E) (Volatile inorganic acids) - 1997 - EU project-BC/CEN/ENTR/000/2002-16 card 93-1 (2004)-INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air)-OSHA ID-174SG (Hydrogen chloride in workplace atmospheresw) - 1986
BMGV:	Other information:
billott.	

©® ℝ M

Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

Hydrochloric acid						
Area of application	Exposure route / Environmental	Effect on health	Descripto r	Value	Unit	Note
	compartment Environment - freshwater		PNEC	36	µg/l	
	Environment - marine		PNEC	36	µg/l	
	Environment - water, sporadic (intermittent) release		PNEC	45	µg/l	
	Environment - sewage treatment plant		PNEC	36	µg/l	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	15	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	8	mg/m3	

Inited Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2024, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2024, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)): ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and Safety Executive (HSE), UK.

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

GB (RL M

Page 7 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

| Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2024, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Skin = Can be absorbed through skin. Asphx = asphyxiant. Sens = The substance can cause sensitisation. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

• Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.

 $(EU) = \text{Directive } 91/322/\text{EEC}, 98/24/\text{EC}, 2000/39/\text{EC}, 2004/37/\text{EC}, 2006/15/\text{EC}, 2009/161/\text{EU}, 2017/164/\text{EU} \text{ or } 2019/1831/\text{EU} \text{:} \\ (8) = \text{Inhalable fraction } (2004/37/\text{EC}, 2017/164/\text{EU}) \text{.} \\ (9) = \text{Respirable fraction } (2004/37/\text{EC}, 2017/164/\text{EU}) \text{.} \\ (10) = \text{Short-term exposure limit value in relation to a reference period of 1 minute } (2017/164/\text{EU}) \text{.} \\ (3) = \text{Short-term exposure limit value in relation to a reference period of 1 minute } (2017/164/\text{EU}) \text{.} \\ (3) = \text{Short-term exposure limit value in relation to a reference period of 1 minute } (2017/164/\text{EU}) \text{.} \\ (3) = \text{Short-term exposure limit value in relation to a reference period of 1 minute } (2017/164/\text{EU}) \text{.} \\ (3) = \text{Short-term exposure limit value in relation to a reference period of 1 minute } (2017/164/\text{EU}) \text{.} \\ (3) = \text{Short-term exposure limit value in relation to a reference period of 1 minute } (2017/164/\text{EU}) \text{.} \\ (3) = \text{Short-term exposure limit value in relation to a reference period of 1 minute } (2017/164/\text{EU}) \text{.} \\ (3) = \text{Short-term exposure limit value in relation to a reference period of 1 minute } (2017/164/\text{EU}) \text{.} \\ (3) = \text{Short-term exposure limit value } (3) = \text{Short-term exposure limit val$

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom). (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE), (EU15) = Substantial contribution to the total body burden via dermal exposure possible.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166). If applicable Face protection (EN 166).

GBIRI Page 8 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999 Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended Protective gloves in butyl rubber (EN ISO 374). Minimum layer thickness in mm: > 0,5 Permeation time (penetration time) in minutes: > 120 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended. Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments). Respiratory protection: If OES or MEL is exceeded. Filter E (EN 14387), code colour yellow Filter P2 (EN 143), code colour white Observe wearing time limitations for respiratory protection equipment. Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

3.1 million action on basic physical and chemical pl	loperties
Physical state:	Liquid
Colour:	Red
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	0
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Soluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,09 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
9.2 Other information	
Corrosive to metals:	There is no information available on this parameter.

GB (RL M

Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

SECTION 10: Stability and reactivity

10.1 Reactivity

Product corrodes metals.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Avoid contact with strong alkalis (exothermic reaction possible).

Avoid contact with certain metals e.g. aluminium (development of hydrogen gas possible).

10.4 Conditions to avoid

See also section 7. None known

10.5 Incompatible materials

See also section 7. Avoid contact with strong alkalis. Avoid contact with strong oxidizing agents. Avoid contact with certain metals e.g. aluminium. Avoid contact with acid sensitive materials.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Felgenreiniger extrem						
Art.: 187999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrochloric acid						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	900	mg/kg	Rabbit		
Acute toxicity, by dermal	LD50	> 5010	mg/kg	Rabbit		
route:						
Skin corrosion/irritation:				Rabbit		Skin Corr. 1B
Serious eye				Rabbit		Eye Dam. 1
damage/irritation:						

GB (RL M

Page 10 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

Respiratory or skin	Guinea pig	Not sensitizising
sensitisation:		
Germ cell mutagenicity:		Negative
Carcinogenicity:		Negative
Reproductive toxicity:		Negative
Specific target organ toxicity -		May cause
single exposure (STOT-SE),		respiratory
inhalative:		irritation.
Aspiration hazard:		No
Symptoms:		respiratory
		distress,
		unconsciousnes
		s, coughing,
		cramps,
		mucous
		membrane
		irritation

2-Propylheptanol, ethoxylated								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>700-1700	mg/kg	Rat				
Acute toxicity, by oral route:	ATE	700	mg/kg					
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rabbit				
route:								
Symptoms:						mucous		
						membrane		
						irritation		

11.2. Information on other hazards

Felgenreiniger extrem Art.: 187999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).									
Felgenreiniger extrem									
Art.: 187999									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:							n.d.a.		
12.1. Toxicity to							n.d.a.		
daphnia:									
12.1. Toxicity to algae:							n.d.a.		

GBRIM

Revision date / version: Replacing version dated Valid from: 23.05.2025 PDF print date: 23.05.20 Felgenreiniger extrem Art.: 187999	d / version: 26.1			
12.2. Persistence and degradability:				The surfactant(s) contained in this mixture complies(compl y) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a
				detergent manufacturer.
12.3. Bioaccumulative				n.d.a.
potential:				
12.4. Mobility in soil: 12.5. Results of PBT				n.d.a. n.d.a.
and vPvB assessment				n.u.a.
12.6. Endocrine				Does not apply
disrupting properties:				to mixtures.
12.7. Other adverse effects:				No information available on other adverse effects on the environment.
Other information:				DOC- elimination degree(complex ing organic substance)>= 80%/28d: n.a.
Other information:	AOX	%		According to the recipe, contains no AOX.

Page 11 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	7,45	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	24,6	mg/l	Lepomis macrochirus		

©B (RL) (M)

Page 12 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

12.1. Toxicity to daphnia:	EC50	48h	0,492	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	0,78	mg/l	Selenastrum	OEĆD 201	
					capricornutum	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and							Inorganic
degradability:							products
							cannot be
							eliminated from
							water through
							biological
							purification
							methods.
12.3. Bioaccumulative							Bioaccumulatio
potential:							n is unlikely
							(LogPow < 1).
12.4. Mobility in soil:							Not to be
							expected
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10- 100	mg/l	Oncorhynchus tshawytscha		Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>10- 100	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	10-100	mg/l	Scenedesmus subspicatus		Analogous conclusion
12.2. Persistence and degradability:	BOD	28d	>60	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substanc

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 06 01 aqueous washing liquids and mother liquors

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

-@R.M				
Page 13 of 16				
Safety data sheet according to Regulation (EC) No 1907/2006	, Annex II (last amended by Regulation (EU) 2020/878)			
Revision date / version: 23.05.2025 / 0005				
Replacing version dated / version: 26.11.2024 / 0004				
Valid from: 23.05.2025				
PDF print date: 23.05.2025				
Felgenreiniger extrem				
Art.: 187999				
Pay attention to local and national official regulations.				
Empty container completely.				
Uncontaminated packaging can be recycled.				
Dispose of packaging that cannot be cleaned in the same mar	nner as the substance.			
	ransport information			
General statements				
Transport by road/by rail (ADR/RID)				
14.1. UN number or ID number:	1789			
14.2. UN proper shipping name:	-			
UN 1789 HYDROCHLORIC ACID, SOLUTION				
14.3. Transport hazard class(es):	8			
14.4. Packing group:	II	·		
14.5. Environmental hazards:	Not applicable			
Tunnel restriction code:	E			
Classification code:	C1			
LQ:	1 L			
Transport category:	2			
Transport by sea (IMDG-code)				
14.1. UN number or ID number:	1789			
14.2. UN proper shipping name:				
UN 1789 HYDROCHLORIC ACID, SOLUTION				
14.3. Transport hazard class(es):	8			
14.4. Packing group:	II	·		
14.5. Environmental hazards:	Not applicable			
Marine Pollutant:	Not applicable			
EmS:	F-A, S-B			
Transport by air (IATA)				
14.1. UN number or ID number:	1789			
14.2. UN proper shipping name:				
UN 1789 Hydrochloric acid solution				
14.3. Transport hazard class(es):	8			
14.4. Packing group:	ll l	*		
14.5. Environmental hazards:	Not applicable			
14.6. Special precautions for user				
Persons employed in transporting dangerous goods must be to	rained.			
All persons involved in transporting must observe safety regula				
Precautions must be taken to prevent damage.				
14.7. Maritime transport in bulk according to I				
Freighted as packaged goods rather than in bulk, therefore no				
Minimum amount regulations have not been taken into accour	nt.			
Danger code and packing code on request.				
Comply with special provisions.				
SECTION 15: R	egulatory information			

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): **REGULATION (EC) No 648/2004** 5 % or over but less than 15 % non-ionic surfactants 0,4 %

GB (RL M)

Page 14 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999

perfumes

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

8

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H335	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification based on the pH value.
Met. Corr. 1, H290	Classification based on test data.
Skin Corr. 1, H314	Classification based on the pH value.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Eye Dam. — Serious eye damage

Met. Corr. — Substance or mixture corrosive to metals

Skin Corr. — Skin corrosion

Acute Tox. — Acute toxicity - oral

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds

(B) (RL) (M) Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999 approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council CAS Chemical Abstracts Service CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances EN **European Norms** United States Environmental Protection Agency (United States of America) EPA $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil octanol-water partition coefficient Kow IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLIDInternational Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships mg/kg bw mg/kg body weight mg/kg bw/d, mg/kg bw/day mg/kg body weight/day mg/kg dw mg/kg dry weight mg/kg wwt mg/kg wet weight not applicable n.a. n.av. not available n.c. not checked n.d.a. no data available NIOSHNational Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org.

GBRIM Page 16 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 23.05.2025 / 0005 Replacing version dated / version: 26.11.2024 / 0004 Valid from: 23.05.2025 PDF print date: 23.05.2025 Felgenreiniger extrem Art.: 187999 OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning REACH the Registration, Evaluation, Authorisation and Restriction of Chemicals) 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other REACH-IT List-No. numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the RID International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.