

Page 1 of 30  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.08.2024 / 0004  
Replacing version dated / version: 11.03.2024 / 0003  
Valid from: 08.08.2024  
PDF print date: 08.08.2024  
Hydro Foam Sealant  
Art.: 465999

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Hydro Foam Sealant**  
**Art.: 465999**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Sealing

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH  
Einsteinstrasse 42  
59423 Unna  
Telefon: +49 (0) 2303 / 9 86 70 - 0  
Fax: +49 (0) 2303 / 9 86 70 - 26  
info@koch-chemie.com  
www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:  
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)  
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

**Telephone number of the company in case of emergencies:**

+1 872 5888271 (KCC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Skin Corr.	1B	H314-Causes severe skin burns and eye damage.
Eye Dam.	1	H318-Causes serious eye damage.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.08.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 08.08.2024

PDF print date: 08.08.2024

Hydro Foam Sealant

Art.: 465999



**Danger**

H332-Harmful if inhaled. H314-Causes severe skin burns and eye damage. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.

P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH208-Contains Cinnamaldehyde. May produce an allergic reaction.

2-Butoxyethanol

Acetic acid

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated

### 2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

2-Butoxyethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	203-905-0
CAS	111-76-2
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 3, H331 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Specific Concentration Limits and ATE	ATE (oral): 1200 mg/kg ATE (as inhalation, Aerosol): 0,5 mg/l/4h ATE (as inhalation, Vapours): 3 mg/l

Page 3 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

<b>1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)</b>	
<b>Registration number (REACH)</b>	01-2119983493-26-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	939-685-4
<b>CAS</b>	---
<b>content %</b>	10-<25
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412

<b>Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	102782-92-3
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412

<b>Butene, homopolymer, hydrogenated</b>	
<b>Registration number (REACH)</b>	01-2119457401-46-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	68937-10-0
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Flam. Liq. 3, H226 Asp. Tox. 1, H304

<b>Siloxanes and silicones, di-Me, 3-[3-[(3-coco amidopropyl)dimethylammonio]-2-hydroxypropoxy]propyl group-terminated, acetates (salts)</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	134737-05-6
<b>content %</b>	3-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Aquatic Chronic 2, H411

<b>Amines, tallow alkyl, ethoxylated</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	61791-26-2
<b>content %</b>	2,5-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
<b>Specific Concentration Limits and ATE</b>	ATE (oral): 500 mg/kg

<b>Phenolpolyethoxylate</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---

GB IRL M

Page 4 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	500-013-6
<b>CAS</b>	9004-78-8
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302
<b>Specific Concentration Limits and ATE</b>	ATE (oral): 500 mg/kg

<b>Acetic acid</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119475328-30-XXXX
<b>Index</b>	607-002-00-6
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	200-580-7
<b>CAS</b>	64-19-7
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Flam. Liq. 3, H226 Skin Corr. 1A, H314 Eye Dam. 1, H318
<b>Specific Concentration Limits and ATE</b>	Skin Corr. 1A, H314: >=90 % Skin Corr. 1B, H314: >=25 % Skin Irrit. 2, H315: >=10 % Eye Irrit. 2, H319: >=10 %

<b>Ethanol</b>	
<b>Registration number (REACH)</b>	01-2119457610-43-XXXX
<b>Index</b>	603-002-00-5
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	200-578-6
<b>CAS</b>	64-17-5
<b>content %</b>	0,1-<2
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Flam. Liq. 2, H225 Eye Irrit. 2, H319
<b>Specific Concentration Limits and ATE</b>	Eye Irrit. 2, H319: >=50 %

<b>Octamethylcyclotetrasiloxane</b>	<b>PBT-substance vPvB-substance SVHC-substance</b>
<b>Registration number (REACH)</b>	01-2119529238-36-XXXX
<b>Index</b>	014-018-00-1
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	209-136-7
<b>CAS</b>	556-67-2
<b>content %</b>	<0,1
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Flam. Liq. 3, H226 Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)

<b>Cinnamaldehyde</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	606-155-00-6
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	203-213-9
<b>CAS</b>	104-55-2
<b>content %</b>	0,001-<0,01
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
<b>Specific Concentration Limits and ATE</b>	Skin Sens. 1, H317: >=0,01 % ATE (dermal): 1100 mg/kg

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

Page 5 of 30  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.08.2024 / 0004  
Replacing version dated / version: 11.03.2024 / 0003  
Valid from: 08.08.2024  
PDF print date: 08.08.2024  
Hydro Foam Sealant  
Art.: 465999

The substances named in this section are given with their actual, appropriate classification!  
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.  
Cauterizations not treated lead to wounds difficult to heal.

#### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.  
Protect uninjured eye.  
Follow-up examination by an ophthalmologist.

#### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.  
Corrosive burns on skin as well as mucous membrane possible.  
Risk of serious damage to eyes.

Conjunctivitis

Corneal damage.

Danger of blindness.

Ingestion:

pain in the mouth and throat

stomach pain

Oesophageal perforation

Gastric perforation

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Toxic gases

### 5.3 Advice for firefighters

Page 6 of 30  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.08.2024 / 0004  
Replacing version dated / version: 11.03.2024 / 0003  
Valid from: 08.08.2024  
PDF print date: 08.08.2024  
Hydro Foam Sealant  
Art.: 465999

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Keep unprotected persons away.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
Prevent from entering drainage system.  
If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.  
Fill the absorbed material into lockable containers.  
Flush residue using copious water.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Avoid contact with eyes or skin.  
Handle and open container with care.  
There should be an eyewash station and safety shower located near the area of use.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.  
Under all circumstances prevent penetration into the soil.  
Store in a well ventilated place.  
Store cool.

GB IRL M

Page 7 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Observe special storage conditions.

### 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

GB	Chemical Name	2-Butoxyethanol	
	WEL-TWA: 25 ppm (123 mg/m <sup>3</sup> ) (WEL-TWA), 20 ppm (98 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 50 ppm (246 mg/m <sup>3</sup> ) (WEL-STEL, EU)	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-190 U(C) (548 873)</li> <li>- DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)</li> <li>- NIOSH 1403 (ALCOHOLS IV) - 2003</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990</li> </ul>	
	BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Sk (WEL)	
IRL	Chemical Name	2-Butoxyethanol	
	OELV-8h: 20 ppm (98 mg/m <sup>3</sup> ) (OELV-8h, EU)	OELV-15min: 50 ppm (246 mg/m <sup>3</sup> ) (OELV- 15min, EU)	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-190 U(C) (548 873)</li> <li>- DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)</li> <li>- NIOSH 1403 (ALCOHOLS IV) - 2003</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990</li> </ul>	
	BLV: 200 mg/g creatinine (Butoxyacetic acid (BAA) in urine, h) (ACGIH-BEI)	Other information: Sk, IOELV	
M	Chemical Name	2-Butoxyethanol	
	OELV-8h: 20 ppm (98 mg/m <sup>3</sup> ) (OELV-8h, EU)	OELV-ST: 50 ppm (246 mg/m <sup>3</sup> ) (OELV-ST, EU)	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-190 U(C) (548 873)</li> <li>- DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)</li> <li>- NIOSH 1403 (ALCOHOLS IV) - 2003</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990</li> </ul>	
	BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Skin	
GB	Chemical Name	Acetic acid	
	WEL-TWA: 10 ppm (25 mg/m <sup>3</sup> ) (WEL-TWA, EU)	WEL-STEL: 20 ppm (50 mg/m <sup>3</sup> ) (WEL-STEL, EU)	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Acetic Acid 5/a (67 22 101)</li> <li>- Compur - KITA-216 S (549 194)</li> <li>- NIOSH 1603 (Acetic acid in workplace atmospheres) - 1994</li> <li>- OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 64-5 (2004)</li> </ul>	
	BMGV: ---	Other information: ---	
IRL	Chemical Name	Acetic acid	
	OELV-8h: 10 ppm (25 mg/m <sup>3</sup> ) (OELV-8h, EU)	OELV-15min: 20 ppm (50 mg/m <sup>3</sup> ) (OELV-15min, EU)	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Acetic Acid 5/a (67 22 101)</li> <li>- Compur - KITA-216 S (549 194)</li> <li>- NIOSH 1603 (Acetic acid in workplace atmospheres) - 1994</li> <li>- OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 64-5 (2004)</li> </ul>	

GB IRL M

Page 8 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

BLV: --- Other information: IOELV

Chemical Name	Acetic acid		
OELV-8h: 10 ppm (25 mg/m3) (OELV-8h, EU)	OELV-ST: 20 ppm (50 mg/m3) (OELV-ST, EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Acetic Acid 5/a (67 22 101)</li> <li>- Compur - KITA-216 S (549 194)</li> <li>- NIOSH 1603 (Acetic acid in workplace atmospheres) - 1994</li> <li>- OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 64-5 (2004)</li> </ul>		
BMGV: ---	Other information: ---		

Chemical Name	Ethanol		
WEL-TWA: 1000 ppm (1920 mg/m3)	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Alcohol 25/a Ethanol (81 01 631)</li> <li>- Compur - KITA-104 SA (549 210)</li> <li>- DFG (D) (Loesungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> <li>- DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> <li>- DFG Meth. Nr. 3 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> </ul>		
BMGV: ---	Other information: ---		

Chemical Name	Ethanol		
OELV-8h: 1000 ppm	OELV-15min: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Alcohol 25/a Ethanol (81 01 631)</li> <li>- Compur - KITA-104 SA (549 210)</li> <li>- DFG (D) (Loesungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> <li>- DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> <li>- DFG Meth. Nr. 3 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> </ul>		
BLV: ---	Other information: ---		

2-Butoxyethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	



Page 9 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Consumer	Human - inhalation	Short term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3	

**1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,017	mg/l	
	Environment - sediment, freshwater		PNEC	1,7	mg/kg dw	
	Environment - marine		PNEC	0,002	mg/l	
	Environment - sediment, marine		PNEC	0,17	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - soil		PNEC	0,331	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,17	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	56,25	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,25	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,72	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	112,5	mg/kg bw/d	

**Acetic acid**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	3,058	mg/l	
	Environment - marine		PNEC	0,3058	mg/l	
	Environment - periodic release		PNEC	30,58	mg/l	
	Environment - sediment, freshwater		PNEC	11,36	mg/kg dry weight	
	Environment - sediment, marine		PNEC	1,136	mg/kg dry weight	
	Environment - soil		PNEC	0,478	mg/kg dry weight	

Page 10 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

	Environment - sewage treatment plant		PNEC	85	mg/kg dry weight	
Consumer	Human - inhalation	Short term, local effects	DNEL	25	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	25	mg/kg	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3	

<b>Ethanol</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,75	mg/l	
	Environment - sewage treatment plant		PNEC	580	mg/l	
	Environment - sediment, freshwater		PNEC	3,6	mg/kg dry weight	
	Environment - soil		PNEC	0,63	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	0,38	g/kg feed	
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight	
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m3	

<b>Octamethylcyclotetrasiloxane</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1,5	µg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - soil		PNEC	0,54	mg/kg	
	Environment - sediment, freshwater		PNEC	3	mg/kg	
	Environment - marine		PNEC	0,15	µg/l	

Page 11 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

	Environment - sediment, marine		PNEC	0,3	mg/kg	
	Environment - oral (animal feed)		PNEC	41	mg/kg feed	
Consumer	Human - oral	Short term, systemic effects	DNEL	3,7	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,7	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	13	mg/kg	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	73	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |  
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |  
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |  
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

IRL - Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |  
 | OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |  
 | BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)): ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational

Page 12 of 30  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.08.2024 / 0004  
Replacing version dated / version: 11.03.2024 / 0003  
Valid from: 08.08.2024  
PDF print date: 08.08.2024  
Hydro Foam Sealant  
Art.: 465999

Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and Safety Executive (HSE), UK.

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Aspfx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

**M** - Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |

| OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE). |

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Page 13 of 30  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.08.2024 / 0004  
Replacing version dated / version: 11.03.2024 / 0003  
Valid from: 08.08.2024  
PDF print date: 08.08.2024  
Hydro Foam Sealant  
Art.: 465999

Chemical resistant protective gloves (EN ISO 374).  
Recommended  
Protective gloves made of butyl (EN ISO 374).  
Protective nitrile gloves (EN ISO 374).  
Protective PVC gloves (EN ISO 374).  
Minimum layer thickness in mm:  
> 0,5  
Permeation time (penetration time) in minutes:  
> 480  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.  
Protective hand cream recommended.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
If OES or MEL is exceeded.  
Gas mask filter A (EN 14387), code colour brown  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Orange
Odour:	Fruity
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	4,5
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Mixable
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,97 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

### 9.2 Other information

No information available at present.

Page 14 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

None known

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

#### Hydro Foam Sealant

Art.: 465999

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	13	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	2,2	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

#### 2-Butoxyethanol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	ATE	3	mg/l			Vapours
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Aerosol

Page 15 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	720	mg/kg bw/d			
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	
Aspiration hazard:						No
Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness, nausea

Page 16 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

**1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Mouse	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	500	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Symptoms:						gastrointestinal disturbances

**Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1

**Butene, homopolymer, hydrogenated**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Aspiration hazard:						Asp. Tox. 1

**Siloxanes and silicones, di-Me, 3-[3-[(3-coco amidopropyl)dimethylammonio]-2-hydroxypropoxy]propyl group-terminated, acetates (salts)**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat		



Page 17 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Acute toxicity, by inhalation:	LC50	55-60	mg/l/4h			Vapours
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:						Not sensitising, Analogous conclusion
Germ cell mutagenicity:					(Ames-Test)	Negative

**Amines, tallow alkyl, ethoxylated**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>300-2000	mg/kg	Rat		Analogous conclusion
Acute toxicity, by oral route:	ATE	500	mg/kg			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:						Eye Dam. 1

**Phenolpolyethoxylate**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	500-2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by oral route:	ATE	500	mg/kg			
Acute toxicity, by dermal route:	LD50	2140	mg/kg	Rabbit		
Aspiration hazard:						No
Symptoms:						gastrointestinal disturbances

**Acetic acid**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3310	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	11,4	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Corrosive
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Corrosive, Eye Dam. 1
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative

Page 18 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Symptoms:						acidosis, respiratory distress, burning of the membranes of the nose and throat, diarrhoea, disturbed heart rhythm, cornea opacity, cramps, circulatory collapse, stomach cramps, shock, nausea and vomiting.
-----------	--	--	--	--	--	---

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	51-124,7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Carcinogenicity:	NOAEL	>3000	mg/kg	Rat	OECD 451 (Carcinogenicity Studies)	24 mon
Reproductive toxicity:	NOAEL	5200	mg/kg bw/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAL	>20	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Male

Page 19 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1730	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Female
Symptoms:						respiratory distress, drowsiness, unconsciousness, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea

Octamethylcyclotetrasiloxane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2375	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	36	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rat	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:	NOAEL	150	mg/kg	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	inhalation
Reproductive toxicity:	NOAEL			Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Repr. 2
Reproductive toxicity (Developmental toxicity):	NOAEL	300	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	960	mg/kg bw/d	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	(21 d)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	150	mg/kg	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	



Page 21 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a.
Other information:	AOX			%			According to the recipe, contains no AOX.

<b>2-Butoxyethanol</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable

Page 22 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,2				Slight
12.3. Bioaccumulative potential:	Log Pow		0,81			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Not to be expected
12.4. Mobility in soil:	H (Henry)		0,0000016	atm*m3/mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

**1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,686	mg/l	Pimephales promelas	U.S. EPA ECOTOX Database	Analogous conclusion
12.1. Toxicity to fish:	LC50	96h	>10	mg/l	Cyprinus caprio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>8,6	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,39	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	1,2	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	>60	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Toxicity to bacteria:	EC50	6d	100	mg/l	activated sludge		Analogous conclusion

**Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Not readily biodegradable

Page 23 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

**Siloxanes and silicones, di-Me, 3-[3-[(3-coco amidopropyl)dimethylammonio]-2-hydroxypropoxy]propyl group-terminated, acetates (salts)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	12	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC50	72h	>969	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC10	18h	4168	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	DOC	28d	73	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable

**Amines, tallow alkyl, ethoxylated**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,13	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	0,17	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC10	21d	>0,001-0,01	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.2. Persistence and degradability:						OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**Phenolpolyethoxylate**

Page 24 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l		OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>128	mg/l	Daphnia pulex	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		60d	40-50	%		OECD 311 (Anaerobic Biodeg. of Organic Comp. in Digested Sludge - by Measurement of Gas Production)	
12.2. Persistence and degradability:						OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	79	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Acetic acid							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	75	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	88	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>300,82	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	24h	47	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>300,82	mg/l	Skeletonema costatum		
12.2. Persistence and degradability:		30d	>99	%			
12.2. Persistence and degradability:		20d	98	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,17				
12.3. Bioaccumulative potential:	BCF		<1				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	15min	11	mg/l	Photobacterium phosphoreum		



Page 25 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Toxicity to bacteria:	EC5	16h	2850	mg/l	Pseudomonas putida		
Other information:	BOD5		0,88	g/g			

Ethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	120h	250	mg/l	Brachydanio rerio	OECD 212 (Fish, Short-term Toxicity Test on Embryo and Sac-fry Stages)	
12.1. Toxicity to daphnia:	EC50	48h	5414	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	97	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		(-0,35) - (-0,32)				Bioaccumulation is unlikely (LogPow < 1).
12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				
12.4. Mobility in soil:	H (Henry)		0,000138				
12.4. Mobility in soil:	Koc		1,0				Highestimated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	
Other information:	COD		1,9	g/g			
Other information:	BOD5		1	g/g			

Octamethylcyclotetrasiloxane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	> 22	µg/l	Oncorhynchus mykiss		EPA OTS 797.1400

Page 26 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

12.1. Toxicity to fish:	NOEC/NOEL	>60d	>=0,004 4	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	> 15	µg/l	Daphnia magna		EPA OTS 797.1300
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>0,015	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC10	96h	0,022	mg/l			
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l			
12.2. Persistence and degradability:		28d	3,7	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF	28d	12400		Pimephales promelas		EPA OTS 797.1520
12.3. Bioaccumulative potential:	Log Pow		6,98				21,7 °C
12.5. Results of PBT and vPvB assessment							PBT-substance, vPvB-substance
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	ISO 8192	

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 08 discarded organic chemicals consisting of or containing hazardous substances

20 01 99 other fractions not otherwise specified

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:

3265

14.2. UN proper shipping name:

UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (AMINO FUNCTIONAL SILOXANE, TALLOW ALKYL AMINES, ETHOXYLATED)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

14.5. Environmental hazards:

environmentally hazardous

Tunnel restriction code:

E



Page 27 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

Classification code: C3  
 LQ: 1 L  
 Transport category: 2

**Transport by sea (IMDG-code)**

14.1. UN number or ID number: 3265  
 14.2. UN proper shipping name:  
 UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (AMINO FUNCTIONAL SILOXANE, TALLOW ALKYL AMINES, ETHOXYLATED)  
 14.3. Transport hazard class(es): 8  
 14.4. Packing group: II  
 14.5. Environmental hazards: environmentally hazardous  
 Marine Pollutant: Yes  
 EmS: F-A, S-B



**Transport by air (IATA)**

14.1. UN number or ID number: 3265  
 14.2. UN proper shipping name:  
 UN 3265 Corrosive liquid, acidic, organic, n.o.s. (AMINO FUNCTIONAL SILOXANE, TALLOW ALKYL AMINES, ETHOXYLATED)  
 14.3. Transport hazard class(es): 8  
 14.4. Packing group: II  
 14.5. Environmental hazards: Not applicable



**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

**14.7. Maritime transport in bulk according to IMO instruments**

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:  
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Regulation (EC) No 1907/2006, Annex XVII  
 Octamethylcyclotetrasiloxane  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 31,4 %

Observe incident regulations.

Page 28 of 30  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.08.2024 / 0004  
 Replacing version dated / version: 11.03.2024 / 0003  
 Valid from: 08.08.2024  
 PDF print date: 08.08.2024  
 Hydro Foam Sealant  
 Art.: 465999

National requirements/regulations on safety and health protection must be applied when using work equipment.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 2, 3, 11, 16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Skin Corr. 1B, H314	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H314 Causes severe skin burns and eye damage.

H361f Suspected of damaging fertility.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - inhalation

Skin Corr. — Skin corrosion

Eye Dam. — Serious eye damage

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - oral

Skin Irrit. — Skin irritation

Eye Irrit. — Eye irritation

Flam. Liq. — Flammable liquid

Asp. Tox. — Aspiration hazard

Aquatic Acute — Hazardous to the aquatic environment - acute

Repr. — Reproductive toxicity

Acute Tox. — Acute toxicity - dermal

Skin Sens. — Skin sensitization

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Page 29 of 30  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.08.2024 / 0004  
Replacing version dated / version: 11.03.2024 / 0003  
Valid from: 08.08.2024  
PDF print date: 08.08.2024  
Hydro Foam Sealant  
Art.: 465999

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
Safety data sheets for the constituent substances.  
ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).  
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
National Lists of Occupational Exposure Limits for each country as amended.  
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### **Any abbreviations and acronyms used in this document:**

acc., acc. to according, according to  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOX Adsorbable organic halogen compounds  
approx. approximately  
Art., Art. no. Article number  
ASTM ASTM International (American Society for Testing and Materials)  
ATE Acute Toxicity Estimate  
BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)  
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
BCF Bioconcentration factor  
BSEF The International Bromine Council  
CAS Chemical Abstracts Service  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
DOC Dissolved organic carbon  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
EC European Community  
ECHA European Chemicals Agency  
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
etc. et cetera  
EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
Koc Adsorption coefficient of organic carbon in the soil  
Kow octanol-water partition coefficient  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population

Page 30 of 30  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.08.2024 / 0004  
Replacing version dated / version: 11.03.2024 / 0003  
Valid from: 08.08.2024  
PDF print date: 08.08.2024  
Hydro Foam Sealant  
Art.: 465999

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
mg/kg bw mg/kg body weight  
mg/kg bw/d, mg/kg bw/day mg/kg body weight/day  
mg/kg dw mg/kg dry weight  
mg/kg wwt mg/kg wet weight  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute for Occupational Safety and Health (USA)  
NLP No-longer-Polymer  
NOEC, NOEL No Observed Effect Concentration/Level  
OECD Organisation for Economic Co-operation and Development  
org. organic  
OSHA Occupational Safety and Health Administration (USA)  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.