

Trade name: Kcu-Reifenschaum**Product no.:** 196612**Current version :** 1.0.1, issued: 21.12.2020**Replaced version:** 1.0.0, issued: 27.11.2020**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****Kcu-Reifenschaum****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

car care

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**

Koch-Chemie GmbH

Einsteinstr. 42

D-59423 Unna

Telephone no. +49-2303-9 86 70-0

Fax no. +49-2303-9 86 70-26

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

For information in the event of an emergency during transport:

+44 1865 407333

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aerosol 1; H222

Eye Irrit. 2; H319

Skin Irrit. 2; H315

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07

Signal word

Danger

Hazard statement(s)

Trade name: Kcu-Reifenschaum**Product no.:** 196612**Current version :** 1.0.1, issued: 21.12.2020**Replaced version:** 1.0.0, issued: 27.11.2020**Region:** GB

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3 Other hazards

PBT assessment

According to the information provided in the supply chain, the mixture does not contain > 0.1% of a substance that is considered to be PBT.

vPvB assessment

According to the information provided in the supply chain, the mixture does not contain > 0.1% of a substance that is considered to be vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	butane		pls. refer to footnote (2)
	106-97-8 203-448-7 601-004-00-0 01-2119474631-32	Flam. Gas 1; H220 Press. Gas compr.; H280	>= 5.00 - < 10.00 wt%
2	propane		
	74-98-6 200-827-9 601-003-00-5 01-2119486944-21	Flam. Gas 1; H220 Press. Gas compr.; H280	>= 5.00 - < 10.00 wt%
3	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched		
	69011-36-5 - - 01-2119976362-32	Aquatic Chronic 3; H412	>= 5.00 - < 10.00 wt%
4	ammonia		
	1336-21-6 215-647-6 007-001-01-2 01-2119488876-14	Aquatic Acute 1; H400 Skin Corr. 1B; H314 STOT SE 3; H335	< 2.50 wt%
5	octamethylcyclotetrasiloxane		pls. refer to footnote (1)
	556-67-2	Aquatic Chronic 4; H413	< 2.50 wt%

Trade name: Kcu-Reifenschaum**Product no.:** 196612**Current version :** 1.0.1, issued: 21.12.2020**Replaced version:** 1.0.0, issued: 27.11.2020**Region:** GB

209-136-7 014-018-00-1 -	Repr. 2; H361f*** Flam. Liq. 3; H226		
--------------------------------	---	--	--

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*, **, ***, ****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

(2) According to the latest state of knowledge and applying the criteria set out in annex I to Regulation (EC) No 1272/2008, the aforementioned classification is required. This classification goes beyond the classification set out in table 3, Annex VI to Regulation (CE) No 1272/2008.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	C, U	-	-	-
4	B	Skin Irrit. 2; H315: C >= 1% Aquatic Chronic 3; H412: C >= 2.5% STOT SE 3; H335: C >= 5%	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
4	350 mg/kg bodyweight		

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Ensure supply of fresh air. Remove affected person from the immediate area. Irregular breathing/no breathing: artificial respiration. Take medical treatment.

After skin contact

In case of contact with skin wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse out mouth and give plenty of water to drink. Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Extinguishing powder; Alcohol-resistant foam; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

Trade name: Kcu-Reifenschaum**Product no.:** 196612**Current version :** 1.0.1, issued: 21.12.2020**Replaced version:** 1.0.0, issued: 27.11.2020**Region:** GB

Vapours can form a highly flammable mixture with air. In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Drums can explode from steam pressure. Cool endangered containers with water spray jet. Run-off water from fire fighting must not be discharged into drains or enter surface water.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Do not inhale vapours/aerosols. Keep away from ignition sources.

For emergency responders

Personal protective equipment (PPE) - see section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. In case of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g., sand, kieselguhr, acid binder, universal binder, sawdust) and send for disposal.

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****General protective and hygiene measures**

Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke during work time. Wash hands before breaks and after work. Avoid contact with eyes and skin. Do not inhale aerosols. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Keep away from sources of heat and ignition. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Vapours can form an explosive mixture with air. Heating up leads to increase of pressure - danger of bursting.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight. Store in a dry place.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Keep in original packaging, tightly closed.

Incompatible products

Substances to be avoided, see section 10.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
List of approved workplace exposure limits (WELs) / EH40			
Butane			
	WEL short-term (15 min reference period)	1810	mg/m ³ 750 ppm
	WEL long-term (8-hr TWA reference period)	1450	mg/m ³ 600 ppm
	Comments	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	

DNEL, DMEL and PNEC values**DNEL values (worker)**

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched			69011-36-5
	dermal	Long term (chronic)	systemic	2080 mg/kg/day
	inhalative	Long term (chronic)	systemic	294 mg/m ³
2	ammonia			1336-21-6 215-647-6
	dermal	Short term (acut)	systemic	6.8 mg/kg/day
	with reference to: CAS 7664-41-7			
	dermal	Long term (chronic)	systemic	6.8 mg/kg/day
	with reference to: CAS 7664-41-7			
	inhalative	Short term (acut)	systemic	47.6 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Short term (acut)	local	36 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Long term (chronic)	systemic	47.6 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Long term (chronic)	local	14 mg/m ³
	with reference to: CAS 7664-41-7			

DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched			69011-36-5
	oral	Long term (chronic)	systemic	25 mg/kg/day
	dermal	Long term (chronic)	systemic	1250 mg/kg/day
	inhalative	Long term (chronic)	systemic	87 mg/m ³
2	ammonia			1336-21-6 215-647-6
	oral	Short term (acut)	systemic	6.8 mg/kg/day
	with reference to: CAS 7664-41-7			
	oral	Long term (chronic)	systemic	6.8 mg/kg/day
	with reference to: CAS 7664-41-7			
	dermal	Short term (acut)	systemic	68 mg/kg/day
	with reference to: CAS 7664-41-7			
	dermal	Long term (chronic)	systemic	68 mg/kg/day
	with reference to: CAS 7664-41-7			
	inhalative	Short term (acut)	systemic	23.8 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Short term (acut)	local	7.2 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Long term (chronic)	systemic	23.8 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Long term (chronic)	local	2.8 mg/m ³

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

with reference to: CAS 7664-41-7

PNEC values

No	Substance name	CAS / EC no
ecological compartment	Type	Value
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5
	water	fresh water
	water	marine water
	water	Aqua intermittent
	water	fresh water sediment
	water	marine water sediment
	soil	-
	sewage treatment plant	-
2	ammonia	1336-21-6 215-647-6
	water	fresh water
	with reference to: CAS: 7664-41-7	
	water	marine water
	with reference to: CAS: 7664-41-7	
	water	Aqua intermittent
	with reference to: CAS: 7664-41-7	

8.2 Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, local exhaust at the work station if necessary.

Personal protective equipment**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. Respiratory protection mask with combination filter.

Respirator ABEK/P2

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material nitrile rubber
Material thickness > 0.5 mm

Other

Chemical-resistant work clothes.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****State of aggregation**

liquid

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

Form/Colour			
Aerosol			
Odour			
characteristic			
pH value			
Value	10		
Boiling point / boiling range			
Value	-44.5 °C		
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	97 °C		
Ignition temperature			
No data available			
Explosive properties			
This product is not explosive. In and after use danger of production of inflammable compounds.			
Flammability			
No data available			
Lower explosion limit			
Value	1.5	% vol	
Upper explosion limit			
Value	10.9	% vol	
Vapour pressure			
Value	3600	hPa	
Reference temperature	20	°C	
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	0.935	g/cm ³	
Reference temperature	20	°C	
Solubility in water			
Comments	Not miscible or difficult to mix		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
	log Pow	appr.	1.8
	Method	QSAR	
	Source	ECHA	
2	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

log Pow	4.73	
Reference temperature	25	°C
Source	ECHA	

Viscosity

No data available

Particle characteristics

No data available

9.2 Other information**Other information**

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Generation of flammable vapor-air mixtures possible.

10.4 Conditions to avoid

Protect from heat and direct sunlight. Keep away sources of ignition.

10.5 Incompatible materials

Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
2	ammonia	1336-21-6	215-647-6
LD50	>	350	mg/kg bodyweight
Species	rat		
with reference to	CAS 7664-41-7		
Method	OECD 401		
Source	ECHA		
3	octamethylcyclotetrasiloxane	556-67-2	209-136-7
LD50	>	4800	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-	69011-36-5	-

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

hydroxy-, branched			
LD50	>	2000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
2	octamethylcyclotetrasiloxane	556-67-2	209-136-7
LD50	>	4640	mg/kg bodyweight
Species	rabbit		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
LC50	>	800000	ppmV
Duration of exposure	0.25 h		
State of aggregation	Gas		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
LC50	>	1600	mg/l
Duration of exposure	4 h		
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
LC50	>	36	mg/l
Duration of exposure	4 h		
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
Species	rabbit		
Method	Read-across		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	ammonia	1336-21-6	215-647-6
Duration of exposure	4 h		
Species	rabbit		
with reference to	CAS 7664-41-7		
Method	OECD 404		
Source	ECHA		
Evaluation	corrosive		
3	octamethylcyclotetrasiloxane	556-67-2	209-136-7
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
Species	rabbit		
Method	Read-across		
Source	ECHA		

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

Evaluation/classification	Based on available data, the classification criteria are not met.		
2	octamethylcyclotetrasiloxane	556-67-2	209-136-7
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
Route of exposure		Skin	
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	octamethylcyclotetrasiloxane	556-67-2	209-136-7
Route of exposure		Skin	
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Type of examination	In vitro Mammalian Chromosomal Aberration Test		
Species	Human Lymphocyte		
Method	OECD 473		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propane	74-98-6	200-827-9
Route of exposure		inhalational	
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	ammonia	1336-21-6	215-647-6
Duration of exposure		48	h
Type of examination	Bacterial Reverse Mutation Test		
Species	Salmonella typhimurium TA98, TA100, TA1535, TA1537		
with reference to	CAS 7664-41-7		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Route of exposure		inhalational	
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

2	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Aspiration hazard

No data available

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
LC50		2.5	mg/l
Duration of exposure		96	h
Species	Danio rerio		
Method	EU C.1		
Source	ECHA		

Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
EC20		1.097	mg/l
Duration of exposure		30	day(s)
Species	Pimephales promelas		
Method	OECD 210		
Source	ECHA		

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
EC50		1.5	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	EU C.2		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
EC20		0.74	mg/l
Species	Daphnia magna		
Method	QSAR		
Source	ECHA		

Toxicity to algae (acute)			
No data available			

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No data available			

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Type	aerobic biodegradation		
Value		50	%
Duration		3.46	d
Method	QSAR		
Source	ECHA		
2	propane	74-98-6	200-827-9
Type	aerobic biodegradation		
Value		50	%
Duration		3	d
Method	QSAR		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	octamethylcyclotetrasiloxane	556-67-2	209-136-7
BCF		12400	
Species	Pimephales promelas		
Source	ECHA		

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
log Pow	appr.	1.8	
Method	QSAR		
Source	ECHA		

Trade name: Kcu-Reifenschaum**Product no.:** 196612**Current version :** 1.0.1, issued: 21.12.2020**Replaced version:** 1.0.0, issued: 27.11.2020**Region:** GB

2	Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	-
log Pow		4.73	
Reference temperature		25	°C
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	According to the information provided in the supply chain, the mixture does not contain > 0.1% of a substance that is considered to be PBT.
vPvB assessment	According to the information provided in the supply chain, the mixture does not contain > 0.1% of a substance that is considered to be vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.7 Other information

Other information
Do not discharge into the drains or waters and do not store on public depositories.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

No data available.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

Class	2
Classification code	5F
UN number	UN1950
Proper shipping name	AEROSOLS
Tunnel restriction code	D
Label	2.1

14.2 Transport IMDG

Class	2
UN number	UN1950
Proper shipping name	AEROSOLS
EmS	F-D, S-U
Label	2.1

14.3 Transport ICAO-TI / IATA

Class	2.1
UN number	UN1950
Proper shipping name	Aerosols, flammable
Label	2.1

14.4 Other information

Trade name: Kcu-Reifenschaum

Product no.: 196612

Current version : 1.0.1, issued: 21.12.2020

Replaced version: 1.0.0, issued: 27.11.2020

Region: GB

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
EU regulations**Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

The product contains following substance(s) meeting the criteria in Article 57 in association with Article 59 of the REACH regulation ((EC) 1907/2006) that are placed on the list of candidates considered for inclusion in annex XIV (substances subject to Authorisation).

No	Substance name	CAS no.	EC no.
1	octamethylcyclotetrasiloxane	556-67-2	209-136-7

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3
--	------

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	octamethylcyclotetrasiloxane	556-67-2	209-136-7	70

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P3a
--	-----

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.
Employment restrictions, according to the regulations for protection of expectant and nursing mothers and the youth health and safety regulations, serving to protect against hazardous materials, should be observed.
The surfactants contained in this product comply with the DetVO 648/2004/EC.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

Trade name: Kcu-Reifenschaum**Product no.:** 196612**Current version :** 1.0.1, issued: 21.12.2020**Replaced version:** 1.0.0, issued: 27.11.2020**Region:** GB

H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

B	Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.
C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
U	When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Creation of the safety data sheet

UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 770865