- GB (RL) M

Page 1 of 25

Art.: 196612

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Kcu-Reifenschaum

Art.: 196612

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Cleaner

### **Uses advised against:**

No information available at present.

### 1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna

Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26

info@koch-chemie.com www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

### 1.4 Emergency telephone number

### **Emergency information services / official advisory body:**

(RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

### Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Aerosol 1 H222-Extremely flammable aerosol.

Aerosol 1 H229-Pressurised container: May burst if heated.

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

®®™M

Page 2 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum Art.: 196612



H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH208-Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

# n.a. 3.2 Mixtures

Ammonia	Substance for which an EU exposure limit value
	applies.
Registration number (REACH)	01-2119982985-14-XXXX
Index	007-001-01-2
EINECS, ELINCS, NLP, REACH-IT List-No.	215-647-6
CAS	1336-21-6
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Skin Corr. 1B, H314
factors	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 2, H411
Specific Concentration Limits and ATE	STOT SE 3, H335: >=5 %

1,2-benzisothiazol-3(2H)-one	
Registration number (REACH)	
Index	613-088-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	220-120-9
CAS	2634-33-5
content %	<0,036

- GB (RL) M

Page 3 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 2, H330
factors	Acute Tox. 4, H302
	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Skin Sens. 1A, H317
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,036 %
	ATE (oral): 450 mg/kg
	ATE (as inhalation, Dusts or mist): 0,21 mg/l/4h
	ATE (as inhalation, Vapours): 0,5 mg/l/4h

2-methylisothiazol-3(2H)-one	
Registration number (REACH)	01-2120764690-50-XXXX
Index	613-326-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	220-239-6
CAS	2682-20-4
content %	<0,0015
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH071
factors	Acute Tox. 2, H330
	Acute Tox. 3, H301
	Acute Tox. 3, H311
	Skin Corr. 1B, H314
	Eye Dam. 1, H318
	Skin Sens. 1A, H317
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,0015 %
	ATE (oral): 120 mg/kg
	ATE (dermal): 242 mg/kg
	ATE (as inhalation, Dusts or mist): 0,11 mg/l/4h
	ATE (as inhalation, Vapours): 0,5 mg/l/4h

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

- GB (RL M)

Page 4 of 25

Art.: 196612

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Allergic reaction possible.

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

## Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

## Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of phosphorus

Ammonia

Toxic gases

Possible build up of explosive/highly flammable vapour/air mixture.

Danger of bursting (explosion) when heated

# 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### SECTION 6: Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures

# 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

## **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

## **6.2 Environmental precautions**

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

- GB (RL M)-

Page 5 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum Art.: 196612

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

# 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Observe special storage conditions.

Do not store with flammable or self-igniting materials.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well-ventilated place.

Store cool.

### 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

	A!-		
Chemical Name	Ammonia		
WEL-TWA: NH3 25 ppm (18 mg	g/m3) (WEL-	WEL-STEL: NH3 35 ppm (25 mg/m3) (WEL-	
TWA), 20 ppm (14 mg/m3) (EU)		STEL), 50 ppm (36 mg/m3) (EU)	
Monitoring procedures:	-	Draeger - Ammonia 0,25/a (81 01 711)	
	-	Draeger - Ammonia 0,5%/a (CH 31 901)	
	-	Draeger - Ammonia 2/a (67 33 231)	
	-	Draeger - Ammonia 5/a (CH 20 501)	
	-	Draeger - Ammonia 5/b (81 01 941)	
	-	Compur - KITA-105 SA (548 642)	
	-	Compur - KITA-105 SB (548 659)	
	-	Compur - KITA-105 SC (548 667)	
	-	Compur - KITA-105 SD (548 675)	
	-	Compur - KITA-105 SH (548 683)	
	-	Compur - KITA-105 SM (548 691)	
	-	NIOSH 6015 (Ammonia) - 1990	
	-	NIOSH 6016 (AMMONIA by IC) - 2016	
	-	OSHA ID-164 (Ammonia in Workplace Atmospheres) - 1988	
	-	OSHA ID-188 (Ammonia in workplace atmospheres - solid sorbent) - 200	2
BMGV:		Other information:	
(R) Chamical Name	Λ i.a	·	

© Chemical Name Ammonia

GB RLM-

GD (RL) (M)	
Page 6 of 25 Safety data sheet according to Regulation (EC)	No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 04.11.2024 / 0001	
Replacing version dated / version: 04.11.2024	/ 0001
Valid from: 04.11.2024	
PDF print date: 05.11.2024	
Kcu-Reifenschaum	
Art.: 196612	
OELV-8h: NH3 20 ppm (14 mg/m3) (OELV-8	h, OELV-15min: NH3 50 ppm (36 mg/m3) (OELV-
EU)	15min, EU)
Monitoring procedures:	- Draeger - Ammonia 0,25/a (81 01 711)
	- Draeger - Ammonia 0,5%/a (CH 31 901)
	- Draeger - Ammonia 2/a (67 33 231)
	<ul><li>Draeger - Ammonia 5/a (CH 20 501)</li><li>Draeger - Ammonia 5/b (81 01 941)</li></ul>
	- Compur - KITA-105 SA (548 642)
	- Compur - KITA-105 SB (548 659)
	- Compur - KITA-105 SC (548 667)
	- Compur - KITA-105 SD (548 675)
	- Compur - KITA-105 SH (548 683)
	- Compur - KITA-105 SM (548 691)
	<ul> <li>NIOSH 6015 (Ammonia) - 1990</li> <li>NIOSH 6016 (AMMONIA by IC) - 2016</li> </ul>
	- OSHA ID-164 (Ammonia in Workplace Atmospheres) - 1988
	- OSHA ID-188 (Ammonia in workplace atmospheres – solid sorbent) - 2002
BLV:	Other information: IOELV
M Chemical Name Ammonia	
OELV-8h: NH3 20 ppm (14 mg/m3) (OELV-8	
EU)	EU) - Draeger - Ammonia 0,25/a (81 01 711)
Monitoring procedures:	- Draeger - Ammonia 0,25/a (61 01 711) - Draeger - Ammonia 0,5%/a (CH 31 901)
	- Draeger - Ammonia 0,5 %a (61737 901) - Draeger - Ammonia 2/a (67 33 231)
	- Draeger - Ammonia 5/a (CH 20 501)
	- Draeger - Ammonia 5/b (81 01 941)
	- Compur - KITA-105 SA (548 642)
	- Comput - KITA-105 SB (548 659)
	- Compur - KITA-105 SC (548 667) - Compur - KITA-105 SD (548 675)
	- Comput - KITA-103 3D (346 673) - Compur - KITA-105 SH (548 683)
	- Compur - KITA-105 SM (548 691)
	- NIOSH 6015 (Ammonia) - 1990
	- NIOSH 6016 (AMMONIA by IC) - 2016
	- OSHA ID-164 (Ammonia in Workplace Atmospheres) - 1988
BMGV:	- OSHA ID-188 (Ammonia in workplace atmospheres – solid sorbent) - 2002  Other information:
-	Other information:
© Chemical Name Butane	MEI OTEL . 750 mm (4040 / 0)
WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3) Compur - KITA-221 SA (549 459)
Monitoring procedures:	- OSHA PV2010 (n-Butane) - 1993
BMGV:	Other information:
© Chemical Name Butane OELV-8h:	OELV-15min: 1000 ppm
Monitoring procedures:	- Compur - KITA-221 SA (549 459)
	- OSHA PV2010 (n-Butane) - 1993
BLV:	Other information:
© Chemical Name Propane	
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL:
Monitoring procedures:	- Compur - KITA-125 SA (549 954)
	- OSHA PV2077 (Propane) - 1990
BMGV:	Other information:
® Chemical Name Isobutane	
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL:
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)
BMGV:	Other information:
R Chemical Name Isobutane	
OELV-8h:	OELV-15min: 1000 ppm

®®®™

Page 7 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum Art.: 196612

Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)
BLV:	Other information:

Ammonia		F	<b>D</b> • • •		111.4	N1 4
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	0,0011	mg/l	
	Environment - marine		PNEC	0,0011	mg/l	
	Environment - periodic release		PNEC	0,0068	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	2,8	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	7,2	mg/m3	
Consumer	Human - dermal	Short term, local effects	DNEL	68	mg/kg body weight/day	
Consumer	Human - dermal	Short term, systemic effects	DNEL	68	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	23,8	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	23,8	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	6,8	mg/kg body weight/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,8	mg/kg body weight/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	6,8	mg/kg body weight/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	6,8	mg/kg body weight/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	47,6	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	36	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	47,6	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	14	mg/m3	

1,2-benzisothiazol-3(2H	)-one					
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	0,00403	mg/l	
	Environment - marine		PNEC	0,00040 3	mg/l	
	Environment - sediment, freshwater		PNEC	0,0499	mg/kg dw	
	Environment - sediment, marine		PNEC	0,00499	mg/kg dw	
	Environment - soil		PNEC	3	mg/kg dw	

- GB (RL) M

Page 8 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

	Environment - sewage treatment plant		PNEC	1,03	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,0011	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,345	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,2	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,966	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,81	mg/m3	

2-methylisothiazol-3(2H	)-one					
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	3,39	μg/l	
	Environment - marine		PNEC	3,39	μg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,39	μg/l	
	Environment - sewage treatment plant		PNEC	0,23	mg/l	
	Environment - soil		PNEC	0,0471	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,021	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,043	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,027	mg/kg body weight/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,053	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,021	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,043	mg/m3	

- United Kingdom | WEL-TWA = Workplace Exposure Limit Long-term exposure limit 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
- (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure

- GB (RL) M

Page 9 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

possible. |

- Ireland/Éire | OELV-8h = Occupational Exposure Limit Value 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | OELV-15min = Occupational Exposure Limit Value 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- | BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)):
  | ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of
  | Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational
  | Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European
  | Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and
  | Safety Executive (HSE), UK.
- (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- | Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.
- Malta | OELV-8h = Occupational Exposure Limit Value 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | OELV-ST = Occupational Exposure Limit Value Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom). (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
- (EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE), (EU15) = Substantial contribution to the total body burden via dermal exposure possible.

### 8.2 Exposure controls

- GB (RL) M

Page 10 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum Art.: 196612

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0,5

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

-GB (RL M)-

Page 11 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

Colour: White Odour: Ammonia

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: -44,5 °C

Flammability: Does not apply to aerosols.

Lower explosion limit: 1,5 Vol-% Upper explosion limit: 8,5 Vol-% Flash point: -60 °C Auto-ignition temperature: 365 °C

Decomposition temperature:

There is no information available on this parameter.

pH: Mixture is non-polar/aprotic. Kinematic viscosity: Does not apply to aerosols.

Solubility: Mixable

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: 2100 hPa (20°C)
Density and/or relative density: 0,93 g/cm3 (20°C)

Relative vapour density:

Particle characteristics:

Does not apply to aerosols.

Does not apply to aerosols.

9.2 Other information

Explosives: Product is not explosive. Possible build up of explosive/highly

flammable vapour/air mixture. 10,2 % (Organic solvents)

Solvents content:

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

# 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

# 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.

®®®™

Page 12 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum Art.: 196612

Reproductive toxicity:			n.d.a.
Specific target organ toxicity -			n.d.a.
single exposure (STOT-SE):			
Specific target organ toxicity -			n.d.a.
repeated exposure (STOT-			
RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Ammonia						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	350	mg/kg	Rat		
Acute toxicity, by oral route:	LDLo	550	mg/kg	Cat		
Acute toxicity, by oral route:	LDLo	43	mg/kg	Human being		
Acute toxicity, by inhalation:	LCLo	5000	ppm	Human being		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Corrosive
Serious eye damage/irritation:				Rabbit		Risk of serious damage to eyes.
Respiratory or skin				Guinea pig		Not sensitizising
sensitisation:						3
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies)	Negative
Reproductive toxicity:	NOAEL	408	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	
Symptoms:						asthmatic symptoms, respiratory distress, unconsciousnes s, burning of the membranes of the nose and throat, vomiting, cornea opacity, coughing, cramps, circulatory collapse, shock, nausea

1,2-benzisothiazol-3(2H)-one							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	490	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)		
Acute toxicity, by oral route:	ATE	450	mg/kg				
Acute toxicity, by dermal route:	LD50	4115	mg/kg	Rat			

- GB (RL M)-

Page 13 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	0,21	mg/l/4h		OECD 403 (Acute Inhalation Toxicity)	Dusts or mist
Skin corrosion/irritation:				Rabbit		Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig		Yes (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells In Vivo)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	150	mg/kg/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Symptoms:						vomiting, headaches, gastrointestinal disturbances, nausea

2-methylisothiazol-3(2H)-on	е					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	120	mg/kg	Rat	U.S. EPA Guidline OPPTS 870.1100	Female
Acute toxicity, by oral route:	LD50	183	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	120	mg/kg			
Acute toxicity, by dermal route:	ATE	242	mg/kg			
Acute toxicity, by dermal route:	LD50	242	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	0,11	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	0,11	mg/l/4h			Dusts or mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Corrosive
Serious eye damage/irritation:				Rabbit		Risk of serious damage to eyes.
Serious eye damage/irritation:						Risk of serious damage to eves.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)

-GB (RL M)-

Page 14 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024

Kcu-Reifenschaum Art.: 196612

Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation	
					Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Reproductive toxicity:	NOAEL	200	ppm	Rat	OECD 416 (Two-	
					generation	
					Reproduction Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	60	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-					Dose 90-Day Oral	
RE):					Toxicity Study in	
					Rodents)	
Symptoms:						mucous
						membrane
						irritation,
						watering eyes

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Rat	OECD 474	Negative
					(Mammalian	
					Erythrocyte	
					Micronucleus Test)	
Specific target organ toxicity -	NOAEC	21,394	mg/l	Rat	OECD 422	
repeated exposure (STOT-					(Combined Repeated	
RE), inhalat.:					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	
Aspiration hazard:						No

-GB (RL M)-

Page 15 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Kcu-Reifenschaum Art.: 196612

Symptoms:		ataxia,
		breathing
		difficulties,
		drowsiness,
		unconsciousnes
		s, frostbite,
		disturbed heart
		rhythm,
		headaches,
		cramps,
		intoxication,
		dizziness,
		nausea and
		vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male,
						Analogous
						conclusion
Skin corrosion/irritation:						Not irritant
Serious eye						Not irritant
damage/irritation:						
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Reproductive toxicity	NOAEC	21,641	mg/l		OECD 422	
(Developmental toxicity):					(Combined Repeated	
					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	
Specific target organ toxicity -	NOAEL	7,214	mg/l	Rat	OECD 422	
repeated exposure (STOT-					(Combined Repeated	
RE), inhalat.:					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	
Specific target organ toxicity -	LOAEL	21,641	mg/l	Rat	OECD 422	
repeated exposure (STOT-					(Combined Repeated	
RE), inhalat.:					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
A					Test)	N
Aspiration hazard:						No

- GB (RL M)-

Page 16 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

Symptoms:	breathing difficulties, unconsciousnes s, frostbite, headaches, cramps, mucous membrane
	irritation, dizziness, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						unconsciousnes, frostbite, headaches, cramps, dizziness, nausea and vomiting.

## 11.2. Information on other hazards

Kcu-Reifenschaum Art.: 196612						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting	-					Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Kcu-Reifenschaum							
Art.: 196612							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.

- GB (RL M)

Page 17 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024

Kcu-Reifenschaum Art.: 196612

12.1. Toxicity to	
daphnia:	
12.1. Toxicity to algae: n.	.d.a.
12.2. Persistence and	he
degradability:	urfactant(s)
	ontained in
	nis mixture
	omplies(compl
	) with the
	iodegradability
cr	riteria as laid
da	own in
	Regulation
	EC)
	lo.648/2004
	n detergents.
	ata to support
	nis assertion
	re held at the
	isposal of the
	ompetent
	uthorities of
	ne Member
	States and will
	e made
	vailable to
	nem, at their
	irect request
	r at the
	equest of a
	etergent nanufacturer.
	.d.a.
potential:	.u.a.
	.d.a.
	.d.a.
and vPvB assessment	.a.a.
	oes not apply
	mixtures.
12.7. Other adverse	lo information
	vailable on
	ther adverse
ef	ffects on the
er	nvironment.

Ammonia							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	8,2	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	0,53	mg/l	Oncorhynchus mykiss		Anhydrous substance
12.1. Toxicity to fish:	NOEC/NOEL	30d	<0,048	mg/l	lctalurus punctatus	OECD 215 (Fish, Juvenile Growth Test)	
12.1. Toxicity to fish:	LC50	96h	0,16-1,1	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	

®®®™

Page 18 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum Art.: 196612

12.1. Toxicity to daphnia:	EC50	48h	24-25,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,42	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	0,66	mg/l	Daphnia pulex		
12.1. Toxicity to daphnia:	EC50	48h	1,16	mg/l	Daphnia pulicaria		Anhydrous substance
12.1. Toxicity to algae:	EC50	72h	>1000		Skeletonema costatum	ISO 10253	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>1000	mg/l	Skeletonema costatum	ISO 10253	
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-1,14			Regulation (EC) 440/2008 A.8 (PARTITION COEFFICIENT)	Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	5min	1,16	mg/l	Photobacterium phosphoreum		Anhydrous substance
Water solubility:					<u> </u>		Soluble

1,2-benzisothiazol-3(2H)-one									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:	LC50	96h	0,8-2,18	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)			
12.1. Toxicity to daphnia:	EC50	48h	1,1-4,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)			
12.1. Toxicity to algae:	ErC50	24h	0,1087	mg/l	Pseudokirchnerie Ila subcapitata				
12.1. Toxicity to algae:	ErC10	24h	0,0268	mg/l	Pseudokirchnerie Ila subcapitata				
12.2. Persistence and degradability:						OECD 303 (Simulation Test - Aerobic Sewage Treatment)	Hardly biodegradable		
12.3. Bioaccumulative potential:	Log Pow		1,11				A notable biological accumulation potential is not to be expected (LogPow 1-3).		
Toxicity to bacteria:	EC50	16h	0,4	mg/l	Pseudomonas putida		. 5		

2-methylisothiazol-3(2	2-methylisothiazol-3(2H)-one									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,38	mg/l	Pimephales promelas	OECD 210 (Fish, Early-Life Stage Toxicity Test)				

- GB (RL M

Page 19 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

12.1. Toxicity to fish:	LC50	96h	4,77	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,55	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,359	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,445	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,03	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	120h	0,05	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		48h	97	%		OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	Readily biodegradable
12.2. Persistence and degradability:			< 0,08	d		OECD 307 (Aerobic and Anaerobic Transformation in Soil)	
12.2. Persistence and degradability:			1,28-2,1	d		OECD 308 (Aerobic and Anaerobic Transformation in Aquatic Sediment Systems)	
12.2. Persistence and degradability:			4,1	d		OECD 309 (Aerobic Mineralisation in Surface Water - Simulation Biodegradation Test)	
12.2. Persistence and degradability:		28d	0,32	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,32			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	Slight
12.3. Bioaccumulative potential:	BCF		3,16			,	calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

- GB (RL) (M)

Page 20 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

Toxicity to bacteria:	EC50	3h	34,6	mg/l	activated sludge	DIN 38412-3 (TTC-Test)
Toxicity to bacteria:	EC20	3h	2,8	mg/l	activated sludge	DIN 38412-3 (TTC-Test)

Butane									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR			
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR			
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is no to be expected (LogPow 1-3).		
12.4. Mobility in soil:							Not to be expected		
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance		

Propane	Propane								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).		
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance		

Isobutane								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l				
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l				
12.2. Persistence and							Readily	
degradability:							biodegradable	
12.3. Bioaccumulative							A notable	
potential:							biological	
							accumulation	
							potential is not	
							to be expected	
							(LogPow 1-3).	
12.5. Results of PBT							No PBT	
and vPvB assessment							substance, No	
							vPvB substance	

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be

# KochChemie<sup>6</sup> **ExcellenceForExperts.**

GB (RL) M

Page 21 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Art.: 196612

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations. Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

# **SECTION 14: Transport information**

#### **General statements**

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1 14.4. Packing group:

14.5. Environmental hazards: Not applicable

Tunnel restriction code: 5F Classification code: LO: 1 L Transport category: 2

Transport by sea (IMDG-code)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name:

**UN 1950 AEROSOLS** 

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: Not applicable Marine Pollutant: Not applicable F-D, S-U FmS.

Transport by air (IATA)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name: UN 1950 Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: 14.5. Environmental hazards: Not applicable

# 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

### 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture







- GB (RL M

Page 22 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

#### Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be

considered according to storage, handling etc.):

our order our decorraining to ottorage, marraining ottor,											
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of								
		dangerous substances as	dangerous substances as								
		referred to in Article 3(10) for	referred to in Article 3(10) for								
		the application of - Lower-tier	the application of - Upper-tier								
		requirements	requirements								
P3a	11.1	150 (netto)	500 (netto)								

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Directive 2012/10/LO ( Geveso III ), Affilex 1, 1 art 2 - 11lls product contains the substances listed below.				
Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity
			(tonnes) for the	(tonnes) for the
			application of - Lower-	application of - Upper-
			tier requirements	tier requirements
18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

10,42 %

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

**REGULATION (EC) No 648/2004** 

5 % or over but less than 15 % aliphatic hydrocarbons less than 5 % non-ionic surfactants

BENZISOTHIAZOLINONE METHYLISOTHIAZOLINONE

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label.

Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012.

Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods.

These are indicated in the approval of the active substance.

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

Revised sections:

n.a.

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

(B) (RL) (M)

Page 23 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H330 Fatal if inhaled.

H317 May cause an allergic skin reaction.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Aerosol — Aerosols

Skin Corr. — Skin corrosion Eye Dam. — Serious eye damage

Aquatic Acute — Hazardous to the aquatic environment - acute

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - inhalation

Acute Tox. — Acute toxicity - oral

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Acute Tox. — Acute toxicity - dermal

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approximately approx. Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

# KochChemie<sup>®</sup>

# **ExcellenceForExperts.**

- GB (RL M)-

Page 24 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of

substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight mg/kg wwt mg/kg wet weight

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

- GB (RL) M

Page 25 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 04.11.2024 / 0001

Replacing version dated / version: 04.11.2024 / 0001

Valid from: 04.11.2024 PDF print date: 05.11.2024 Kcu-Reifenschaum

Art.: 196612

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

# Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.