

Page 1 of 27
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.11.2022 / 0001
Replacing version dated / version: 29.11.2022 / 0001
Valid from: 29.11.2022
PDF print date: 29.11.2022
NanoMagic Twin Wax
Art.: 220999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

NanoMagic Twin Wax
Art.: 220999

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Preservatives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH
Einsteinstrasse 42
59423 Unna
Telefon: +49 (0) 2303 / 9 86 70 - 0
Fax: +49 (0) 2303 / 9 86 70 - 26
info@koch-chemie.com
www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Skin Corr.	1B	H314-Causes severe skin burns and eye damage.
Eye Dam.	1	H318-Causes serious eye damage.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H314-Causes severe skin burns and eye damage. H412-Harmful to aquatic life with long lasting effects.

P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.

P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

EUH208-Contains Tetramethyl acetyloctahydronaphthalenes (OTNE). May produce an allergic reaction.

Acetic acid

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated

2-Butoxyethanol

2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

2-Butoxyethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	203-905-0
CAS	111-76-2
content %	25-<50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Specific Concentration Limits and ATE	ATE (oral): 1200 mg/kg

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)

Page 3 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Registration number (REACH)	01-2119983493-26-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	939-685-4
CAS	---
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	102782-92-3
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

SILICONE QUATERNIUM-17	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	519142-86-0
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Chronic 2, H411

Acetic acid	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475328-30-XXXX
Index	607-002-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	200-580-7
CAS	64-19-7
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
Specific Concentration Limits and ATE	Skin Corr. 1A, H314: >=90 % Skin Corr. 1B, H314: >=25 % Skin Irrit. 2, H315: >=10 % Eye Irrit. 2, H319: >=10 %

Tetramethyl acetyloctahydronaphthalenes (OTNE)	
Registration number (REACH)	01-2119489989-04-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	915-730-3
CAS	---
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411

Decamethylcyclopentasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119511367-43-XXXX

Page 4 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	208-764-9
CAS	541-02-6
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	---

Dodecamethylcyclohexasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119517435-42-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	208-762-8
CAS	540-97-6
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	---

Octamethylcyclotetrasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119529238-36-XXXX
Index	014-018-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	209-136-7
CAS	556-67-2
content %	0,01-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 Avoid mouth-to-mouth resuscitation.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.
 Cauterizations not treated lead to wounds difficult to heal.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.
 Protect uninjured eye.
 Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Page 5 of 27
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.11.2022 / 0001
Replacing version dated / version: 29.11.2022 / 0001
Valid from: 29.11.2022
PDF print date: 29.11.2022
NanoMagic Twin Wax
Art.: 220999

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.
Corrosive burns on skin as well as mucous membrane possible.

Necrosis

Allergic reaction

Risk of serious damage to eyes.

Corneal damage.

Danger of blindness.

Pain in the mouth and throat

Gastrointestinal disturbances

Oesophageal perforation

Gastric perforation

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Handle and open container with care.

There should be an eyewash station and safety shower located near the area of use.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect from frost.

Store in a dry place.

Observe special storage conditions.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

GB	Chemical Name	2-Butoxyethanol	
	WEL-TWA: 25 ppm (123 mg/m ³) (WEL), 20 ppm (98 mg/m ³) (EU)	WEL-STEL: 50 ppm (246 mg/m ³) (WEL, EU)	---
	Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-190 U(C) (548 873) - DFG Meth.-Nr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990 	
	BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Sk (WEL)	

IRL	Chemical Name	2-Butoxyethanol	
	OELV-8h: 20 ppm (98 mg/m ³) (OELV-8h, EU)	OELV-15min: 50 ppm (246 mg/m ³) (OELV-15min, EU)	---
	Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-190 U(C) (548 873) - DFG Meth.-Nr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990 	
	BLV: 200 mg/g creatinine (Butoxyacetic acid (BAA) in urine, h) (ACGIH-BEI)	Other information: Sk, IOELV	

GB IRL M

Page 7 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Chemical Name		2-Butoxyethanol	
OELV-8h:	20 ppm (98 mg/m3) (OELV-8h, UE)	OELV-ST:	50 ppm (246 mg/m3) (OELV-ST, UE) ---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-190 U(C) (548 873) - DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990 		
BMGV:	240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information:	Skin

Chemical Name		Acetic acid	
WEL-TWA:	10 ppm (25 mg/m3) (WEL, EU)	WEL-STEL:	20 ppm (50 mg/m3) (WEL, EU) ---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Acetic Acid 5/a (67 22 101) - Compur - KITA-216 S (549 194) - NIOSH 1603 (Acetic acid in workplace atmospheres) - 1994 - OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 64-5 (2004) 		
BMGV:	---	Other information:	---

Chemical Name		Acetic acid	
OELV-8h:	10 ppm (25 mg/m3) (OELV-8h, EU)	OELV-15min:	20 ppm (50 mg/m3) (OELV-15min, EU) ---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Acetic Acid 5/a (67 22 101) - Compur - KITA-216 S (549 194) - NIOSH 1603 (Acetic acid in workplace atmospheres) - 1994 - OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 64-5 (2004) 		
BLV:	---	Other information:	IOELV

Chemical Name		Acetic acid	
OELV-8h:	10 ppm (25 mg/m3) (OELV-8h, UE)	OELV-ST:	20 ppm (50 mg/m3) (OELV-ST, UE) ---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Acetic Acid 5/a (67 22 101) - Compur - KITA-216 S (549 194) - NIOSH 1603 (Acetic acid in workplace atmospheres) - 1994 - OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 64-5 (2004) 		
BMGV:	---	Other information:	---

2-Butoxyethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	

Page 8 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3	

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,017	mg/l	
	Environment - sediment, freshwater		PNEC	1,7	mg/kg dw	
	Environment - marine		PNEC	0,002	mg/l	
	Environment - sediment, marine		PNEC	0,17	mg/kg dw	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - soil		PNEC	0,331	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,17	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	56,25	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,25	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,72	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	112,5	mg/kg bw/d	

Tetramethyl acetyloctahydronaphthalenes (OTNE)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0028	mg/l	
	Environment - marine		PNEC	0,00028	mg/l	
	Environment - sediment, freshwater		PNEC	3,73	mg/kg	
	Environment - sediment, marine		PNEC	0,75	mg/kg	

Page 9 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

	Environment - soil		PNEC	0,705	mg/kg	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,1011	mg/cm2	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1,76	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,73	mg/kg body weight/day	

Decamethylcyclopentasiloxane

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - sediment, freshwater		PNEC	11	mg/kg	
	Environment - sediment, marine		PNEC	1,1	mg/kg	
	Environment - soil		PNEC	2,54	mg/kg	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - oral (animal feed)		PNEC	16	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,3	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	4,3	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,3	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	4,3	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	97,3	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	24,2	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	97,3	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	24,2	mg/m3	

Dodecamethylcyclohexasiloxane

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sediment, freshwater		PNEC	2,826	mg/kg dw	
	Environment - sediment, marine		PNEC	0,282	mg/kg dw	
	Environment - soil		PNEC	3,336	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,7	mg/kg bw/d	

Page 10 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Consumer	Human - inhalation	Short term, local effects	DNEL	1,5	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,3	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	6,1	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	11	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1,22	mg/m ³	

Octamethylcyclotetrasiloxane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1,5	µg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - soil		PNEC	0,54	mg/kg	
	Environment - sediment, freshwater		PNEC	3	mg/kg	
	Environment - marine		PNEC	0,15	µg/l	
	Environment - sediment, marine		PNEC	0,3	mg/kg	
	Environment - oral (animal feed)		PNEC	41	mg/kg feed	
Consumer	Human - oral	Short term, systemic effects	DNEL	3,7	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,7	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	13	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	13	mg/kg	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	73	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	73	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	73	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	73	mg/m ³	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period)
 EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value

EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

IRL OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

M OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average)

[9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period)

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

[8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) |

BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) |

Other information: Skin = Possibility of a significant uptake through the skin.

[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction.

(S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Page 12 of 27
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.11.2022 / 0001
Replacing version dated / version: 29.11.2022 / 0001
Valid from: 29.11.2022
PDF print date: 29.11.2022
NanoMagic Twin Wax
Art.: 220999

Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Use acid resistant protective gloves (EN ISO 374).
Recommended
Protective gloves in butyl rubber (EN ISO 374).
Protective Neoprene® / polychloroprene gloves (EN ISO 374).
Protective nitrile gloves (EN ISO 374).
Minimum layer thickness in mm:
> 0,5
Permeation time (penetration time) in minutes:
> 120
Protective hand cream recommended.
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.
Filter A2 P2 (EN 14387), code colour brown, white
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Red
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	5
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Mixable

Page 13 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,97 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

NanoMagic Twin Wax

Art.: 220999

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

2-Butoxyethanol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

Page 14 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by oral route:	LD50	1746	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit		Irritant, Product removes fat.
Serious eye damage/irritation:				Rabbit		Intensively irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Mouse	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion
Symptoms:						gastrointestinal disturbances
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	500	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

Page 15 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		Analogous conclusion
--------------------------------	------	-------	-------	-----	--	----------------------

Acetic acid						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3310	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>1060	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	11,4	mg/l/4h	Rat		
Skin corrosion/irritation:						Corrosive
Serious eye damage/irritation:						Corrosive
Respiratory or skin sensitisation:						Possible
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						acidosis, respiratory distress, burning of the membranes of the nose and throat, diarrhoea, disturbed heart rhythm, cornea opacity, cramps, circulatory collapse, stomach cramps, shock, nausea and vomiting.

Tetramethyl acetyloctahydronaphthalenes (OTNE)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Human being	OECD 439 (In Vitro Skin Irritation - Reconstructed Human Epidermis Test Method)	Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative

Page 16 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	150	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	Target organ(s): liver, Target organ(s): gastrointestinal tract

Decamethylcyclopentasiloxane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	8,67	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative vapour
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells In Vivo)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:				Rat		Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>=1600	mg/kg bw/d	Rat	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	

Page 17 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	>=160	mg/l/6h/d	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Vapours
---	-------	-------	-----------	-----	--	---------

Dodecamethylcyclohexasiloxane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,15	mg/kg bw/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	

Octamethylcyclotetrasiloxane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2375	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	36	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rat	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative

Page 18 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Carcinogenicity:	NOAEL	150	mg/kg	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	inhalation
Reproductive toxicity:	NOAEL			Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Repr. 2
Reproductive toxicity (Developmental toxicity):	NOAEL	300	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	> 1	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	(21 d)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	150	mg/kg	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	

11.2. Information on other hazards

NanoMagic Twin Wax Art.: 220999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

NanoMagic Twin Wax Art.: 220999							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Page 19 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Other information:							DOC-elimination degree (complexing organic substance) \geq 80%/28d: n.a.
Other information:	AOX			%			According to the recipe, contains no AOX.

2-Butoxyethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	
12.3. Bioaccumulative potential:	Log Pow		0,83				Negative
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	1490	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to bacteria:	EC0	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Koc		67				Expert judgement
12.4. Mobility in soil:	H (Henry)		0,0000016	atm*m3/mol			

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,686	mg/l	Pimephales promelas	U.S. EPA ECOTOX Database	Analogous conclusion

Page 20 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

12.2. Persistence and degradability:		28d	>60	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>8,6	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,39	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	1,2	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to fish:	LC50	96h	>10	mg/l	Cyprinus caprio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
Toxicity to bacteria:	EC50	6d	100	mg/l	activated sludge		Analogous conclusion

Acetic acid

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	75	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	88	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	24h	47	mg/l	Daphnia magna		
12.2. Persistence and degradability:		30d	>99	%			
12.3. Bioaccumulative potential:	Log Pow		-0,17				
12.3. Bioaccumulative potential:	BCF		<1				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	15min	11	mg/l	Photobacterium phosphoreum		
Toxicity to bacteria:	EC5	16h	2850	mg/l	Pseudomonas putida		
Other information:	BOD5		0,88	g/g			

Tetramethyl acetyloctahydronaphthalenes (OTNE)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:			96	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF	21d	391		Lepomis macrochirus	OECD 305 (Bioconcentration - Flow-Through Fish Test)	

Page 21 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

12.1. Toxicity to fish:	LC50	96h	1,3	mg/l	Lepomis macrochirus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	30d	0,16	mg/l	Brachydanio rerio	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	1,38	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,028	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
Toxicity to bacteria:	NOEC/NOEL	42d	> 100	mg/l	activated sludge		Test guideline: OECD 301 F
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Log Koc		4,1				

Decamethylcyclopentasiloxane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>16	µg/l	Oncorhynchus mykiss	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	Water toxicology is above the water-solubility value.
12.1. Toxicity to fish:	NOEC/NOEL	>60d	>14	µg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	Water toxicology is above the water-solubility value.90 d
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>15	µg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to daphnia:	EC50	48h	>2,9	µg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	EC50	96h	>12	µg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	NOEC/NOEL	96h	>= 12	µg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.

Page 22 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

12.2. Persistence and degradability:		28d	0,14	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		7060			OECD 305 (Bioconcentration - Flow-Through Fish Test)	High
12.3. Bioaccumulative potential:	Log Pow		8,023				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							vPvB-substance, PBT-substance
Toxicity to annelids:	NOEC/NOEL		>=76	mg/kg	Eisenia foetida		
Toxicity to bacteria:	EC50	3h	>2000	mg/l	activated sludge	Regulation (EC) 440/2008 C.11 (BIODEGRADATION - ACTIVATED SLUDGE RESPIRATION INHIBITION)	
Water solubility:			<0,05	mg/l			@25°C

Dodecamethylcyclohexasiloxane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	>= 2	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	NOEC/NOEL	49d	>= 4,4	µg/l	Pimephales promelas		
12.1. Toxicity to fish:	LD50	49d	>4,4	µg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>4,6	µg/l	Daphnia magna		
12.3. Bioaccumulative potential:	Log Pow		8,87-9,45				
12.3. Bioaccumulative potential:	BCF	49d	1160			OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.1. Toxicity to algae:	EC50	72h	>2	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	4,47	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable CO2 evolution

Page 23 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.5. Results of PBT and vPvB assessment							vPvB-substance, PBT-substance

Octamethylcyclotetrasiloxane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							PBT-substance, vPvB-substance
12.3. Bioaccumulative potential:	Log Pow		6,49			OECD 123 (Partition Coefficient (1-Octanol / Water) - Slow-Stirring Method)	25,1 °C
12.1. Toxicity to fish:	LC50	96h	> 22	µg/l	Oncorhynchus mykiss		EPA OTS 797.1400
12.1. Toxicity to fish:	NOEC/NOEL	14d	0,0044	mg/l			
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>0,0015	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	> 15	µg/l	Daphnia magna		EPA OTS 797.1300
12.1. Toxicity to algae:	ErC10	96h	0,022	mg/l			
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l			
12.2. Persistence and degradability:		28d	3,7	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,1				A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	BCF	28d	12400		Pimephales promelas		EPA OTS 797.1520
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	ISO 8192	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 08 discarded organic chemicals consisting of or containing hazardous substances

Recommendation:

Page 24 of 27
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.11.2022 / 0001
Replacing version dated / version: 29.11.2022 / 0001
Valid from: 29.11.2022
PDF print date: 29.11.2022
NanoMagic Twin Wax
Art.: 220999

Sewage disposal shall be discouraged.
Pay attention to local and national official regulations.
E.g. suitable incineration plant.
E.g. dispose at suitable refuse site.

For contaminated packing material


Pay attention to local and national official regulations.
Empty container completely.
Dispose of packaging that cannot be cleaned in the same manner as the substance.
Uncontaminated packaging can be recycled.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1760

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
UN 1760 CORROSIVE LIQUID, N.O.S. (1-PROPANAMINIUM, 2-HYDROXY-N-(2-HYDROXYPROPYL)-N,N-DIMETHYL-, DIESTERS WITH VEGETABLE-OIL FATTY ACIDS, C18-UNSATD., ME SULFATES (SALTS), ACETIC ACID) 

14.3. Transport hazard class(es): 8

14.4. Packing group: II


Classification code: C9

LQ: 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: E

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
CORROSIVE LIQUID, N.O.S. (1-PROPANAMINIUM, 2-HYDROXY-N-(2-HYDROXYPROPYL)-N,N-DIMETHYL-, DIESTERS WITH VEGETABLE-OIL FATTY ACIDS, C18-UNSATD., ME SULFATES (SALTS), ACETIC ACID) 

14.3. Transport hazard class(es): 8

14.4. Packing group: II


EmS: F-A, S-B

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

IMDG Code segregation group 1 - Acids

Transport by air (IATA)

14.2. UN proper shipping name:
Corrosive liquid, n.o.s. (1-PROPANAMINIUM, 2-HYDROXY-N-(2-HYDROXYPROPYL)-N,N-DIMETHYL-, DIESTERS WITH VEGETABLE-OIL FATTY ACIDS, C18-UNSATD., ME SULFATES (SALTS), ACETIC ACID) 

14.3. Transport hazard class(es): 8

14.4. Packing group: II

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.
Danger code and packing code on request.
Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Page 25 of 27
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.11.2022 / 0001
 Replacing version dated / version: 29.11.2022 / 0001
 Valid from: 29.11.2022
 PDF print date: 29.11.2022
 NanoMagic Twin Wax
 Art.: 220999

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

2-Butoxyethanol

Decamethylcyclopentasiloxane

Octamethylcyclotetrasiloxane

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): ~ 32 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: n.a.
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Skin Corr. 1B, H314	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H361f Suspected of damaging fertility.

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - inhalation

Skin Corr. — Skin corrosion

Eye Dam. — Serious eye damage

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - oral

Skin Irrit. — Skin irritation

Eye Irrit. — Eye irritation

Aquatic Acute — Hazardous to the aquatic environment - acute

Flam. Liq. — Flammable liquid

Met. Corr. — Substance or mixture corrosive to metals

Page 26 of 27
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.11.2022 / 0001
Replacing version dated / version: 29.11.2022 / 0001
Valid from: 29.11.2022
PDF print date: 29.11.2022
NanoMagic Twin Wax
Art.: 220999

Skin Sens. — Skin sensitization
Repr. — Reproductive toxicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
bw body weight
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient

Page 27 of 27
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.11.2022 / 0001
Replacing version dated / version: 29.11.2022 / 0001
Valid from: 29.11.2022
PDF print date: 29.11.2022
NanoMagic Twin Wax
Art.: 220999

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.