

Page 1 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 16.12.2024 / 0004
Replacing version dated / version: 11.03.2024 / 0003
Valid from: 16.12.2024
PDF print date: 16.12.2024
Panel Preparation Spray
Art.: 441999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Panel Preparation Spray
Art.: 441999

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Cleaning product

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH
Einsteinstrasse 42
59423 Unna
Telefon: +49 (0) 2303 / 9 86 70 - 0
Fax: +49 (0) 2303 / 9 86 70 - 26
info@koch-chemie.com
www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H225-Highly flammable liquid and vapour. H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear eye protection / face protection.
 P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.
 P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.
 P501-Dispose of contents / container to an approved waste disposal facility.

Propan-2-ol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	200-661-7
CAS	67-63-0
content %	25-<50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

2-Butoxyethanol	
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	203-905-0
CAS	111-76-2
content %	5-<10

Page 3 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 16.12.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 16.12.2024

PDF print date: 16.12.2024

Panel Preparation Spray

Art.: 441999

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 3, H331 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Specific Concentration Limits and ATE	ATE (oral): 1200 mg/kg ATE (as inhalation, Aerosol): 0,5 mg/l/4h ATE (as inhalation, Vapours): 3 mg/l

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

eyes, reddened

watering eyes

headaches

dizziness

Coordination disorders

mental confusion

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Exinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Use explosion-proof equipment / explosion-protected tools if necessary.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

GB IRL M

Page 5 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 16.12.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 16.12.2024

PDF print date: 16.12.2024

Panel Preparation Spray

Art.: 441999

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Observe special storage conditions.
 Do not store with flammable or self-igniting materials.
 Protect from direct sunlight and warming.
 Store in a well ventilated place.
 Store cool.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Propan-2-ol	
WEL-TWA: 400 ppm (999 mg/m ³)	WEL-STEL: 500 ppm (1250 mg/m ³)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Alcohol 25/a i-Propanol (81 01 631) - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - NIOSH 1400 (ALCOHOLS I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - Draeger - Alcohol 100/a (CH 29 701) 	
BMGV: ---	Other information: ---	

Chemical Name	Propan-2-ol	
OELV-8h: 200 ppm	OELV-15min: 400 ppm	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Alcohol 25/a i-Propanol (81 01 631) - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - NIOSH 1400 (ALCOHOLS I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - Draeger - Alcohol 100/a (CH 29 701) 	
BLV: 40 mg/l (acetone, U, d) (ACGIH-BEI)	Other information: Sk	

Chemical Name	2-Butoxyethanol	
WEL-TWA: 25 ppm (123 mg/m ³) (WEL-TWA), 20 ppm (98 mg/m ³) (EU)	WEL-STEL: 50 ppm (246 mg/m ³) (WEL-STEL, EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-190 U(C) (548 873) - DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990 	
BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Sk (WEL)	

Chemical Name	2-Butoxyethanol	
OELV-8h: 20 ppm (98 mg/m ³) (OELV-8h, EU)	OELV-15min: 50 ppm (246 mg/m ³) (OELV-15min, EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-190 U(C) (548 873) - DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 	

GB IRL M

Page 6 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 16.12.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 16.12.2024

PDF print date: 16.12.2024

Panel Preparation Spray

Art.: 441999

- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990

BLV: 200 mg/g creatinine (Butoxyacetic acid (BAA) in urine, h) (ACGIH-BEI) Other information: Sk, IOELV

Chemical Name		2-Butoxyethanol	
OELV-8h: 20 ppm (98 mg/m ³) (OELV-8h, EU)	OELV-ST: 50 ppm (246 mg/m ³) (OELV-ST, EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-190 U(C) (548 873) - DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004) - NIOSH 1403 (ALCOHOLS IV) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990 		
BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Skin		

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg dw	
	Environment - sediment, marine		PNEC	552	mg/kg dw	
	Environment - soil		PNEC	28	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
	Environment - oral (animal feed)		PNEC	160	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	319	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	89	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	888	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	500	mg/m ³	

2-Butoxyethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	

GB IRL M

Page 7 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 16.12.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 16.12.2024

PDF print date: 16.12.2024

Panel Preparation Spray

Art.: 441999

	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

IRL - Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) =

Page 8 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 16.12.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 16.12.2024

PDF print date: 16.12.2024

Panel Preparation Spray

Art.: 441999

Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)); ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and Safety Executive (HSE), UK.

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Aspfx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

M - Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |

| OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE), (EU15) = Substantial contribution to the total body burden via dermal exposure possible. |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 16.12.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 16.12.2024

PDF print date: 16.12.2024

Panel Preparation Spray

Art.: 441999

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Protective gloves made of butyl (EN ISO 374).

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Protective PVC gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Liquid

Colour:

Colourless

Odour:

Characteristic

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

Flammability:

There is no information available on this parameter.

Lower explosion limit:

There is no information available on this parameter.

Upper explosion limit:

There is no information available on this parameter.

Flash point:

21 °C

Page 10 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 16.12.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 16.12.2024

PDF print date: 16.12.2024

Panel Preparation Spray

Art.: 441999

Auto-ignition temperature:
 Decomposition temperature:
 pH:
 Kinematic viscosity:
 Solubility:
 Partition coefficient n-octanol/water (log value):
 Vapour pressure:
 Density and/or relative density:
 Relative vapour density:
 Particle characteristics:

There is no information available on this parameter.
 There is no information available on this parameter.
 Mixture is non-polar/aprotic.
 There is no information available on this parameter.
 There is no information available on this parameter.
 Does not apply to mixtures.
 There is no information available on this parameter.
 0,92 g/ml
 There is no information available on this parameter.
 Does not apply to liquids.

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Panel Preparation Spray

Art.: 441999

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Dusts or mist
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.

Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Propan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	12800-13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	> 25	mg/l/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LC50	46600	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:		500	mg/kg/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Negative (oral, 7 weeks)
Reproductive toxicity:	NOAEL	853	mg/kg bw/d	Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative
Reproductive toxicity:	NOAEL	400	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336, May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	5000	ppm	Rat		Vapours (OECD 451)
Aspiration hazard:						No

Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes
-----------	--	--	--	--	--	---

2-Butoxyethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	ATE	3	mg/l			Vapours
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Aerosol
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	720	mg/kg bw/d			
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	
Aspiration hazard:						No

Page 13 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 16.12.2024 / 0004
 Replacing version dated / version: 11.03.2024 / 0003
 Valid from: 16.12.2024
 PDF print date: 16.12.2024
 Panel Preparation Spray
 Art.: 441999

Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness, nausea
-----------	--	--	--	--	--	---

11.2. Information on other hazards

Panel Preparation Spray Art.: 441999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Panel Preparation Spray Art.: 441999							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Other information:							DOC-elimination degree (complexing organic substance) \geq 80%/28d: n.a.
Other information:	AOX			%			According to the recipe, contains no AOX.

Propan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Slight
12.3. Bioaccumulative potential:	BCF		3,2				Low
12.4. Mobility in soil:	Koc		1,1				Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other organisms:	IC50	3d	2104	mg/l	Lactuca sativa		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD		1171	mg/g			

2-Butoxyethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	

12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,2				Slight
12.3. Bioaccumulative potential:	Log Pow		0,81			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Not to be expected
12.4. Mobility in soil:	H (Henry)		0,0000016	atm*m3/mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Page 16 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 16.12.2024 / 0004
 Replacing version dated / version: 11.03.2024 / 0003
 Valid from: 16.12.2024
 PDF print date: 16.12.2024
 Panel Preparation Spray
 Art.: 441999

E.g. dispose at suitable refuse site.
 E.g. suitable incineration plant.


For contaminated packing material

Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.
 Do not perforate, cut up or weld uncleaned container.
 Residues may present a risk of explosion.


SECTION 14: Transport information

General statements


Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1219	
14.2. UN proper shipping name:		
UN 1219 ISOPROPANOL, SOLUTION		
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D/E	
Classification code:	F1	
LQ:	1 L	
Transport category:	2	

Transport by sea (IMDG-code)

14.1. UN number or ID number:	1219	
14.2. UN proper shipping name:		
UN 1219 ISOPROPANOL, SOLUTION		
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-E, S-D	

Transport by air (IATA)

14.1. UN number or ID number:	1219	
14.2. UN proper shipping name:		
UN 1219 Isopropanol solution		
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
14.5. Environmental hazards:	Not applicable	

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Page 17 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 16.12.2024 / 0004
 Replacing version dated / version: 11.03.2024 / 0003
 Valid from: 16.12.2024
 PDF print date: 16.12.2024
 Panel Preparation Spray
 Art.: 441999

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 50 %

REGULATION (EC) No 648/2004

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H225 Highly flammable liquid and vapour.
 H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H336 May cause drowsiness or dizziness.

Flam. Liq. — Flammable liquid
 Eye Irrit. — Eye irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Acute Tox. — Acute toxicity - inhalation
 Acute Tox. — Acute toxicity - oral
 Skin Irrit. — Skin irritation

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

Page 19 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 16.12.2024 / 0004

Replacing version dated / version: 11.03.2024 / 0003

Valid from: 16.12.2024

PDF print date: 16.12.2024

Panel Preparation Spray

Art.: 441999

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight

mg/kg wwt mg/kg wet weight

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.