(B) (RI) (M)

Page 1 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by **Regulation (EU) 2020/878)**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

PerfectFinish Sealant Art.: 685999

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Cleaner Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26 info@koch-chemie.com www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body: (RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week) Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)					
Hazard class	Hazard category	Hazard statement			
Skin Sens.	1	H317-May cause an allergic skin reaction.			
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.			

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

GB (RL M

Page 2 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999



Warning

H317-May cause an allergic skin reaction. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves. P333+P313-If skin irritation or rash occurs: Get medical advice / attention. P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

2-Octyl-2H-isothiazol-3-one 2-methylisothiazol-3(2H)-one

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

01-2119457273-39-XXXX	
918-481-9	
(64742-48-9)	
1-<10	
EUH066	
Asp. Tox. 1, H304	
	 918-481-9 (64742-48-9) 1-<10 EUH066

Bronopol (INN)		
Registration number (REACH)		
Index	603-085-00-8	
EINECS, ELINCS, NLP, REACH-IT List-No.	200-143-0	
CAS	52-51-7	
content %	0,01-<0,1	
	·	

(B) (RL) (M)

Page 3 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H312
factors	Acute Tox. 4, H302
	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	STOT SE 3, H335
	Aquatic Acute 1, H400 (M=10)
Specific Concentration Limits and ATE	ATE (oral): 305 mg/kg
	ATE (dermal): 1600 mg/kg

2-Octyl-2H-isothiazol-3-one	
Registration number (REACH)	
Index	613-112-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	247-761-7
CAS	26530-20-1
content %	0,0015-<0,01
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH071
factors	Acute Tox. 2, H330
	Acute Tox. 3, H301
	Acute Tox. 3, H311
	Skin Corr. 1, H314
	Eye Dam. 1, H318
	Skin Sens. 1A, H317
	Aquatic Acute 1, H400 (M=100)
	Aquatic Chronic 1, H410 (M=100)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,0015 %
	ATE (oral): 125 mg/kg
	ATE (dermal): 311 mg/kg
	ATE (as inhalation, Mist): 0,27 mg/l/4h
	ATE (as inhalation, Vapours): 0,5 mg/l/4h

2-methylisothiazol-3(2H)-one	
Registration number (REACH)	
Index	613-326-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	220-239-6
CAS	2682-20-4
content %	0,0001-<0,0015
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH071
factors	Acute Tox. 2, H330
	Acute Tox. 3, H301
	Acute Tox. 3, H311
	Skin Corr. 1B, H314
	Eye Dam. 1, H318
	Skin Sens. 1A, H317
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,0015 %
	ATE (oral): 183 mg/kg
	ATE (dermal): 242 mg/kg
	ATE (as inhalation, Dusts or mist): 0,11 mg/l/4h
	ATE (as inhalation, Vapours): 0,5 mg/l/4h

Impurities, test data and additional information may have been taken into account in classifying and labelling the product. For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

(BR) M

Page 4 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. reddening of the skin drving of the skin.

Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Silicon dioxide Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures 6.1.1 For non-emergency personnel

GB (RL M

Page 5 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aro	matics
WEL-TWA: 800 mg/m3	WEL-STEL:	

· 68 RL M								
Page 6 of 20 Safety data sheet according Revision date / version: 13. Replacing version dated / v Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999	rersion: 13.03.2025 / 0001	2006, Annex II (last amei	nded by Regu	lation (EU)	2020/878)			
Monitoring procedures:	- Draeg	er - Hydrocarbons 0,1%/ er - Hydrocarbons 2/a (8 ur - KITA-187 S (551 174	1 03 581)					
BMGV:	- Compur - KITA-187 S (551 174) BMGV: Other information: (OEL acc. to RCP- method, paragraphs 84-87, EH40)							
Chemical Name	Hydrocarbons, C10-C1	3, n-alkanes, isoalkanes	. cvclics. <2%	aromatics				
OELV-8h: 100 ppm (573 solvent", [White spirit])		LV-15min:	, - , - , - , - , - , - , - , - , - , - , -					
Monitoring procedures:	- Draeg	er - Hydrocarbons 0,1%/ er - Hydrocarbons 2/a (8 ur - KITA-187 S (551 174	1 03 581)					
BLV:	- Comp		Other info	rmation: -				
		00/						
	n-alkanes, isoalkanes, cyclic		Decerinte	Value	11	Nata		
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note		
Consumer	Human - oral	Long term, systemic effects	DNEL	125	mg/kg			
Consumer	Human - dermal	Long term, systemic effects	DNEL	125	mg/kg			
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	208	mg/kg body weight/day			
Brononol (INN)								
Bronopol (INN) Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note		
	Environmental compartment		r	Value	Onit	NOLE		
	Environment - freshwater		PNEC	0,01	mg/l			
	Environment - marine		PNEC	0,0008	mg/l			
	Environment - water, sporadic (intermittent) release		PNEC	0,0025	mg/l			
	Environment - sewage treatment plant		PNEC	0,43	mg/l			
	Environment - sediment, freshwater		PNEC	0,041	mg/kg dw			
	Environment - sediment, marine		PNEC	0,00328	mg/kg dw			
	Environment - soil		PNEC	0,5	mg/kg dw			
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,6	mg/m3			
Consumer	Human - inhalation	Short term, systemic effects	DNEL	1,8	mg/m3			
Consumer	Human - inhalation	Short term, local effects	DNEL	0,6	mg/m3			
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,7	mg/kg bw/day			
Consumer	Human - dermal	Short term, systemic effects	DNEL	2,1	mg/kg bw/day			
Consumer	Human - dermal	Long term, local effects	DNEL	0,004	mg/cm2			

(BR)

Page 7 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

Consumer	Human - dermal	Short term, local effects	DNEL	0,004	mg/cm2	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,18	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,008	mg/cm2	
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,008	mg/cm2	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3,5	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	10,5	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	2,5	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2,5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	6	mg/kg bw/day	

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	0,00339	mg/l	
	Environment - marine		PNEC	0,00339	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,00339	mg/l	
	Environment - sewage treatment plant		PNEC	0,23	mg/l	
	Environment - soil		PNEC	0,0471	mg/kg dw	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,021	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,043	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,027	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,053	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,021	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,043	mg/m3	

Inited Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(BR)

Page 8 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)): ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and Safety Executive (HSE), UK.

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Skin = Can be absorbed through skin. Asphx = asphyxiant. Sens = The substance can cause sensitisation. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

• Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom). (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic

© ℝ M

Page 9 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE), (EU15) = Substantial contribution to the total body burden via dermal exposure possible.

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Protective nitrile gloves (EN ISO 374). Protective Neoprene® / polychloroprene gloves (EN ISO 374). Protective PVC gloves (EN ISO 374). Minimum layer thickness in mm: 0,5 Permeation time (penetration time) in minutes: 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

© RI M

Page 10 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: White Characteristic Odour: Melting point/freezing point: There is no information available on this parameter. Boiling point or initial boiling point and boiling range: There is no information available on this parameter. Flammability: No Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. Flash point: There is no information available on this parameter. Auto-ignition temperature: There is no information available on this parameter. Decomposition temperature: There is no information available on this parameter. 6,5 pH: Kinematic viscosity: There is no information available on this parameter. Solubility: There is no information available on this parameter. Partition coefficient n-octanol/water (log value): Does not apply to mixtures. There is no information available on this parameter. Vapour pressure: Density and/or relative density: 0,99 g/cm3 Relative vapour density: There is no information available on this parameter. Particle characteristics: Does not apply to liquids.

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** None known **10.5 Incompatible materials** None known **10.6 Hazardous decomposition products** No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

PerfectFinish Sealant						
Art.: 685999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.

(B) (A)
Page 11 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 13.03.2025 / 0001
Replacing version dated / version: 13.03.2025 / 0001
Valid from: 13.03.2025
PDF print date: 13.03.2025
PerfectFinish Sealant
Art.: 685999

Skin corrosion/irritation:	Repeated exposure may cause skin dryness or cracking.
Serious eye	n.d.a.
damage/irritation:	
Respiratory or skin	n.d.a.
sensitisation:	
Germ cell mutagenicity:	n.d.a.
Carcinogenicity:	n.d.a.
Reproductive toxicity:	n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):	n.d.a.
Specific target organ toxicity - repeated exposure (STOT- RE):	n.d.a.
Aspiration hazard:	n.d.a.
Symptoms:	n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/m3/4	Rat	OECD 403 (Acute	Vapours,
			h		Inhalation Toxicity)	Analogous
						conclusion
Acute toxicity, by inhalation:	LC50	>4,951	mg/m3/4	Rat	OECD 403 (Acute	Analogous
			h		Inhalation Toxicity)	conclusion,
						Maximum
						achievable
						concentration.
						Vapours
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.,
						Product
						removes fat.
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion,
					,	Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye					OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	

GBRIM

Page 12 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 421 (Reproduction/Develop mental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEC	>= 5220	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusioninhal ation
Specific target organ toxicity - repeated exposure (STOT- RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousnes s, headaches, dizziness, Dermatitis (skin inflammation), Reddening, drying of the skin., mucous membrane irritation, nausea and vomiting., diarrhoea, lower abdominal pain

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	305	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	data of a diluted
						aequous solution
Acute toxicity, by oral route:	ATE	305	mg/kg			
Acute toxicity, by dermal route:	ATE	1600	mg/kg			
Acute toxicity, by dermal route:	LD50	1600	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	(Draize-Test)	Risk of serious damage to eyes.
Specific target organ toxicity - single exposure (STOT-SE):						May cause respiratory irritation.

 Image: The second se

Symptoms:			eyes,
			reddened,
			drowsiness,
			coughing,
			mucous
			membrane
			irritation,
			nausea and
			vomiting.

2-Octyl-2H-isothiazol-3-one									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	ATE	125	mg/kg						
Acute toxicity, by dermal route:	ATE	311	mg/kg						
Acute toxicity, by inhalation:	ATE	0,27	mg/l/4h			Dust, Mist			
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Vapours			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B			
Serious eye damage/irritation:						Eye Dam. 1			
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1A			
Symptoms:						ataxia, diarrhoea			

2-methylisothiazol-3(2H)-one	9					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	183	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	183	mg/kg			
Acute toxicity, by dermal	ATE	242	mg/kg			
route:						
Acute toxicity, by dermal	LD50	242	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	0,11	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	0,11	mg/l/4h			Dusts or mist
Skin corrosion/irritation:						Corrosive
Serious eye						Irreversible
damage/irritation:						effects
Respiratory or skin						Sensitising
sensitisation:						(skin contact)

11.2. Information on other hazards

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting	•			U		Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

GBRIM

Page 14 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

SECTION 12: Ecological information

PerfectFinish Sealant							
Art.: 685999 Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:			Tuluo	•	gamon		n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
Other information:							environment. DOC-
Other information.							elimination
							degree(comple
							ing organic substance)>=
							80%/28d: n.a.
Other information:	AOX			%			According to
				/0			the recipe,
							contains no
							AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,10	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna	QSÁR	
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

GBRIM

Page 15 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

40.0 Develotories and		004	00	%		Decelilu
12.2. Persistence and		28d	80	%	OECD 301 F	Readily
degradability:					(Ready	biodegradable
					Biodegradability -	
					Manometric	
					Respirometry	
					Test)	
12.3. Bioaccumulative	Log Pow		5,5-7,2			
potential:						
12.4. Mobility in soil:	Log Koc		>3			Product is
,						slightly volatile.
12.5. Results of PBT						No PBT
and vPvB assessment						substance, No
						vPvB substance
12.7. Other adverse						Product floats
effects:						on the water
						surface.
Water solubility:			~10	mg/l		Slight

Bronopol (INN)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	41,2	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	11	mg/l	Lepomis macrochirus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	1,4	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	0,4 - 2,8	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	DOC		50	%		ISO 9888	Biodegradable
12.2. Persistence and degradability:		28d	100	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,18- 0,22				Not accepted due to the log Pow - value.
12.3. Bioaccumulative potential:	BCF		3,16				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	43	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

2-Octyl-2H-isothiazol-3-one										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	LC50	96h	0,047	mg/l	Oncorhynchus mykiss					
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,0085	mg/l	Pimephales promelas					

GB (RL M)

Page 16 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,003	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,32	mg/l	Daphnia magna	1660	
12.1. Toxicity to algae:	ErC10	48h	0,00022 4	mg/l	Navicula pelliculosa	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	0,00129	mg/l	Navicula pelliculosa	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			25	%			Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,92- 2,95				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Endocrine disrupting properties:							Negative
Toxicity to bacteria:	EC50		30,2	mg/l	activated sludge		
Toxicity to bacteria:	EC20	3h	7,3	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:

Not applicable

©B (RL) M

Page 17 of 20							
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)							
Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025							
						PDF print date: 13.03.2025 PerfectFinish Sealant	
						Art.: 685999	
7.11.1.000000							
14.2. UN proper shipping name:							
Not applicable							
14.3. Transport hazard class(es):	Not applicable						
14.4. Packing group:	Not applicable						
14.5. Environmental hazards:	Not applicable						
Tunnel restriction code:	Not applicable						
Classification code:	Not applicable						
LQ:	Not applicable						
Transport category:	Not applicable						
Transport by sea (IMDG-code)							
14.1. UN number or ID number:	Not applicable						
14.2. UN proper shipping name:							
Not applicable							
14.3. Transport hazard class(es):	Not applicable						
14.4. Packing group:	Not applicable						
14.5. Environmental hazards:	Not applicable						
Marine Pollutant:	Not applicable						
EmS:	Not applicable						
Transport by air (IATA)							
14.1. UN number or ID number:	Not applicable						
14.2. UN proper shipping name:							
Not applicable							
14.3. Transport hazard class(es):	Not applicable						
14.4. Packing group:	Not applicable						
14.5. Environmental hazards:	Not applicable						
14.6. Special precautions for user							
	the many and according to the faille stand						

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): **REGULATION (EC) No 648/2004**

less than 5 % aliphatic hydrocarbons polycarboxylates

perfumes 2-BROMO-2-NITROPROPANE-1,3-DIOL OCTYLISOTHIAZOLINONE METHYLISOTHIAZOLINONE BENZISOTHIAZOLINONE

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label. Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012. Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods. These are indicated in the approval of the active substance.

National requirements/regulations on safety and health protection must be applied when using work equipment.

2,6 %

GB (RL M

Page 18 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

n.a.

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H330 Fatal if inhaled. H317 May cause an allergic skin reaction. H314 Causes severe skin burns and eye damage. H301 Toxic if swallowed. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. EUH071 Corrosive to the respiratory tract. Skin Sens. — Skin sensitization Aquatic Chronic — Hazardous to the aquatic environment - chronic Asp. Tox. — Aspiration hazard Acute Tox. — Acute toxicity - dermal Acute Tox. - Acute toxicity - oral Skin Irrit. — Skin irritation Eye Dam. — Serious eye damage STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation Aquatic Acute - Hazardous to the aquatic environment - acute Acute Tox. — Acute toxicity - inhalation Skin Corr. — Skin corrosion Key literature references and sources for data: Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA). Safety data sheets for the constituent substances. ECHA Homepage - Information about chemicals. **GESTIS** Substance Database (Germany). German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended. National Lists of Occupational Exposure Limits for each country as amended.

© ℝ M

Page 19 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approximately approx. Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council CAS Chemical Abstracts Service CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community **EINECS** European Inventory of Existing Commercial Chemical Substances European List of Notified Chemical Substances ELINCS ΕN **European Norms** EPA United States Environmental Protection Agency (United States of America) $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax number Fax. gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil octanol-water partition coefficient Kow International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLIDInternational Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships mg/kg bw mg/kg body weight mg/kg bw/d, mg/kg bw/day mg/kg body weight/day mg/kg dw mg/kg dry weight

GBRIM Page 20 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 13.03.2025 / 0001 Replacing version dated / version: 13.03.2025 / 0001 Valid from: 13.03.2025 PDF print date: 13.03.2025 PerfectFinish Sealant Art.: 685999 mg/kg wwt mg/kg wet weight not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSHNational Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon **UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility. These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.