-GB (RL) (M)

Page 1 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

### Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### Plast Star

Art.: 108999

### 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Care product for plastic surfaces

### **Uses advised against:**

No information available at present.

### 1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna

Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26 info@koch-chemie.com

www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

### 1.4 Emergency telephone number

### Emergency information services / official advisory body:

(RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:

+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)

+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

#### Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Flam. Liq. 2 H225-Highly flammable liquid and vapour.

Asp. Tox. 1 H304-May be fatal if swallowed and enters airways.

STOT SE 3 H336-May cause drowsiness or dizziness.

Aquatic Chronic 2 H411-Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

®®™M

Page 2 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999



#### Danger

H225-Highly flammable liquid and vapour. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P312-Call a POISON CENTRE / doctor if you feel unwell. P331-Do NOT induce vomiting.

EUH066-Repeated exposure may cause skin dryness or cracking.

EUH205-Contains epoxy constituents. May produce an allergic reaction.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

### 2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

### n.a. 3.2 Mixtures

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	
content %	60-<80
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 2, H225
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

1167-67-1
<5
in Irrit. 2, H315
e Irrit. 2, H319
</th

- GB (RL) M

Page 3 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

Octamethylcyclotetrasiloxane	PBT-substance
	vPvB-substance
	SVHC-substance
Registration number (REACH)	01-2119529238-36-XXXX
Index	014-018-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	209-136-7
CAS	556-67-2
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Repr. 2, H361f
factors	Aquatic Chronic 1, H410 (M=10)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

#### **Eve contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Headaches

dizziness

Coordination disorders

mental confusion

reddening of the skin

drying of the skin.

Allergic reaction

nausea

vomiting

Danger of aspiration.

oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

### **SECTION 5: Firefighting measures**

- GB (RL M

Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

### 5.1 Extinguishing media

### Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Possible build up of explosive/highly flammable vapour/air mixture.

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Use no flammable substances.

Fill the absorbed material into lockable containers.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Use explosion-proof equipment / explosion-protected tools if necessary.

Avoid contact with eyes or skin.

®®M−

Page 5 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special storage conditions.

Under all circumstances prevent penetration into the soil.

Do not store with flammable or self-igniting materials.

Protect from direct sunlight and warming.

Store in a well ventilated place.

Store cool.

### 7.3 Specific end use(s)

No information available at present.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
WEL-TWA: 1200 mg/m3	WEL-STEL:	
Monitoring procedures:	<ul> <li>Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> </ul>	
	<ul> <li>Draeger - Hydrocarbons 2/a (81 03 581)</li> </ul>	
	- Compur - KITA-187 S (551 174)	
BMGV:	Other information:	(OEL acc. to RCP-
	method, paragraph	s 84-87, EH40)

Chemical Name Hy	drocarbons, C7	7-C9, n-alkanes, isoalkanes, cyclics	
OELV-8h: 100 ppm (573 mg/m3) ("	Stoddard	OELV-15min:	
solvent", [White spirit])			
Monitoring procedures:	- [	Oraeger - Hydrocarbons 0,1%/c (81 03 571)	
	- [	Oraeger - Hydrocarbons 2/a (81 03 581)	
	- (	Compur - KITA-187 S (551 174)	
BLV:		Other information:	

Hydrocarbons, C7-C9, n	n-alkanes, isoalkanes, cycli	cs				
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

- GB (RL) M

Page 6 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	1,5	μg/l	
	Environment - marine		PNEC	0,15	μg/l	
	Environment - sediment, freshwater		PNEC	3	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,3	mg/kg dry weight	
	Environment - soil		PNEC	0,54	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - oral (animal feed)		PNEC	41	mg/kg feed	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	13	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,7	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	3,7	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	73	mg/m3	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).
- © OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE).
- OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

- GB (RL) M

Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).  $\mid$ 

BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

© OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average)

[9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE).

OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period)

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

[8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) |

BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.

[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

### 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

Recommended

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Protective gloves made of fluorocarbon rubber (EN ISO 374).

Minimum layer thickness in mm:

- GB (RL M)

Page 8 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

0,7

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state: Liquid

Colour: White, Turbid Odour: Fruity

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit:

There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

Upper explosion limit:

There is no information available on this parameter.

There is no information available on this parameter.

Flash point: ~1 °C

Auto-ignition temperature:

There is no information available on this parameter.

Decomposition temperature:

There is no information available on this parameter.

pH: Mixture is non-polar/aprotic. Kinematic viscosity: <=20,5 mm2/s (40°C)
Kinematic viscosity: 7 mm2/s (40°C)

Solubility: Insoluble

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 0,78 g/ml

Relative vapour density:

There is no information available on this parameter.

Particle characteristics:

Does not apply to liquids.

#### 9.2 Other information

No information available at present.

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

-GB (RL M)-

Page 9 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Electrostatic charge

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with oxidizing agents.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Plast Star						
Art.: 108999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics							
Endpoint	Value	Unit	Organism	Test method	Notes		
LD50	>5000	mg/kg	Rat	OECD 401 (Acute			
				Oral Toxicity)			
LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute			
				Dermal Toxicity)			
LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Vapours		
				Inhalation Toxicity)			
	Endpoint LD50 LD50	Endpoint         Value           LD50         >5000           LD50         >2800	Endpoint         Value         Unit           LD50         >5000         mg/kg           LD50         >2800         mg/kg	EndpointValueUnitOrganismLD50>5000mg/kgRatLD50>2800mg/kgRabbit	Endpoint         Value         Unit         Organism         Test method           LD50         >5000         mg/kg         Rat         OECD 401 (Acute Oral Toxicity)           LD50         >2800         mg/kg         Rabbit         OECD 402 (Acute Dermal Toxicity)           LC50         >23,3         mg/l/4h         Rat         OECD 403 (Acute		

(B) (R) (M)

Page 10 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001 Valid from: 29.11.2022

PDF print date: 29.11.2022

Plast Star Art.: 108999

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:					imation/corresion/	Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:					OEĆD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousnes s,
						heart/circulatory disorders, headaches,
						cramps, drowsiness, mucous
						membrane irritation, dizziness, nausea and
						vomiting.

Octamethylcyclotetrasiloxane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>4800	mg/kg	Rat	OECD 401 (Acute	Male
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>2375	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	36	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	

- GB (RL M)

Page 11 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

Skin corrosion/irritation:	Rabbit	OECD 404 (Acute	Not irritant
		Dermal	
		Irritation/Corrosion)	
Serious eye	Rat	OECD 405 (Acute	Not irritant
damage/irritation:		Eye	
		Irritation/Corrosion)	
Respiratory or skin	Mouse	OECD 429 (Skin	No (skin
sensitisation:		Sensitisation - Local	contact)
		Lymph Node Assay)	
Respiratory or skin	Guinea pig	OECD 406 (Skin	No (skin
sensitisation:		Sensitisation)	contact)
Germ cell mutagenicity:			Negative
Reproductive toxicity:			Repr. 2
Symptoms:			mucous
			membrane
			irritation

### 11.2. Information on other hazards

Plast Star						
Art.: 108999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

### **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Plast Star Art.: 108999	Forder stort	T:	V-I	11	0	To at weath and	Notes
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as
degradability:							much as
							possible with
							an oil separator.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.

(B) (R) (M)

Page 12 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001 Valid from: 29.11.2022

PDF print date: 29.11.2022

Plast Star Art.: 108999

Other information:			According to
			the recipe,
			contains no
			AOX.
Other information:			DOC-
			elimination
			degree(complex
			ing organic
			substance)>=
			80%/28d: n.a.
Other information:	AOX	%	According to
			the recipe,
			contains no
			AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.7. Other adverse							Product floats
effects:							on the water
							surface.
12.3. Bioaccumulative							Not to be
potential:							expected(evapo
							ration)
12.4. Mobility in soil:							Product is
				-			slightly volatile.
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna		
12.1. Toxicity to fish:	NOELR	28d	0,574	mg/kg	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	3 - 10	mg/l	Oncorhynchus	OECD 203	
12.1. TOXICILY TO 11511.	LC30	9011	3 - 10	ilig/i	mykiss	(Fish, Acute	
					IIIykiss	Toxicity Test)	
12.1. Toxicity to	EL50	48h	4.6 - 10	mg/l	Daphnia magna	OECD 202	
daphnia:	2200	1011	1,0 10	1119/1	Daprilla magna	(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	10	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	98	%		OECD 301 F	Completely
degradability:						(Ready	biodegradable.
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.5. Results of PBT						7	No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value

Octamethylcyclotetrasiloxane								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.3. Bioaccumulative	BCF	28d	12400		Pimephales			
potential:					promelas			
12.1. Toxicity to fish:	NOEC/NOEL	14d	0,0068	mg/l				
12.1. Toxicity to fish:	LC50	96h	>500	mg/l	Brachydanio rerio			

- GB (RL M)

Page 13 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Salmo gairdneri		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,0079	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC10	96h	0,022	mg/l			
12.2. Persistence and degradability:			3,7	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	29d
12.3. Bioaccumulative potential:	Log Pow		6,98				
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge		

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 01 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

### **SECTION 14: Transport information**

### **General statements**

14.1. UN number or ID number: 1993

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1993 FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C7-C9)
14.3. Transport hazard class(es):
3
14.4. Packing group:
Il Classification code:
F1
LQ:
1 L

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code: D/

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C7-C9)

14.3. Transport hazard class(es):

14.4. Packing group:

II





-GB (RL M)-

Page 14 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

EmS: F-E, S-E Marine Pollutant: Yes

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Flammable liquid, n.o.s. (HYDROCARBONS, C7-C9)

14.3. Transport hazard class(es):14.4. Packing group:II

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Octamethylcyclotetrasiloxane

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

contract a decorating to everage	, manamig eter):		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for	referred to in Article 3(10) for
		the application of - Lower-tier	the application of - Upper-tier
		requirements	requirements
P5c		5000	50000
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 73,7 %

Observe incident regulations.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### **SECTION 16: Other information**

Revised sections:

n.a.

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.



®®™M

Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361f Suspected of damaging fertility.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Skin Irrit. — Skin irritation Eye Irrit. — Eye irritation

Repr. — Reproductive toxicity

### **Key literature references and sources for data:**

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Article number Art., Art. no.

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

### **KochChemie**<sup>®</sup>

### **ExcellenceForExperts.**

- GB (RL M)-

Page 16 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of

substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

**IUCLIDInternational Uniform Chemical Information Database** 

IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSHNational Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

-GB (RL M)-

Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.11.2022 / 0001

Replacing version dated / version: 29.11.2022 / 0001

Valid from: 29.11.2022 PDF print date: 29.11.2022

Plast Star Art.: 108999

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

### Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.