

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Power-Schaum

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaner

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Koch-Chemie GmbH

Einsteinstr. 42

D-59423 Unna

Telephone no. +49-2303-9 86 70-0

Fax no. +49-2303-9 86 70-26

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

For information in the event of an emergency during transport:

+44 1865 407333

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Dam. 1; H318

Skin Irrit. 2; H315

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS05

Signal word

Danger

Hazardous component(s) to be indicated on label:

Sulfonic acids, C14-17-sec-alkane, sodium salts

Trade name: Power-Schaum**Product no.:** 250999**Current version :** 1.1.0, issued: 19.10.2020**Replaced version:** 1.0.0, issued: 24.09.2020**Region:** GB**Hazard statement(s)**

H315 Causes skin irritation.
 H318 Causes serious eye damage.

Precautionary statement(s)

P280 Wear protective gloves/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.

2.3 Other hazards**PBT assessment**

According to the information provided in the supply chain, the mixture does not contain > 0.1% of a substance that is considered to be PBT.

vPvB assessment

According to the information provided in the supply chain, the mixture does not contain > 0.1% of a substance that is considered to be vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Sulfonic acids, C14-17-sec-alkane, sodium salts		
	97489-15-1 307-055-2 - 01-2119489924-20	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Irrit. 2; H315 Aquatic Chronic 3; H412	>= 10.00 - < 25.00 wt%
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts		
	68891-38-3 500-234-8 - 01-2119488639-16	Eye Dam. 1; H318 Skin Irrit. 2; H315 Aquatic Chronic 3; H412	>= 5.00 - < 10.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 10% Skin Irrit. 2; H315: C >= 10% Eye Dam. 1; H318: C >= 15% Acute Tox. 4; H302: C >= 60%	-	-
2	-	Eye Irrit. 2; H319: C >= 5% Eye Dam. 1; H318: C >= 10%	-	-

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. In case of persisting

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB

adverse effects, consult a physician.

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air.

After skin contact

Wash immediately with plenty of water for several minutes. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get immediate ophthalmic treatment.

After ingestion

Rinse out mouth and give plenty of water to drink. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet; Foam; Carbon dioxide; Dry chemical extinguisher

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Sulphur oxides (S_xO_y)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear full protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Use personal protective clothing.

For emergency responders

Personal protective equipment (PPE) - see section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Trade name: Power-Schaum**Product no.:** 250999**Current version :** 1.1.0, issued: 19.10.2020**Replaced version:** 1.0.0, issued: 24.09.2020**Region:** GB

Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and after work. Remove contaminated clothing and shoes and launder thoroughly before reusing. Have emergency shower available. Provide eye wash fountain in work area.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place. Keep from freezing.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Substances to be avoided, see section 10.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****DNEL, DMEL and PNEC values****DNEL values (worker)**

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Sulfonic acids, C14-17-sec-alkane, sodium salts			97489-15-1 307-055-2	
	dermal	Long term (chronic)	systemic	5	mg/kg/day
	dermal	Long term (chronic)	local	2.8	mg/cm ²
	dermal	Short term (acut)	local	2.8	mg/cm ²
	inhalative	Long term (chronic)	systemic	35	mg/m ³
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts			68891-38-3 500-234-8	
	dermal	Long term (chronic)	systemic	2750	mg/kg/day
	dermal	Long term (chronic)	local	132	µg/cm ²
	inhalative	Long term (chronic)	systemic	175	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Sulfonic acids, C14-17-sec-alkane, sodium salts			97489-15-1 307-055-2	
	oral	Long term (chronic)	systemic	7.1	mg/kg/day
	dermal	Long term (chronic)	systemic	3.57	mg/kg/day
	dermal	Long term (chronic)	local	2.8	mg/cm ²
	dermal	Short term (acut)	local	2.8	mg/cm ²
	inhalative	Long term (chronic)	systemic	12.4	mg/m ³
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts			68891-38-3 500-234-8	
	oral	Long term (chronic)	systemic	15	mg/kg/day
	dermal	Long term (chronic)	systemic	1650	mg/kg/day
	dermal	Long term (chronic)	local	79	µg/cm ²
	inhalative	Long term (chronic)	systemic	52	mg/m ³

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	Sulfonic acids, C14-17-sec-alkane, sodium salts		97489-15-1 307-055-2	
	water	fresh water	0.04	mg/L
	water	marine water	0.004	mg/L
	water	Aqua intermittent	0.06	mg/L
	water	fresh water sediment	9.4	mg/kg dry weight
	water	marine water sediment	0.94	mg/kg dry weight
	soil	-	9.4	mg/kg dry weight
	sewage treatment plant	-	600	mg/L
	secondary poisoning	-	53.3	mg/kg food
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts		68891-38-3 500-234-8	
	water	fresh water	0.24	mg/L
	water	marine water	0.024	mg/L
	water	Aqua intermittent	0.071	mg/L
	water	fresh water sediment	0.917	mg/kg dry weight
	water	marine water sediment	0.092	mg/kg dry weight
	soil	-	7.5	mg/kg dry weight
	sewage treatment plant	-	10	g/L

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protective equipment**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material butyl

Material thickness >= 0.7 mm

Breakthrough time > 480 min

Other

Chemical-resistant work clothes.

Environmental exposure controls

No data available.

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Form/Colour	
liquid	
yellow	
Odour	
of lemon	
Odour threshold	
No data available	
pH value	
Value	9.5
Boiling point / boiling range	
No data available	
Melting point / melting range	
No data available	
Decomposition point / decomposition range	
No data available	
Flash point	
No data available	
Auto-ignition temperature	
No data available	
Oxidising properties	
not oxidizing	
Explosive properties	
Product does not present an explosion hazard.	
Flammability (solid, gas)	
No data available	
Lower flammability or explosive limits	
No data available	
Upper flammability or explosive limits	
No data available	
Vapour pressure	
No data available	
Vapour density	
No data available	
Evaporation rate	
No data available	
Relative density	
No data available	
Density	
Value	1.03 g/cm ³
Reference temperature	20 °C
Solubility in water	
Comments	miscible

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB

Solubility(ies)			
No data available			
Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
log Pow		0.2	
Reference temperature		20	°C
Method		92/69/EEC, A.8	
Source		ECHA	
Viscosity			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

10.4 Conditions to avoid

Keep from freezing.

10.5 Incompatible materials

strong oxidizing agents; strong acids

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity (result of the ATE calculation for the mixture)			
No	Product Name	CAS no.	EC no.
1	Power-Schaum		
Comments		The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).	
Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
LD50		500	- 2000 mg/kg bodyweight
Species		rat	
Method		OECD 401	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are met.	
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB

LD50	4100	mg/kg bodyweight
Species	rat	
Method	OECD 401	
Source	ECHA	

Acute dermal toxicity

No	Substance name	CAS no.	EC no.
1	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No	Substance name	CAS no.	EC no.
1	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	irritant		

Serious eye damage/irritation

No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	strongly irritant		

Respiratory or skin sensitisation

No	Substance name	CAS no.	EC no.
1	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity

No	Substance name	CAS no.	EC no.
1	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity

No	Substance name	CAS no.	EC no.
1	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB

salts	
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Carcinogenicity	
No data available	
STOT - single exposure	
No data available	
STOT - repeated exposure	
No data available	
Aspiration hazard	
No data available	

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
LC50		8.4	mg/l
Duration of exposure		96	h
Species	Leuciscus idus melanotus		
Method	440/2008/EC C.1.		
Source	ECHA		
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
LC50		7.1	mg/l
Duration of exposure		96	h
Species	Danio rerio		
Method	OECD 203		
Source	ECHA		
Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
NOEC		1.4	mg/l
Species	Oncorhynchus mykiss		
Method	OECD 204		
Source	ECHA		
Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
EC50		7.26	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
EC50		7.4	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
Toxicity to Daphnia (chronic)			

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB

No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
NOEC		1.0	mg/l
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
EC50		>	100 mg/l
Duration of exposure		72	h
Species	Scenedesmus subspicatus		
Method	OECD 201		
Source	ECHA		
2	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
ErC50		27.7	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
NOEC		0.95	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Method	OECD 201		
Source	ECHA		

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
EC50		>	10000 mg/l
Duration of exposure		16	h
Species	Pseudomonas putida		
Method	DIN 38412 T.8		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	500-234-8
Type	DOC decrease		
Value		100	%
Duration		14	day(s)
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1	307-055-2
log Pow		0.2	

Trade name: Power-Schaum**Product no.:** 250999**Current version :** 1.1.0, issued: 19.10.2020**Replaced version:** 1.0.0, issued: 24.09.2020**Region:** GB

Reference temperature	20 °C
Method	92/69/EEC, A.8
Source	ECHA

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	According to the information provided in the supply chain, the mixture does not contain > 0.1% of a substance that is considered to be PBT.
vPvB assessment	According to the information provided in the supply chain, the mixture does not contain > 0.1% of a substance that is considered to be vPvB.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Trade name: Power-Schaum**Product no.:** 250999**Current version :** 1.1.0, issued: 19.10.2020**Replaced version:** 1.0.0, issued: 24.09.2020**Region:** GB

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3
--	------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.
Employment restrictions, according to the regulations for protection of expectant and nursing mothers and the youth health and safety regulations, serving to protect against hazardous materials, should be observed.
The surfactants contained in this product comply with the DetVO 648/2004/EC.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H302 Harmful if swallowed.

H412 Harmful to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 769424

Trade name: Power-Schaum

Product no.: 250999

Current version : 1.1.0, issued: 19.10.2020

Replaced version: 1.0.0, issued: 24.09.2020

Region: GB
