- GB (RL M)-

Page 1 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

PreFoam efficient

Art.: 461999

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Vehicle cleansing

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna

Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26

info@koch-chemie.com www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

(IRL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:

+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)

+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Eye Dam. 1 H318-Causes serious eye damage. Met. Corr. 1 H290-May be corrosive to metals.

Skin Corr. 1 H314-Causes severe skin burns and eye damage.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

GB (RL M)

Page 2 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999



Danger

H290-May be corrosive to metals. H314-Causes severe skin burns and eye damage.

P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P390-Absorb spillage to prevent material damage.

Sodium hydroxide

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n a

3.2 Mixtures

· — · · · · · · · · · · · · · · · · · ·	
Sodium hydroxide	
Registration number (REACH)	01-2119457892-27-XXXX
Index	011-002-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	215-185-5
CAS	1310-73-2
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Met. Corr. 1, H290
factors	Skin Corr. 1A, H314
	Eye Dam. 1, H318
Specific Concentration Limits and ATE	Skin Corr. 1A, H314: >=5 %
	Skin Corr. 1B, H314: >=2 %
	Skin Irrit. 2, H315: >=0,5 %
	Eve Irrit. 2. H319: >=0.5 %

Alcohols, C12-14, ethoxylated, sulfates, sodium salts	
Registration number (REACH)	01-2119488639-16-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	500-234-8
CAS	68891-38-3
content %	1-<5

- GB (RL) M

Page 3 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Classification according to Regulation (EC) 1272/2008 (CLP), M-	Skin Irrit. 2, H315
factors	Eye Dam. 1, H318
	Aquatic Chronic 3, H412
Specific Concentration Limits and ATE	Eye Dam. 1, H318: >=10 %
	Eye Irrit. 2, H319: >=5 %

Sodium p-cumenesulphonate	
Registration number (REACH)	01-2119489411-37-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	239-854-6
CAS	15763-76-5
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Eye Irrit. 2, H319
factors	

Bronopol (INN)	
Registration number (REACH)	
Index	603-085-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	200-143-0
CAS	52-51-7
content %	<0,1
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H302
factors	Acute Tox. 4, H312
	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	STOT SE 3, H335
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	ATE (dermal): 1100 mg/kg

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Cauterizations not treated lead to wounds difficult to heal.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

- GB (RL M

Page 4 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Corrosive burns on skin as well as mucous membrane possible.

Necrosis

Risk of serious damage to eyes.

Corneal damage. Danger of blindness.

Ingestion:

Pain in the mouth and throat

Gastrointestinal disturbances

Oesophageal perforation

Gastric perforation

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Do not take any measures that are associated with personal risk or have not been sufficiently trained.

Keep unprotected persons away.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

-GB (RL M)-

Page 5 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Fill the absorbed material into lockable containers.

Neutralising is possible (only from a specialist).

Diluting with water is possible. Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Handle and open container with care.

There should be an eyewash station and safety shower located near the area of use.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with acids.

Do not use alkali sensitive materials.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Sodium hydroxide	
WEL-TWA:	WEL-STEL: 2 mg/m3	
Monitoring procedures:	ISO 15202 (Workplace air - Determination of metals an particulate matter by Inductively Coupled Plasma Atomi - Spectrometry), Part 1-3 - 2012(Part 1), 2012(Part 2), 20 - NIOSH 7401 (Alkaline dusts) - 1994 OSHA ID-121 (Metal and metalloid particulates in work (Atomic absorption)) - 2002 - EU project BC/CEN/ENTF - (2004)	ic Emission 004 (Part 3) place atmospheres
BMGV:	Other information: -	
Chemical Name	Sodium hydroxide	

Chemical Name	Sodium hydroxide	
OELV-8h:	OELV-15min: 2 mg/m3	

(B) (RL) (M)

Page 6 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Monitoring procedures: ISO 15202 (Workplace air - Determination of metals and metalloids in airborne

particulate matter by Inductively Coupled Plasma Atomic Emission Spectrometry), Part 1-3 - 2012(Part 1), 2012(Part 2), 2004 (Part 3)

NIOSH 7401 (Alkaline dusts) - 1994

OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 45-5

(2004)

Other information: ---BLV: ---

Sodium hydroxide									
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note			
Consumer	Human - inhalation	Long term, local effects	DNEL	1	mg/m3				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m3				

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	0,24	mg/l	
	Environment - periodic release		PNEC	0,13	mg/l	
	Environment - marine		PNEC	0,024	mg/l	
	Environment - sediment, marine		PNEC	0,0917	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	10000	mg/l	
	Environment - soil		PNEC	0,946	mg/kg dry weight	
	Environment - sporadic (intermittent) release		PNEC	0,071	mg/l	
	Environment - sediment, freshwater		PNEC	0,917	mg/kg	
	Environment - sediment, marine		PNEC	0,092	mg/kg	
	Environment - soil		PNEC	7,5	mg/kg	
Consumer	Human - dermal	Long term, local effects	DNEL	0,079	mg/cm2	
Consumer	Human - oral	Long term, systemic effects	DNEL	15	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1650	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	52	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2750	mg/kg bw/day	
Workers / employees Human - inhalation		Long term, systemic effects	DNEL	175	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,132	mg/cm2	

Sodium p-cumenesulphonate

-GB (RL M)-

Page 7 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	0,23	mg/l	
	Environment - sporadic (intermittent) release		PNEC	2,3	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - marine		PNEC	0,023	mg/l	
	Environment - sediment, freshwater		PNEC	0,862	mg/kg dw	
	Environment - sediment, marine		PNEC	0,086	mg/kg dw	
	Environment - soil		PNEC	0,037	mg/kg dw	
Consumer	Human - dermal	Long term, local effects	DNEL	0,048	mg/cm2	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,8	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	3,8	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	6,6	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,8	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	7,6	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	26,9	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,096	mg/cm2	

Bronopol (INN) Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,01	mg/l	
	Environment - marine		PNEC	0,001	mg/kg	
	Environment - sewage treatment plant		PNEC	0,43	mg/l	
	Environment - sediment, freshwater		PNEC	0,041	mg/kg dw	
	Environment - sediment, marine		PNEC	0,00328	mg/kg dw	
	Environment - soil		PNEC	0,5	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,2	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,3	mg/m3	
Consumer	Human - dermal	Long term, systemic	DNEL	1,4	mg/kg	
		effects			bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,35	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,2	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2,3	mg/kg bw/day	

- GB (RL) M

Page 8 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).
- © OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0.002 mg Cd/g creatinine in urine (Directive 2004/37/CE).
- OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

BLV = Biological limit value |

- Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).
- OELV-8h = Occupational Exposure Limit Value 8 h (8-hour reference period as a time-weighted average)
- [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE).
- OELV-ST = Occupational Exposure Limit Value Short-term (15-minute reference period)
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- [8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) |
- BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.
- [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).
- (EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

- GB (RL) (M)

Page 9 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

If applicable

Face protection (EN 166).

Skin protection - Hand protection:

Use alkali resistant protective gloves (EN ISO 374).

Recommended

Protective gloves made of butyl (EN ISO 374).

Protective gloves made of chloroprene (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Protective PVC gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Alkali-resistant protection clothing (EN 13034)

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Characteristic

Melting point/freezing point:

There is no information available on this parameter.

KochChemie⁶ **ExcellenceForExperts.**

GB (RL) M

Page 10 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density:

Relative vapour density:

Particle characteristics:

9.2 Other information

No information available at present.

There is no information available on this parameter.

There is no information available on this parameter. There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

Soluble

Does not apply to mixtures.

There is no information available on this parameter.

1,10 g/ml

There is no information available on this parameter.

Does not apply to liquids.

SECTION 10: Stability and reactivity

10.1 Reactivity

Product corrodes metals.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Avoid contact with strong acids (exothermic reaction possible).

Avoid contact with certain metals e.g. aluminium (development of hydrogen gas possible).

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Avoid contact with strong acids.

Avoid contact with strong oxidizing agents.

Avoid contact with alkali sensitive materials.

Avoid contact with certain metals e.g. aluminium.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

PreFoam efficient									
Art.: 461999									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:						n.d.a.			
Acute toxicity, by dermal						n.d.a.			
route:									
Acute toxicity, by inhalation:						n.d.a.			
Skin corrosion/irritation:						n.d.a.			
Serious eye						n.d.a.			
damage/irritation:									
Respiratory or skin						n.d.a.			
sensitisation:									
Germ cell mutagenicity:						n.d.a.			
Carcinogenicity:						n.d.a.			
Reproductive toxicity:						n.d.a.			

(B) (R) (M)

Page 11 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001 Valid from: 07.12.2022

PDF print date: 10.03.2023

Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-		
RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal	LD50	>2500	mg/kg	Rabbit	Regulation (EC)	
route:					440/2008 B.3 (ACUTE	
					TOXICITY (DERMAL)	
Skin corrosion/irritation:				Rabbit	·	Skin Corr. 1A
Serious eye				Rabbit	OECD 405 (Acute	Eye Dam. 1
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Human being	(Patch-Test)	Not sensitizising
sensitisation:					0500 474 (0 4 1 1	NI d
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Symptoms:						breathing
						difficulties,
						coughing,
						abdominal
						pain, shock,
						cramps

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4100	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:		>=10	%	Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Serious eye damage/irritation:		>=5	%	Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:	NOAEL	>1000	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, References

-GB (RL M)-

Page 12 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001 Valid from: 07.12.2022

Valid from: 07.12.2022 PDF print date: 10.03.2023

Reproductive toxicity:	NOAEL	>300	mg/kg	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	Negative, References
Aspiration hazard:						No
Symptoms:						mucous membrane irritation
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	>225	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Target organ(s): liver, References

Sodium p-cumenesulphonat						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Irrit. 2
damage/irritation:					Eye	•
3					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Mouse	OECD 474	Negative
Ç ,					(Mammalian	· ·
					Èrythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
3 ,				typhimurium	Reverse Mutation	J
				31	Test)	
Carcinogenicity:				Rat	OECD 453	Negative
ca.cegee.y.					(Combined Chronic	3
					Toxicity/Carcinogenicit	
					y Studies)	
Reproductive toxicity:	NOAEL	>936	mg/kg	Rat	, ,	
Reproductive toxicity (Effects	NOAEL	300-1000	mg/kg	Rat	OECD 421	
on fertility):			bw/d		(Reproduction/Develop	
,,,					mental Toxicity	
					Screening Test)	
Aspiration hazard:						n.a.
Specific target organ toxicity -	NOAEL	763-3534	mg/kg		OECD 408 (Repeated	
repeated exposure (STOT-					Dose 90-Day Oral	
RE), oral:					Toxicity Study in	
112), 5141.					Rodents)	
Specific target organ toxicity -	NOAEL	763	mg/kg	Rat	1 (oderne)	Target
repeated exposure (STOT-	HOALE	700	mg/kg	Tuc		organ(s): heart,
RE), oral:						References
Specific target organ toxicity -	LOAEL	1300	mg/kg	Mouse	OECD 411	1.0101011000
repeated exposure (STOT-	20/122		bw/d	1.70000	(Subchronic Dermal	
RE), dermal:			DW/G		Toxicity - 90-day	
ne, domai.					Study)	
Specific target organ toxicity -	NOAEL	>440	mg/kg		OECD 411	
repeated exposure (STOT-	NOAEL	> 111 0	mg/kg		(Subchronic Dermal	
RE), dermal:					Toxicity - 90-day	
INL), UEIIIIai.					Study)	
					Siduy)	

-GB (RL M)-

Page 13 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	305	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	data of a diluted aequous solution
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Does not conform with EU classification.
Acute toxicity, by dermal route:	ATE	1100	mg/kg			
Acute toxicity, by inhalation:	LC50	>0,588	mg/l/4h	Rat		Aerosol, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	(Draize-Test)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizising
Germ cell mutagenicity:						Negative
Carcinogenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H335
Symptoms:						eyes,
						reddened,
						drowsiness,
						coughing,
						mucous
						membrane
						irritation,
						nausea and
						vomiting.

11.2. Information on other hazards

PreFoam efficient Art.: 461999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

- GB (RL M)-

Page 14 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							The
degradability:							surfactant(s)
3							contained in
							this mixture
							complies(compl
							y) with the
							biodegradability
							criteria as laid
							down in
							Regulation
							(EC)
							No.648/2004
							on detergents.
							Data to support
							this assertion
							are held at the
							disposal of the
							competent
							authorities of
							the Member
							States and will
							be made
							available to
							them, at their
							direct request
							or at the
							request of a
							detergent
							manufacturer.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-
Caror information.							elimination
							degree(complex
							ing organic
							substance)>=
							900//20d: Voc
Other information:	AOV			0/			80%/28d: Yes
Other information:	AOX			%			According to
							the recipe,
							contains no
	1	1				1	AOX.

Sodium hydroxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	EC50	48h	40,4	mg/l	Ceriodaphnia		
daphnia:					spec.		

· GB (RL M)-

Page 15 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001 Valid from: 07.12.2022

Valid from: 07.12.2022 PDF print date: 10.03.2023

12.1. Toxicity to fish:	LC50	96h	45,4	mg/l	Oncorhynchus	
					mykiss	
12.1. Toxicity to fish:	LC50	96h	125	mg/l	Gambusia affinis	
12.2. Persistence and						Not relevant for
degradability:						inorganic
,						substances.
12.3. Bioaccumulative	Log Kow		-3,88			Negative
potential:						
12.5. Results of PBT						Not relevant for
and vPvB assessment						inorganic
						substances.
Toxicity to bacteria:	EC50	15min	22	mg/l	Photobacterium	
-					phosphoreum	

Alcohols, C12-14, etho Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	7,1	mg/l	Brachydanio rerio	OECD 203	NOIES
12.1. TOXICILY TO HISH.	LCSU	9011	7,1	IIIg/I	Brachydanio reno		
						(Fish, Acute	
10.1 =	11050/11051	00.1				Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,1	mg/l	Oncorhynchus	OECD 204	
					mykiss	(Fish, Prolonged	
						Toxicity Test -	
						14-Day Study)	
12.1. Toxicity to	NOEC/NOEL	21d	0,27	mg/l	Daphnia magna	OECD 211	
daphnia:						(Daphnia magna	
•						Reproduction	
						Test)	
12.1. Toxicity to	EC50	48h	7,2	mg/l	Daphnia magna	OECD 202	
daphnia:		1011	,,_	1119/1	- Saprilla magna	(Daphnia sp.	
aupiniu.						Acute	
						Immobilisation	
40.4 Tability ()	NOTO A LOT	001	0.05			Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	0,95	mg/l		OECD 201	
						(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	27,7	mg/l	Desmodesmus	OECD 201	
					subspicatus	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	95	%		OECD 301 E	Readily
degradability:						(Ready	biodegradable
g,						Biodegradability -	
						Modified OECD	
						Screening Test)	
12.2. Persistence and		28d	>70	%		OECD 301 A	Readily
		20u	>10	/0			biodegradable
degradability:						(Ready	biodegradable
						Biodegradability -	
						DOC Die-Away	
						Test)	
12.2. Persistence and	DOC	28d	100	%	activated sludge	Regulation (EC)	Readily
degradability:						440/2008 C.4-C	biodegradable
*						(DETERMINATI	_
						ON OF 'READY'	
						BIODEGRADABI	
						LITY - CO2	
						EVOLUTION	
						TEST)	
12.3. Bioaccumulative	BCF		-1,38	+		. 201)	Low
potential:			- 1,50				LUVV
POLETILIAI.	Koc		191	+			aalaulatad ::al
12.4. Mobility in soil:	NOC		191				calculated val
12.5. Results of PBT							No PBT
and vPvB assessment							substance

(B) (R) (M)

Page 16 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001 Valid from: 07.12.2022

PDF print date: 10.03.2023

Toxicity to bacteria:	EC50	16h	>10	g/l	Pseudomonas	DIN 38412 T.8	
					putida		

Sodium p-cumenesulp			1				
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Cyprinus caprio	OECD 203	
						(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	>100	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus	OECD 201	
					subspicatus	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	31	mg/l	Pseudokirchnerie		EPA OTS
					lla subcapitata		797.1050
12.2. Persistence and		28d	>60	%	activated sludge	OECD 301 B	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Co2 Evolution	
						Test)	
12.3. Bioaccumulative	Log Pow		-1,1			OECD 107	Bioaccumulation
potential:						(Partition	n is unlikely
						Coefficient (n-	(LogPow < 1).
						octanol/water) -	23 °C
						Shake Flask	
						Method)	
12.4. Mobility in soil:							Not to be
							expected
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substand
Toxicity to bacteria:	EC10	3h	>1000	mg/l	activated sludge	OECD 209	
						(Activated	
						Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Àmmonium	
						Oxidation))	

Bronopol (INN)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	EC50	72h	0,068	mg/l	Anabaena flos-	OECD 201	
					aquae	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,0025	mg/l	Anabaena flos-	OECD 201	
					aquae	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	3	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to fish:	LC50	28d	2,61	mg/l	Oncorhynchus	OECD 210	
					mykiss	(Fish, Early-Life	
						Stage Toxicity	
						Test)	

- GB (RL) M

Page 17 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,06	mg/l	Daphnia magna	OECD 211 (Daphnia magna	
·						Reproduction	
						Test)	
12.1. Toxicity to	EC50	48h	1,4	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
10 0 D : 1			70	0/	e () 1 1 1	Test)	D !!!
12.2. Persistence and			>70	%	activated sludge	OECD 301 B	Readily
degradability:						(Ready	biodegradable
						Biodegradability - Co2 Evolution	
						Test)	
12.2. Persistence and			63,5	%		OECD 314	Biodegradable
degradability:			03,5	/6		(Simulation	Diouegrauable
acgradability.						Tests to Assess	
						the	
						Biodegradability	
						of Chemicals	
						Discharged in	
						Wastewater)	
12.3. Bioaccumulative	Log Kow		0,22-			OECD 107	
potential:			0,38			(Partition	
						Coefficient (n-	
						octanol/water) -	
						Shake Flask	
						Method)	
12.3. Bioaccumulative potential:	BCF		3,16				
Other organisms:	LC50	14d	>500	mg/l	Eisenia foetida	OECD 207	
-						(Earthworm,	
						Acute Toxicity	
						Tests)	
Other information:	COD		600	mg/g			
Other information:	Koc		5				
Toxicity to bacteria:	EC50	3h	43	mg/l	activated sludge	OECD 209	
						(Activated	
						Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

- GB (RL M)-

Page 18 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023 PreFoam efficient

Art.: 461999

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: 1760

14.2. UN proper shipping name:

UN 1760 CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE, TETRASODIUM-N,N-BIS(CARBOXYLATOMETHYL)-

L-GLUTAMATE)

14.3. Transport hazard class(es):

8 14.4. Packing group:

14.5. Environmental hazards: Not applicable

Tunnel restriction code: E
Classification code: C9
LQ: 1 L
Transport category: 2

Transport by sea (IMDG-code)

14.1. UN number or ID number: 1760

14.2. UN proper shipping name:

UN 1760 CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE, TETRASODIUM-N,N-BIS(CARBOXYLATOMETHYL)-

L-GLUTAMATE)
14.3. Transport hazard class(es):

14.4. Packing group:II14.5. Environmental hazards:Not applicableMarine Pollutant:Not applicable

EmS:

Not applica

Segregation: -

Transport by air (IATA)

14.1. UN number or ID number: 1760

14.2. UN proper shipping name:

UN 1760 Corrosive liquid, n.o.s. (SODIUM HYDROXIDE, TETRASODIUM-N,N-BIS(CARBOXYLATOMETHYL)-L-

GLUTAMATE)

14.3. Transport hazard class(es):

8
14.4. Packing group:

II

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:







KochChemie[®] **ExcellenceForExperts.**

GB (RL) M

Page 19 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

< 0,3 %

REGULATION (EC) No 648/2004

less than 5 % anionic surfactants

perfumes

HEXYL CINNAMAL LINALOOL

BENZYL SALICYLATE

2-BROMO-2-NITROPROPANE-1,3-DIOL

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

n.a.

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Dam. 1, H318	Classification based on the pH value.
Met. Corr. 1, H290	Classification based on test data.
Skin Corr. 1, H314	Classification based on the pH value.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Eye Dam. — Serious eye damage

Met. Corr. — Substance or mixture corrosive to metals Skin Corr. — Skin corrosion

Skin Irrit. — Skin irritation

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Eye Irrit. — Eye irritation

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - dermal

- GB (RL M)

Page 20 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

GB (RL) (M

Page 21 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2022 / 0001

Replacing version dated / version: 07.12.2022 / 0001

Valid from: 07.12.2022 PDF print date: 10.03.2023

PreFoam efficient Art.: 461999

IARC International Agency for Research on Cancer

IATA International Air Transport Association International Bulk Chemical (Code) IBC (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive

IUCLIDInternational Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Logarithm of adsorption coefficient of organic carbon in the soil Log Koc

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ **Limited Quantities**

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available not checked n.c. n.d.a. no data available

NIOSHNational Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

organic

OSHA Occupational Safety and Health Administration (USA)

persistent, bioaccumulative and toxic PBT

PΕ Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Telephone Tel.

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.