^{GB} (RL M

Page 1 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Quick Dry & Shine Art.: 473999

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
Drying agent
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26 info@koch-chemie.com www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies: +1 872 5888271 (KCC)

SECTION 2: Hazards identification

	of the substance or mixtu ording to Regulation (EC)	
Hazard class	Hazard category	Hazard statement
Skin Corr.	1B	H314-Causes severe skin burns and eye damage.
Eye Dam.	1	H318-Causes serious eye damage.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

GB (RL M

Page 2 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999



Danger

H314-Causes severe skin burns and eye damage.

P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

Index

2-Butoxyethanol Substance for which an EU exposure limit value applies. 01-2119475108-36-XXXX **Registration number (REACH)** Index 603-014-00-0 EINECS, ELINCS, NLP, REACH-IT List-No. 203-905-0 CAS 111-76-2 content % 5-<10 Classification according to Regulation (EC) 1272/2008 (CLP), M-Acute Tox. 3, H331 Acute Tox. 4, H302 factors Skin Irrit. 2, H315 Eye Irrit. 2, H319 Specific Concentration Limits and ATE ATE (oral): 1200 mg/kg ATE (as inhalation, Aerosol): 0,5 mg/l/4h ATE (as inhalation, Vapours): 3 mg/l Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated **Registration number (REACH)**

GBIRIM

Page 3 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	102782-92-3
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Skin Corr. 1B, H314
factors	Eye Dam. 1, H318
	Aquatic Chronic 3, H412

Phenolpolyethoxylate	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	500-013-6
CAS	9004-78-8
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H302
factors	
Specific Concentration Limits and ATE	ATE (oral): 500 mg/kg

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-,	
diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates	
(salts)	
Registration number (REACH)	01-2119983493-26-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	939-685-4
CAS	
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Skin Irrit. 2, H315
factors	Eye Dam. 1, H318
	Aquatic Chronic 3, H412

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Cauterizations not treated lead to wounds difficult to heal.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

GB (RL M

Page 4 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Corrosive burns on skin as well as mucous membrane possible. Risk of serious damage to eyes. Conjunctivitis Corneal damage. Danger of blindness. pain in the mouth and throat

stomach pain Oesophageal perforation Gastric perforation

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

Flush residue using copious water.

©® ℝ M

Page 5 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Handle and open container with care.

There should be an eyewash station and safety shower located near the area of use.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	2-Butoxyethand	
WEL-TWA: 25 ppm (123 mg/m3	B) (WEL-TWA),	WEL-STEL: 50 ppm (246 mg/m3) (WEL-STEL,
20 ppm (98 mg/m3) (EU)		EU)
Monitoring procedures:	-	Compur - KITA-190 U(C) (548 873)
		DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) -
	-	2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)
	-	NIOSH 1403 (ALCOHOLS IV) - 2003
	-	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
	-	OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990
BMGV: 240 mmol butoxyacetic	acid/mol creatini	nine in urine, post shift (BMGV) Other information: Sk (WEL)
Chemical Name	2-Butoxyethan	nol
OELV-8h: 20 ppm (98 mg/m3) (OELV-8h, EU)	OELV-15min: 50 ppm (246 mg/m3) (OELV
		15min, EU)
Monitoring procedures:	-	Compur - KITA-190 U(C) (548 873)
		DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) -
	-	2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)
	-	NIOSH 1403 (ALCOHOLS IV) - 2003
	-	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
	-	OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990

GB (RL M

Page 6 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

BLV: 200 mg/g creatinine (Butc	oxyacetic acid (BAA) in urine, h) (ACGIH-BEI) Other information: Sk, IOELV	
Chemical Name	2-Butoxyethanol	
OELV-8h: 20 ppm (98 mg/m3)	(OELV-8h, EU) OELV-ST: 50 ppm (246 mg/m3) (OELV-ST, EU)	
Monitoring procedures:	- Compur - KITA-190 U(C) (548 873)	
	DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3	3) - (
	- 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)	
	- NIOSH 1403 (ALCOHOLS IV) - 2003	
	- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996	
	- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990	
BMGV: 240 mmol butoxyacetic	acid/mol creatinine in urine, post shift (BMGV) Other information: Skin	

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3	

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates (salts)

©® ℝ M

Page 7 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater Environment - sediment,		PNEC PNEC	0,017 1,7	mg/l mg/kg dw	
	freshwater Environment - marine Environment - sediment,		PNEC PNEC	0,002 0,17	mg/l mg/kg dw	
	marine Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Environment - soil Human - inhalation	Long term, systemic effects	DNEC DNEL	0,331 2,17	mg/kg dw mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	56,25	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,25	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,72	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	112,5	mg/kg bw/d	

Inited Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).

Ireland/Éire | OELV-8h = Occupational Exposure Limit Value - 8-hour reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | OELV-15min = Occupational Exposure Limit Value - 15-minute reference period (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological Monitoring Guidance Value (Biological Monitoring Guidelines 2011, HSA (Health and Safety Authority)): ACGIH-BEI = BMGV have been sourced from Biological Exposure Indices (BEI) as issued by the American Conference of Governmental Industrial Hygienists (ACGIH). SCOEL = BMGV have been sourced from the Scientific Committee on Occupational Exposure Limit Values (SCOEL) which was set up by a Commission Decision (95/320/EC) with the mandate to advise the European Commission on occupational exposure limits for chemicals in the workplace. HSE = BMGV have been sourced from the Health and

© ℝ M

Page 8 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

Safety Executive (HSE), UK.

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (Chemical Agents and Carcinogens CoP (Code of Practice) 2021, HSA (Health and Safety Authority)): Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).

• Malta | OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average) [S.L.424.24, last amended by L.N. 356 of 2021]: [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). | | OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period) [S.L.424.24, last amended by L.N. 356 of 2021]: [8] = Short-term exposure limit value in relation to a reference period of 1 minute, [9] = Inhalable fraction, [10] = Respirable fraction.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020), United Kingdom). (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information [S.L.424.24, last amended by L.N. 356 of 2021]: Skin = Possibility of a significant uptake through the skin. [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. [12] = The mist is defined as the thoracic fraction. [13] = Established in accordance with the Annex to Directive 91/322/EEC. [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended

(B) (M)
Page 9 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 08.01.2024 / 0001
Replacing version dated / version: 08.01.2024 / 0001
Valid from: 08.01.2024
PDF print date: 08.01.2024
Quick Dry & Shine
Art.: 473999
Protective gloves made of butyl (EN ISO 374).

Protective nitrile gloves (EN ISO 374). Protective PVC gloves (EN ISO 374). Minimum layer thickness in mm: > 0,5 Permeation time (penetration time) in minutes: > 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	4,5
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Mixable
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	There is no information available on this parameter.
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
9.2 Other information	
No information available at present.	

SECTION 10: Stability and reactivity

GB (RL M

Page 10 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid See also section 7.

None known

10.5 Incompatible materials

See also section 7. Avoid contact with strong alkalis. Avoid contact with strong oxidizing agents. Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Art.: 473999	·				·	
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated
						value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated
						value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Endpoint	Value	Unit	Organism	Test method	Notes
ATE	1200	mg/kg			
LD50	2275	mg/kg	Rabbit	OECD 402 (Acute	
				Dermal Toxicity)	
ATE	3	mg/l			Vapours
ATE	0,5	mg/l/4h			Aerosol
	ATE LD50 ATE	ATE 1200 LD50 2275 ATE 3	ATE 1200 mg/kg LD50 2275 mg/kg ATE 3 mg/l	ATE1200mg/kgLD502275mg/kgRabbitATE3mg/l	ATE 1200 mg/kg LD50 2275 mg/kg Rabbit OECD 402 (Acute Dermal Toxicity) ATE 3 mg/l

GBRIM

Page 11 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4	Skin Irrit. 2, Product
					(DERMAL IRRITATION/CORRO SION)	removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	720	mg/kg bw/d			
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT- RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	
Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousne s, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT- RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

GBRIM

Page 12 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		Analogous conclusion			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B			
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1			

Phenolpolyethoxylate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	500-2000	mg/kg	Rat	OECD 423 (Acute	
					Oral Toxicity - Acute	
					Toxic Class Method)	
Acute toxicity, by oral route:	ATE	500	mg/kg			
Acute toxicity, by dermal	LD50	2140	mg/kg	Rabbit		
route:						
Aspiration hazard:						No
Symptoms:						gastrointestinal
						disturbances

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Mouse	OECD 423 (Acute	
					Oral Toxicity - Acute	
					Toxic Class Method)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Skin Irrit. 2
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Dam. 1
damage/irritation:					Eye	,
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig		Not sensitizising
sensitisation:						J
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
5 ,					Reverse Mutation	5
					Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
jjj-					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative,
jjj-					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 414 (Prenatal	Analogous
	110/122	1000	bw/d		Developmental	conclusion
			<i>bin</i> a		Toxicity Study)	Contraction
Symptoms:						gastrointestinal
•)p.ee.						disturbances
Specific target organ toxicity -	NOAEL	500	mg/kg	Rat	OECD 407 (Repeated	
repeated exposure (STOT-					Dose 28-Day Oral	
RE), oral:					Toxicity Study in	
					Rodents)	

11.2. Information on other hazards

GBRIM

Page 13 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

Quick Dry & Shine						
Art.: 473999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more informati	on on environm	ental effect	s, see Sec	tion 2.1 (cla	ssification).		
Quick Dry & Shine							
Art.: 473999							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-
							elimination
							degree(complex
							ing organic
							substance)>=
							80%/28d: n.a.
Other information:	AOX			%			According to
							the recipe,
							contains no
							AOX.

2-Butoxyethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus	OECD 203	
				-	mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204	
-						(Fish, Prolonged	
						Toxicity Test -	
						14-Day Study)	

GBRIM

Page 14 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,2				Slight
12.3. Bioaccumulative potential:	Log Pow		0,81			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	Not to be expected
12.4. Mobility in soil:	H (Henry)		0,00000 16	atm*m3/ mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and							Not readily
degradability:							biodegradable
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Other information:							Does not
							contain any
							organically
							bound
							halogens which
							can contribute
							to the AOX
							value in waste
							water.

Phenolpolyethoxylate

GBRIM

Page 15 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l		OECD 203	
				_		(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	>128	mg/l	Daphnia pulex	OECD 202	
daphnia:				_		(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.2. Persistence and		60d	40-50	%		OECD 311	
degradability:						(Anaerobic	
						Biodeg. of	
						Organic Comp.	
						in Digested	
						Sludge - by	
						Measurement of	
						Gas Production)	
12.2. Persistence and						OECD 301 B	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Co2 Evolution	
						Test)	
12.2. Persistence and		28d	79	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,686	mg/l	Pimephales	U.S. EPA	Analogous
					promelas	ECOTOX	conclusion
						Database	
12.1. Toxicity to fish:	LC50	96h	>10	mg/l	Cyprinus caprio	OECD 203	Analogous
						(Fish, Acute	conclusion
						Toxicity Test)	
12.1. Toxicity to	NOEC/NOEL	21d	1	mg/l	Daphnia magna	U.S. EPA	Analogous
daphnia:						ECOTOX	conclusion
						Database	
12.1. Toxicity to	EC50	48h	>8,6	mg/l	Daphnia magna	OECD 202	Analogous
daphnia:						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,39	mg/l	Pseudokirchnerie	OECD 201	Analogous
					lla subcapitata	(Alga, Growth	conclusion
						Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	1,2	mg/l	Pseudokirchnerie	OECD 201	Analogous
					lla subcapitata	(Alga, Growth	conclusion
						Inhibition Test)	

GB (RL M)

Page 16 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

12.2. Persistence and degradability:		28d	>60	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Toxicity to bacteria:	EC50	6d	100	mg/l	activated sludge		Analogous conclusion

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 08 discarded organic chemicals consisting of or containing hazardous substances

20 01 99 other fractions not otherwise specified

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	3265	
14.2. UN proper shipping name:		
UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (AM	/INO FUNCTIONAL SILOXANE, ACETIC ACID)	
14.3. Transport hazard class(es):	8	$\mathbf{\nabla}$
14.4. Packing group:	II	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	E	
Classification code:	C3	
LQ:	1 L	
Transport category:	2	
Transport by sea (IMDG-code)		
14.1. UN number or ID number:	3265	
14.2. UN proper shipping name:		
UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (AM	/INO FUNCTIONAL SILOXANE, ACETIC ACID)	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	II	
14.5. Environmental hazards:	Not applicable	
IMDG Code segregation group 1 - Acids		
Marine Pollutant:	Not applicable	
EmS:	F-A, S-B	
Transport by air (IATA)		
14.1. UN number or ID number:	3265	
14.2. UN proper shipping name:		
- 1 - 1 - 1 - 1		

GB (RL M)

Page 17 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

UN 3265 Corrosive liquid, acidic, organic, n.o.s. (AMINO FUNCTIONAL SILOXANE, ACETIC ACID) 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

5,6 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

n.a.

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Corr. 1B, H314	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled. H412 Harmful to aquatic life with long lasting effects.

Skin Corr. — Skin corrosion Eye Dam. — Serious eye damage

© RI M

Page 18 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999

Acute Tox. — Acute toxicity - inhalation Acute Tox. — Acute toxicity - oral Skin Irrit. — Skin irritation Eye Irrit. — Eye irritation Aquatic Chronic — Hazardous to the aquatic environment - chronic

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council body weight hw CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera ΕU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals

GBIRI Page 19 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.01.2024 / 0001 Replacing version dated / version: 08.01.2024 / 0001 Valid from: 08.01.2024 PDF print date: 08.01.2024 Quick Dry & Shine Art.: 473999 GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code incl. including, inclusive IUCLIDInternational Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSHNational Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PΕ Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the RID International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon **UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.