

Page 1 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 20.11.2023 / 0003  
Replacing version dated / version: 15.11.2023 / 0002  
Valid from: 20.11.2023  
PDF print date: 20.11.2023  
Reactivation Shampoo  
Art.: 806999

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Reactivation Shampoo**  
**Art.: 806999**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Vehicle cleansing

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH  
Einsteinstrasse 42  
59423 Unna  
Telefon: +49 (0) 2303 / 9 86 70 - 0  
Fax: +49 (0) 2303 / 9 86 70 - 26  
info@koch-chemie.com  
www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:  
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)  
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

**Telephone number of the company in case of emergencies:**

+1 872 5888271 (KCC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Eye Dam.	1	H318-Causes serious eye damage.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Met. Corr.	1	H290-May be corrosive to metals.
Skin Corr.	1	H314-Causes severe skin burns and eye damage.

#### 2.2 Label elements

## Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H412-Harmful to aquatic life with long lasting effects. H290-May be corrosive to metals. H314-Causes severe skin burns and eye damage.

P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.

P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P390-Absorb spillage to prevent material damage.

Methanesulphonic acid  
 Myristyl dimethyl aminoxide  
 Phosphoric acid

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Myristyl dimethyl aminoxide</b>	
<b>Registration number (REACH)</b>	01-2119949262-37-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	222-059-3
<b>CAS</b>	3332-27-2
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411
<b>2-Butoxyethanol</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119475108-36-XXXX
<b>Index</b>	603-014-00-0

Page 3 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	203-905-0
<b>CAS</b>	111-76-2
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 3, H331 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
<b>Specific Concentration Limits and ATE</b>	ATE (oral): 1200 mg/kg ATE (as inhalation, Vapours): 3 mg/l

<b>Phosphoric acid</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119485924-24-XXXX
<b>Index</b>	015-011-00-6
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	231-633-2
<b>CAS</b>	7664-38-2
<b>content %</b>	1-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Met. Corr. 1, H290 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318
<b>Specific Concentration Limits and ATE</b>	Skin Corr. 1B, H314: >=25 % Skin Irrit. 2, H315: >=10 % Eye Dam. 1, H318: >=25 % Eye Irrit. 2, H319: >=10 % ATE (oral): 500 mg/kg

<b>Methanesulphonic acid</b>	
<b>Registration number (REACH)</b>	01-2119491166-34-XXXX
<b>Index</b>	607-145-00-4
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	200-898-6
<b>CAS</b>	75-75-2
<b>content %</b>	1-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Met. Corr. 1, H290 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
 The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.  
 Cauterizations not treated lead to wounds difficult to heal.

## Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

## Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Corrosive burns on skin as well as mucous membrane possible.

Necrosis

Risk of serious damage to eyes.

Corneal damage.

Danger of blindness.

Pain in the mouth and throat

Gastrointestinal disturbances

Oesophageal perforation

Gastric perforation

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of nitrogen

Oxides of carbon

Oxides of sulphur

Toxic gases

### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 20.11.2023 / 0003

Replacing version dated / version: 15.11.2023 / 0002

Valid from: 20.11.2023

PDF print date: 20.11.2023

Reactivation Shampoo

Art.: 806999

## 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

Neutralising is possible (only from a specialist).

Diluting with water is possible.

Flush residue using copious water.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Handle and open container with care.

There should be an eyewash station and safety shower located near the area of use.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not use acid sensitive materials.

Acid-resistant floor necessary.

Do not store with alkalis.

Store at room temperature.

Store in a dry place.

## 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

GB	Chemical Name	2-Butoxyethanol	
	WEL-TWA: 25 ppm (123 mg/m <sup>3</sup> ) (WEL), 20 ppm (98 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 50 ppm (246 mg/m <sup>3</sup> ) (WEL, EU)	---
	Monitoring procedures:	-	Compur - KITA-190 U(C) (548 873)

GB IRL M

Page 6 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

- DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)
- NIOSH 1403 (ALCOHOLS IV) - 2003
- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990

BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV) Other information: Sk (WEL)

Chemical Name		2-Butoxyethanol	
OELV-8h: 20 ppm (98 mg/m <sup>3</sup> ) (OELV-8h, EU)	OELV-15min: 50 ppm (246 mg/m <sup>3</sup> ) (OELV-15min, EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-190 U(C) (548 873)</li> <li>- DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)</li> <li>- NIOSH 1403 (ALCOHOLS IV) - 2003</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990</li> </ul>		
BLV: 200 mg/g creatinine (Butoxyacetic acid (BAA) in urine, h) (ACGIH-BEI)	Other information: Sk, IOELV		

Chemical Name		2-Butoxyethanol	
OELV-8h: 20 ppm (98 mg/m <sup>3</sup> ) (OELV-8h, UE)	OELV-ST: 50 ppm (246 mg/m <sup>3</sup> ) (OELV-ST, UE)	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-190 U(C) (548 873)</li> <li>- DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)</li> <li>- NIOSH 1403 (ALCOHOLS IV) - 2003</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990</li> </ul>		
BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Skin		

Chemical Name		Phosphoric acid	
WEL-TWA: 1 mg/m <sup>3</sup> (WEL, EU)	WEL-STEL: 2 mg/m <sup>3</sup> (WEL, EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air)</li> <li>- OSHA ID-111 (Phosphoric Acid in Workplace Atmospheres)</li> <li>- OSHA ID-165SG (Acid Mist In Workplace Atmospheres) - 1985</li> </ul>		
BMGV: ---	Other information: ---		

Chemical Name		Phosphoric acid	
OELV-8h: 1 mg/m <sup>3</sup> (OELV-8h, EU)	OELV-15min: 2 mg/m <sup>3</sup> (OELV-15min, EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air)</li> <li>- OSHA ID-111 (Phosphoric Acid in Workplace Atmospheres)</li> <li>- OSHA ID-165SG (Acid Mist In Workplace Atmospheres) - 1985</li> </ul>		
BLV: ---	Other information: IOELV		

Chemical Name		Phosphoric acid	
OELV-8h: 1 mg/m <sup>3</sup> (OELV-8h, UE)	OELV-ST: 2 mg/m <sup>3</sup> (OELV-ST, UE)	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- INSHT MTA/MA-019/A90 (Determination of inorganic acid anions in air)</li> <li>- OSHA ID-111 (Phosphoric Acid in Workplace Atmospheres)</li> <li>- OSHA ID-165SG (Acid Mist In Workplace Atmospheres) - 1985</li> </ul>		
BMGV: ---	Other information: ---		

Chemical Name		Glycerol	
WEL-TWA: 10 mg/m <sup>3</sup> (mist)	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		

**Myristyl dimethyl aminoxide**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,034	mg/l	
	Environment - marine		PNEC	0,003	mg/l	
	Environment - sediment, freshwater		PNEC	5,24	mg/kg dry weight	

Page 7 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

	Environment - sediment, marine		PNEC	0,524	mg/kg dry weight	
	Environment - soil		PNEC	1,02	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	24	mg/l	
	Environment - oral (animal feed)		PNEC	1,1	mg/kg bw/day	
	Environment - sporadic (intermittent) release		PNEC	0,034	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,53	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,5	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,44	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,2	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day	

<b>2-Butoxyethanol</b>						
<b>Area of application</b>	<b>Exposure route / Environmental compartment</b>	<b>Effect on health</b>	<b>Descriptor</b>	<b>Value</b>	<b>Unit</b>	<b>Note</b>
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	



Page 8 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m <sup>3</sup>	

Phosphoric acid						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, local effects	DNEL	0,73	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	2	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	4,57	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,36	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	2,92	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10,7	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m <sup>3</sup>	

Methanesulphonic acid						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,012	mg/l	
	Environment - marine		PNEC	0,0012	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,12	mg/l	
	Environment - sediment, freshwater		PNEC	0,0251	mg/kg	
	Environment - soil		PNEC	0,00183	mg/kg	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, marine		PNEC	0,0044	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	8,33	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,44	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	1,44	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,42	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	8,33	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,76	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,7	mg/m <sup>3</sup>	



GB IRL M

Page 9 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	19,44	mg/kg	
---------------------	----------------	-----------------------------	------	-------	-------	--

Glycerol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,885	mg/l	
	Environment - marine		PNEC	0,088	mg/l	
	Environment - sewage treatment plant		PNEC	1000	mg/l	
	Environment - sediment, freshwater		PNEC	3,3	mg/kg dw	
	Environment - sediment, marine		PNEC	0,33	mg/kg dw	
	Environment - soil		PNEC	0,141	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	8,85	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	33	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	229	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	56	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |  
 OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |  
 BLV = Biological limit value |  
 Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average)

Page 10 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 20.11.2023 / 0003  
Replacing version dated / version: 15.11.2023 / 0002  
Valid from: 20.11.2023  
PDF print date: 20.11.2023  
Reactivation Shampoo  
Art.: 806999

[9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).  
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |  
OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period)  
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).  
[8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) |  
BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) |  
Other information: Skin = Possibility of a significant uptake through the skin.  
[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).  
(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.  
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
These are specified by e.g. EN 14042.  
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles with side protection (EN 166).  
If applicable  
Face protection (EN 166).

Skin protection - Hand protection:  
Use acid resistant protective gloves (EN ISO 374).  
If applicable  
Protective gloves in butyl rubber (EN ISO 374).  
Protective Neoprene® / polychloroprene gloves (EN ISO 374).  
Protective nitrile gloves (EN ISO 374).  
Protective PVC gloves (EN ISO 374).  
Minimum layer thickness in mm:  
0,5  
Permeation time (penetration time) in minutes:  
480  
Protective hand cream recommended.  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Page 11 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 20.11.2023 / 0003  
Replacing version dated / version: 15.11.2023 / 0002  
Valid from: 20.11.2023  
PDF print date: 20.11.2023  
Reactivation Shampoo  
Art.: 806999

Respiratory protection:  
If OES or MEL is exceeded.  
Filter A P2 (EN 14387), code colour brown, white  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	1
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	There is no information available on this parameter.
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,03 g/cm <sup>3</sup>
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

### 9.2 Other information

Corrosive to metals: Corrosive to aluminium and steel

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Product corrodes metals.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

Avoid contact with strong alkalis (exothermic reaction possible).

Avoid contact with certain metals e.g. aluminium (development of hydrogen gas possible).

### 10.4 Conditions to avoid

None known

### 10.5 Incompatible materials

Avoid contact with strong alkalis.

Page 12 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

Avoid contact with strong oxidizing agents.  
 Avoid contact with certain metals e.g. aluminium.  
 Avoid contact with acid sensitive materials.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

#### Reactivation Shampoo

Art.: 806999

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			Vapours, calculated value
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			Dusts or mist, calculated value
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

#### Myristyl dimethyl aminoxide

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>300-2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	Regulation (EC) 440/2008 B.17 (IN VITRO MAMMALIAN CELL GENE MUTATION TESTS USING HPRT + XPRT GENES)	Negative

Page 13 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

Germ cell mutagenicity:				Mouse	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	100	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:				Mouse	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative

<b>2-Butoxyethanol</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	ATE	3	mg/l			Vapours
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	720	mg/kg bw/d			
Aspiration hazard:						No

Page 14 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	

Phosphoric acid						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	500	mg/kg			
Acute toxicity, by oral route:	LD50	300-2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Skin corrosion/irritation:				Rabbit		Skin Corr. 1B
Serious eye damage/irritation:				Rabbit		Eye Dam. 1
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Symptoms:						respiratory distress, vomiting, coughing, collapse, cramps, mucous membrane irritation, shock

Methanesulphonic acid						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 15 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

Acute toxicity, by oral route:	LD50	648,7	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	The toxicity is determined by the corrosivity of the product.
Acute toxicity, by dermal route:	LD50	>1000-<2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	The toxicity is determined by the corrosivity of the product.
Acute toxicity, by inhalation:	LC50	1,1-1,4	mg/l/6h	Rat		
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Skin Corr. 1B
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity:	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1805	mg/kg	Rat		
Symptoms:						asthmatic symptoms, respiratory distress, burning of the membranes of the nose and throat, cornea opacity, coughing, headaches, dizziness, nausea and vomiting.

**Glycerol**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>10000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	IUCLID Chem. Data Sheet (ESIS)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig		No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	2000	mg/kg/d			Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	3,91	mg/l	Rat		(14d)
Aspiration hazard:						Negative





Page 17 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree(complexing organic substance) $\geq$ 80%/28d: n.a.
Other information:	AOX			%			According to the recipe, contains no AOX.

**Myristyl dimethyl aminoxide**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1-10	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	

Page 18 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

12.1. Toxicity to daphnia:	EC50	48h	>1-10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>0,1-1	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:						OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	67,5	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,7				calculated value
12.3. Bioaccumulative potential:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**2-Butoxyethanol**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	Readily biodegradable

Page 19 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

12.3. Bioaccumulative potential:	BCF		3,2				Slight
12.3. Bioaccumulative potential:	Log Pow		0,81			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Not to be expected
12.4. Mobility in soil:	H (Henry)		0,0000016	atm*m3/mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

**Phosphoric acid**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	3,0 - 3,25	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.

**Methanesulphonic acid**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	73	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	70	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	7,2-20	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		10d	84	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.2. Persistence and degradability:		28d	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-2,38				Not to be expected

Page 20 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

Toxicity to bacteria:	EC50	30min	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
-----------------------	------	-------	-------	------	------------------	---	--

<b>Glycerol</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	> 5000	mg/l	Carassius auratus		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC5	72h	3200	mg/l			Entosiphon sulcatum
12.1. Toxicity to algae:	EC50		2900	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		14d	63	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.2. Persistence and degradability:	BOD/COD		>60	%			
12.2. Persistence and degradability:	BOD5/COD		> 50	%			
12.2. Persistence and degradability:	DOC		>70	%			Readily biodegradable
12.2. Persistence and degradability:	BOD5		0,87	g/g			
12.2. Persistence and degradability:	COD		1,16	g/g			
12.3. Bioaccumulative potential:	Log Pow		-1,75			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Bioaccumulation is unlikely (LogPow < 1).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC5	16h	> 10000	mg/l	Pseudomonas putida		

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 20.11.2023 / 0003

Replacing version dated / version: 15.11.2023 / 0002

Valid from: 20.11.2023

PDF print date: 20.11.2023

Reactivation Shampoo

Art.: 806999

### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.


Dispose of packaging that cannot be cleaned in the same manner as the substance.

Uncontaminated packaging can be recycled.


## SECTION 14: Transport information

### General statements


#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1760	
14.2. UN proper shipping name:		
UN 1760 CORROSIVE LIQUID, N.O.S. (METHANESULFONIC ACID, PHOSPHORIC ACID)		
14.3. Transport hazard class(es):	8	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	E	
Classification code:	C9	
LQ:	5 L	
Transport category:	3	

#### Transport by sea (IMDG-code)

14.1. UN number or ID number:	1760	
14.2. UN proper shipping name:		
UN 1760 CORROSIVE LIQUID, N.O.S. (METHANESULFONIC ACID, PHOSPHORIC ACID)		
14.3. Transport hazard class(es):	8	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	
IMDG Code segregation group 1 - Acids		
Marine Pollutant:	Not applicable	
EmS:	F-A, S-B	

#### Transport by air (IATA)

14.1. UN number or ID number:	1760	
14.2. UN proper shipping name:		
UN 1760 Corrosive liquid, n.o.s. (METHANESULFONIC ACID, PHOSPHORIC ACID)		
14.3. Transport hazard class(es):	8	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	

#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

#### 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Page 22 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 20.11.2023 / 0003  
 Replacing version dated / version: 15.11.2023 / 0002  
 Valid from: 20.11.2023  
 PDF print date: 20.11.2023  
 Reactivation Shampoo  
 Art.: 806999

Directive 2010/75/EU (VOC): ~ 5,37 %  
**REGULATION (EC) No 648/2004**  
 5 % or over but less than 15 %  
 cationic surfactants  
 less than 5 %  
 phosphates

perfumes  
 CITRAL  
 LIMONENE

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

National requirements/regulations on safety and health protection must be applied when using work equipment.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 3, 11, 12, 16  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Dam. 1, H318	Classification based on the pH value.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Met. Corr. 1, H290	Classification based on test data.
Skin Corr. 1, H314	Classification based on the pH value.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.  
 H290 May be corrosive to metals.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H335 May cause respiratory irritation.  
 H400 Very toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.

Eye Dam. — Serious eye damage  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Met. Corr. — Substance or mixture corrosive to metals  
 Skin Corr. — Skin corrosion  
 Acute Tox. — Acute toxicity - oral  
 Skin Irrit. — Skin irritation  
 Aquatic Acute — Hazardous to the aquatic environment - acute  
 Acute Tox. — Acute toxicity - inhalation  
 Eye Irrit. — Eye irritation



Page 23 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 20.11.2023 / 0003  
Replacing version dated / version: 15.11.2023 / 0002  
Valid from: 20.11.2023  
PDF print date: 20.11.2023  
Reactivation Shampoo  
Art.: 806999

Acute Tox. — Acute toxicity - dermal  
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
Guidelines for the preparation of safety data sheets as amended (ECHA).  
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
Safety data sheets for the constituent substances.  
ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).  
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
National Lists of Occupational Exposure Limits for each country as amended.  
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOX Adsorbable organic halogen compounds  
approx. approximately  
Art., Art. no. Article number  
ASTM ASTM International (American Society for Testing and Materials)  
ATE Acute Toxicity Estimate  
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
BCF Bioconcentration factor  
BSEF The International Bromine Council  
bw body weight  
CAS Chemical Abstracts Service  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
DOC Dissolved organic carbon  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
EC European Community  
ECHA European Chemicals Agency  
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
etc. et cetera  
EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
Koc Adsorption coefficient of organic carbon in the soil  
Kow octanol-water partition coefficient

Page 24 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 20.11.2023 / 0003  
Replacing version dated / version: 15.11.2023 / 0002  
Valid from: 20.11.2023  
PDF print date: 20.11.2023  
Reactivation Shampoo  
Art.: 806999

IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population  
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute for Occupational Safety and Health (USA)  
NLP No-longer-Polymer  
NOEC, NOEL No Observed Effect Concentration/Level  
OECD Organisation for Economic Co-operation and Development  
org. organic  
OSHA Occupational Safety and Health Administration (USA)  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.