- GB (RL M)

Page 1 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax Art.: 462999

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### **Shield & Gloss Wax**

Art.: 462999

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Sealing

### **Uses advised against:**

No information available at present.

### 1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna Telefon: +49 (0) 2303 / 9

www.koch-chemie.com

Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26 info@koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

### 1.4 Emergency telephone number

### Emergency information services / official advisory body:

(RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

### Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement

Skin Corr. 1B H314-Causes severe skin burns and eye damage.

Eye Dam. 1 H318-Causes serious eye damage.

Aquatic Chronic 2 H411-Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

®®™M

Page 2 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999



Danger

H314-Causes severe skin burns and eye damage. H411-Toxic to aquatic life with long lasting effects.

P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.

P301+P330+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates

Amines, tallow alkyl, ethoxylated

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated

#### 2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

### **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

### n.a. **3.2 Mixtures**

2-Butoxyethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475108-36-XXXX
Index	603-014-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	203-905-0
CAS	111-76-2
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H302
factors	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
Specific Concentration Limits and ATE	ATE (oral): 1200 mg/kg

1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, diesters with vegetable-oil fatty acids, C18-unsatd., Me sulfates	
(salts)	
Registration number (REACH)	01-2119983493-26-XXXX
Index	

(B) (R) (M)

Page 3 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

EINECS, ELINCS, NLP, REACH-IT List-No.	939-685-4
CAS	
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Skin Irrit. 2, H315
factors	Eye Dam. 1, H318
	Aquatic Chronic 3, H412

Poly[3-((2-aminoethyl)amino)propyl]methyl(dimethyl)siloxane, methoxy-terminated	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	102782-92-3
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Skin Corr. 1B, H314
factors	Eye Dam. 1, H318
	Aquatic Chronic 3, H412

Butene, homopolymer, hydrogenated	
Registration number (REACH)	01-2119457401-46-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	68937-10-0
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 3, H226
factors	Asp. Tox. 1, H304

Amines, tallow alkyl, ethoxylated	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	61791-26-2
content %	2,5-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H302
factors	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Siloxanes and Silicones, di-Me, 3-[3-[(3-coco	
amidopropyl)dimethylammonio]-2-hydroxypropoxy]propyl group-	
terminated, acetates (salts)	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	134737-05-6
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Aquatic Chronic 2, H411
factors	

500-013-6
9004-78-8
1-<2,5
Acute Tox. 4, H302
5

(B) (R) (M)

Page 4 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Acetic acid	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475328-30-XXXX
Index	607-002-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	200-580-7
CAS	64-19-7
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 3, H226
factors	Met. Corr. 1, H290
	Skin Corr. 1A, H314
	Eye Dam. 1, H318
Specific Concentration Limits and ATE	Skin Corr. 1A, H314: >=90 %
	Skin Corr. 1B, H314: >=25 %
	Skin Irrit. 2, H315: >=10 %
	Eye Irrit. 2, H319: >=10 %

Ethanol	
Registration number (REACH)	01-2119457610-43-XXXX
Index	603-002-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	200-578-6
CAS	64-17-5
content %	0,1-<2
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Eye Irrit. 2, H319
Specific Concentration Limits and ATE	Eye Irrit. 2, H319: >=50 %

Dodecamethylcyclohexasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119517435-42-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	208-762-8
CAS	540-97-6
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-	
factors	

Decamethylcyclopentasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	01-2119511367-43-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	208-764-9
CAS	541-02-6
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	

Octamethylcyclotetrasiloxane	PBT-substance
	vPvB-substance
	SVHC-substance
Registration number (REACH)	01-2119529238-36-XXXX
Index	014-018-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	209-136-7
CAS	556-67-2
content %	<0,1
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 3, H226
factors	Repr. 2, H361f
	Aquatic Chronic 1, H410 (M=10)

- GB (RL) (M)

Page 5 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Cauterizations not treated lead to wounds difficult to heal.

#### **Eve contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Corrosive burns on skin as well as mucous membrane possible.

Risk of serious damage to eyes.

Conjunctivitis

Corneal damage.

Danger of blindness.

Ingestion:

pain in the mouth and throat

stomach pain

Oesophageal perforation

Gastric perforation

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

### Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Toxic gases

### 5.3 Advice for firefighters

- GB (RL) (M)

Page 6 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

Flush residue using copious water.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Handle and open container with care.

There should be an eyewash station and safety shower located near the area of use.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special storage conditions.

Under all circumstances prevent penetration into the soil.

Store in a well ventilated place.

(B) (RL) (M) Page 7 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax Art.: 462999

## Store cool. 7.3 Specific end use(s)

No information available at present.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Chemical Name 2-Butoxyethano		
WEL-TWA: 25 ppm (123 mg/m3) (WEL), 20 ppm		
(98 mg/m3) (EU)	(W22 3 122. 33 pp. (2 13 mg/m3) (W22, 23)	
Monitoring procedures:	Compur - KITA-190 U(C) (548 873)	
31	DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG	G(E) (Solvent mixtures 3) -
_	2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 c	
_	NIOSH 1403 (ALCOHOLS IV) - 2003	(=== 1,
_	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (S	CREENING)) - 1996
-	OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990	,,
BMGV: 240 mmol butoxyacetic acid/mol creatinir		Sk (WEL)
Chemical Name 2-Butoxyethano		
OELV-8h: 20 ppm (98 mg/m3) (OELV-8h, EU)	OELV-15min: 50 ppm (246 mg/m3) (OELV-	
3, 3, (3, 3, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4,	15min, EU)	
Monitoring procedures: -	Compur - KITA-190 U(C) (548 873)	
	DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG	G(E) (Solvent mixtures 3) -
_	2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 c	
_	NIOSH 1403 (ALCOHOLS IV) - 2003	,
-	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (S	CREENING)) - 1996
-	OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990	
BLV: 200 mg/g creatinine (Butoxyacetic acid (BA	A) in urine, h) (ACGIH-BEI)  Other information:	Sk, IOELV
Chemical Name     2-Butoxyethano		
OELV-8h: 20 ppm (98 mg/m3) (OELV-8h, UE)	OELV-ST: 50 ppm (246 mg/m3) (OELV-ST, UE)	
Monitoring procedures: -	Compur - KITA-190 U(C) (548 873)	1
	DFG MethNr. 2 (D) (Loesungsmittelgemische 3), DFG	G(E) (Solvent mixtures 3) -
-	2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 c	ard 32-2 (2004)
-	NIOSH 1403 (ALCOHOLS IV) - 2003	
-	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (S	CREENING)) - 1996
-	OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990	
BMGV: 240 mmol butoxyacetic acid/mol creatining	ne in urine, post shift (BMGV)  Other information:	Skin
© Chemical Name Acetic acid		
WEL-TWA: 10 ppm (25 mg/m3) (WEL, EU)	WEL-STEL: 20 ppm (50 mg/m3) (WEL, EU)	
Monitoring procedures: -	Draeger - Acetic Acid 5/a (67 22 101)	
-	Compur - KITA-216 S (549 194)	
-	NIOSH 1603 (Acetic acid in workplace atmospheres) -	
	OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CE	EN/ENTR/000/2002-16
-	card 64-5 (2004)	
BMGV:	Other information:	
Chemical Name Acetic acid		
OELV-8h: 10 ppm (25 mg/m3) (OELV-8h, EU)	OELV-15min: 20 ppm (50 mg/m3) (OELV-15min, EU)	
Monitoring procedures: -	Draeger - Acetic Acid 5/a (67 22 101)	•
-	Compur - KITA-216 S (549 194)	
-	NIOSH 1603 (Acetic acid in workplace atmospheres) -	
	OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CE	EN/ENTR/000/2002-16
-	card 64-5 (2004)	
BLV:	Other information:	IOELV
M Chemical Name Acetic acid		
OELV-8h: 10 ppm (25 mg/m3) (OELV-8h, UE)	OELV-ST: 20 ppm (50 mg/m3) (OELV-ST, UE)	
Monitoring procedures: -	Draeger - Acetic Acid 5/a (67 22 101)	

(B) (R) (M)

Page 8 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

- - -	NIOSH 1603 (Acetic acid in workplace atmospheres) - 1994 OSHA PV2119 (Acetic acid) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 64-5 (2004)			
BMGV:	Other information:			

Chemical Name	Ethanol		
WEL-TWA: 1000 ppm (1920 mg	g/m3)	WEL-STEL:	
Monitoring procedures:	-	Draeger - Alcohol 25/a Ethanol (81 01 631)	
	-	Compur - KITA-104 SA (549 210)	
		DFG (D) (Loesungsmittelgemische), Methode Nr. 6 DF	G (E) (Solvent mixtures) -
	-	2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 c	ard 63-2 (2004)
		DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2013	- EU project
	-	BC/CEN/ENTR/000/2002-16 card 63-2 (2004)	
		DFG Meth. Nr. 3 (D) (Loesungsmittelgemische) - 2013	- EU project
	-	BC/CEN/ENTR/000/2002-16 card 63-2 (2004)	
BMGV:		Other information: -	

Chemical Name	Ethanol		
OELV-8h: 1000 ppm		OELV-15min:	
Monitoring procedures:	-	Draeger - Alcohol 25/a Ethanol (81 01 631)	
	-	Compur - KITA-104 SA (549 210)	
		DFG (D) (Loesungsmittelgemische), Methode Nr. 6 DF	G (E) (Solvent mixtures) -
	-	2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 of	card 63-2 (2004)
		DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2013	- EU project
	-	BC/CEN/ENTR/000/2002-16 card 63-2 (2004)	
		DFG Meth. Nr. 3 (D) (Loesungsmittelgemische) - 2013	- EU project
	-	BC/CEN/ENTR/000/2002-16 card 63-2 (2004)	
BLV:		Other information:	

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	

(B) (R) (M)

Page 9 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3	

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,017	mg/l	
	Environment - sediment,		PNEC	1,7	mg/kg dw	
	freshwater					
	Environment - marine		PNEC	0,002	mg/l	
	Environment - sediment,		PNEC	0,17	mg/kg dw	
	marine					
	Environment - sewage		PNEC	10	mg/l	
	treatment plant					
	Environment - soil		PNEC	0,331	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic	DNEL	2,17	mg/m3	
		effects				
Consumer	Human - dermal	Long term, systemic	DNEL	56,25	mg/kg	
		effects			bw/d	
Consumer	Human - oral	Long term, systemic	DNEL	1,25	mg/kg	
		effects			bw/d	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	8,72	mg/m3	
		effects				
Workers / employees	Human - dermal	Long term, systemic	DNEL	112,5	mg/kg	
		effects			bw/d	

Ethanol						
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water,		PNEC	2,75	mg/l	
	sporadic (intermittent)					
	release					
	Environment - sewage		PNEC	580	mg/l	
	treatment plant					
	Environment - sediment,		PNEC	3,6	mg/kg dry	
	freshwater				weight	
	Environment - soil		PNEC	0,63	mg/kg dry	
					weight	
	Environment - oral (animal		PNEC	0,38	g/kg feed	
	feed)					

(B) (R) (M)

Page 10 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m3
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m3

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - sediment, freshwater		PNEC	2,826	mg/kg dw	
	Environment - sediment, marine		PNEC	0,282	mg/kg dw	
	Environment - soil		PNEC	3,336	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	1,5	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,3	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	6,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	11	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1,22	mg/m3	

Decamethylcyclopenta	siloxane					
Area of application	Exposure route / Environmental	Effect on health	Descripto r	Value	Unit	Note
	compartment					
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - sediment,		PNEC	11	mg/kg	
	freshwater					
	Environment - sediment,		PNEC	1,1	mg/kg	
	marine					
	Environment - soil		PNEC	2,54	mg/kg	

(B) (R) (M)

Page 11 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - oral (animal feed)		PNEC	16	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,3	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	4,3	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,3	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	4,3	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	97,3	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	24,2	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	97,3	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	24,2	mg/m3	

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	1,5	μg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - soil		PNEC	0,54	mg/kg	
	Environment - sediment, freshwater		PNEC	3	mg/kg	
	Environment - marine		PNEC	0,15	μg/l	
	Environment - sediment, marine		PNEC	0,3	mg/kg	
	Environment - oral (animal feed)		PNEC	41	mg/kg feed	
Consumer	Human - oral	Short term, systemic effects	DNEL	3,7	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,7	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	13	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	13	mg/kg	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	73	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	73	mg/m3	

- GB (RL) M

Page 12 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period)
  EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).
- © OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE).
- OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).  $\mid$

BLV = Biological limit value |

- Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).
- OELV-8h = Occupational Exposure Limit Value 8 h (8-hour reference period as a time-weighted average)
- [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE).
- OELV-ST = Occupational Exposure Limit Value Short-term (15-minute reference period)
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- [8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) |
- BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.
- [11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).
- (EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

### 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

- GB (RL) M

Page 13 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective gloves made of butyl (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Protective PVC gloves (EN ISO 374).

Minimum layer thickness in mm:

> 0,5

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state: Liquid
Colour: Orange
Odour: Fruity

Melting point/freezing point:

There is no information available on this parameter.

### KochChemie<sup>6</sup> **ExcellenceForExperts.**

GB (RL) (M

Page 14 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density:

Relative vapour density:

Particle characteristics:

9.2 Other information

No information available at present.

There is no information available on this parameter.

There is no information available on this parameter. There is no information available on this parameter.

There is no information available on this parameter.

4,5

There is no information available on this parameter.

Mixable

Does not apply to mixtures.

There is no information available on this parameter.

0,97 g/ml

There is no information available on this parameter.

Does not apply to liquids.

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

None known

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Shield & Gloss Wax			·			
Art.: 462999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated
						value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated
						value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						

(B) (R) (M)

Page 15 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-		
RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

2-Butoxyethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by oral route:	LD50	1746	mg/kg	Rat		
Acute toxicity, by dermal	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit		Irritant, Product
						removes fat.
Serious eye				Rabbit		Intensively
damage/irritation:						irritant
Respiratory or skin				Guinea pig		Not sensitizising
sensitisation:						
Symptoms:						acidosis,
						ataxia,
						breathing
						difficulties,
						respiratory
						distress,
						drowsiness,
						unconsciousnes
						s, annoyance,
						coughing,
						headaches,
						gastrointestinal
						disturbances,
						insomnia,
						mucous
						membrane
						irritation,
						dizziness

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Mouse	OECD 423 (Acute	
					Oral Toxicity - Acute	
					Toxic Class Method)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Skin Irrit. 2
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Dam. 1
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig		Not sensitizising
sensitisation:						
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative,
					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion

-GB (RL M)-

Page 16 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion
Symptoms:						gastrointestinal disturbances
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	500	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	

Butene, homopolymer, hydrogenated							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat			
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rabbit			
route:							
Aspiration hazard:						Asp. Tox. 1	

Amines, tallow alkyl, ethoxylated							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>300-2000	mg/kg	Rat		Analogous conclusion	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2	
Serious eye damage/irritation:						Eye Dam. 1	

Siloxanes and Silicones, di-Me, 3-[3-[(3-coco amidopropyl)dimethylammonio]-2-hydroxypropoxy]propyl group-terminated, acetates (salts)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rat		
route:						
Acute toxicity, by inhalation:	LC50	55-60	mg/l/4h			Vapours
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye				Rabbit		Not irritant
damage/irritation:						
Respiratory or skin						Not
sensitisation:						sensitizising,
						Analogous
						conclusion
Germ cell mutagenicity:					(Ames-Test)	Negative

Phenolpolyethoxylate								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	500-2000	mg/kg	Rat	OECD 423 (Acute			
					Oral Toxicity - Acute			
					Toxic Class Method)			
Acute toxicity, by dermal	LD50	2140	mg/kg	Rabbit	,			
route:								
Aspiration hazard:						No		
Symptoms:						gastrointestinal		
•						disturbances		

Acetic acid								
Endpoint	Value	Unit	Organism	Test method	Notes			
LD50	3310	mg/kg	Rat					
LD50	>1060	mg/kg	Rabbit					
LC50	11,4	mg/l/4h	Rat					
	LD50 LD50	LD50 3310 LD50 >1060	LD50 3310 mg/kg LD50 >1060 mg/kg	LD50         3310         mg/kg         Rat           LD50         >1060         mg/kg         Rabbit	LD50         3310         mg/kg         Rat           LD50         >1060         mg/kg         Rabbit			

(B) (R) (M)

Page 17 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Skin corrosion/irritation:				Corrosive
Serious eye				Corrosive
damage/irritation:				
Respiratory or skin				Possible
sensitisation:				
Germ cell mutagenicity:			OECD 471 (Bacterial	Negative
			Reverse Mutation	
			Test)	
Symptoms:				acidosis,
				respiratory
				distress,
				burning of the
				membranes of
				the nose and
				throat,
				diarrhoea,
				disturbed hear
				rhythm, cornea
				opacity,
				cramps,
				circulatory
				collapse,
				stomach
				cramps, shock
				nausea and
				vomiting.

Ethanol	1					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	51-124,7	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Irrit. 2
damage/irritation:					Eye	
-					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin
sensitisation:					Sensitisation - Local	contact)
					Lymph Node Assay)	,
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
				•	Test)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
- ,					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 475	Negative
<b>.</b>					(Mammalian Bone	
					Marrow Chromosome	
					Aberration Test)	
Carcinogenicity:	NOAEL	>3000	mg/kg	Rat	OECD 451	24 mon
5 ,					(Carcinogenicity	
					Studies)	

(B) (R) (M)

Page 18 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Reproductive toxicity:	NOAEL	5200	mg/kg bw/d	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAL	>20	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Male
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1730	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Female
Symptoms:						respiratory distress, drowsiness, unconsciousnes s, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute	
Aguta taxiaity, by darmal	LD50	>2000	20 a /l.a	Rat	Toxic Class Method)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Kal	OECD 402 (Acute	
route: Skin corrosion/irritation:				Rabbit	Dermal Toxicity) OECD 404 (Acute	Not irritant
Skin corrosion/irritation.				Kabbit	Decd 404 (Acute	Not imiant
Serious eye				Rabbit	Irritation/Corrosion) OECD 405 (Acute	Not irritant
•				Kabbit	Eve	INOL IIIILAIIL
damage/irritation:					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:				Guiriea pig	Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
Germ cell mutagericity.				typhimurium	Reverse Mutation	ivegative
				тургііншіші	Test)	
Germ cell mutagenicity:				Mouse	OECD 474	Negative
Germ cell mutagericity.				iviouse	(Mammalian	ivegative
					Erythrocyte	
					Micronucleus Test)	
Specific target organ toxicity -	NOAEL	0,15	mg/kg	Rat	OECD 407 (Repeated	
repeated exposure (STOT-	NOALL	0,13	bw/d	Ital	Dose 28-Day Oral	
RE):			DW/G		Toxicity Study in	
IXL).					Rodents)	
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rat	OECD 422	
repeated exposure (STOT-	110/ILL	1000	mg/kg	, tat	(Combined Repeated	
RE), oral:					Dose Tox. Study with	
,, 5.31.					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	

(B) (R) (M)

Page 19 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Decamethylcyclopentasiloxa Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
						Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by dermal	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	8,67	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
, ,		,			Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
				Rabbit		Not iiiitaiit
damage/irritation:					Eye	
D					Irritation/Corrosion)	<b>N</b> 1 / 1:
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin
sensitisation:					Sensitisation - Local	contact)
					Lymph Node Assay)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
com con matagementy.				Modes	Mammalian Cell Gene	rioganio
					Mutation Test)	
Germ cell mutagenicity:				Rat	OECD 474	Negativevapou
Germ cen matagemony.				INal	(Mammalian	Negativevapou
					Erythrocyte	
0 "				0 1 "	Micronucleus Test)	<b>N</b> 1 (1)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:				Rat	OECD 486	Negative
					(Unscheduled DNA	
					Synthesis (UDS) Test	
					with Mammalian Liver	
					Cells In Vivo)	
Carcinogenicity:					-,	Negative
Reproductive toxicity:				Rat		Negative
Specific target organ toxicity -	NOAEL	>=1000	mg/kg	Rat	OECD 408 (Repeated	. 10941110
repeated exposure (STOT-	NOALL	/=1000	bw/d	ιται	Dose 90-Day Oral	
RE), oral:			DW/U		Toxicity Study in	
RE), Oral.					,	
0 " 1	NOAEL	4000	/1	<b>D</b> .	Rodents)	
Specific target organ toxicity -	NOAEL	>=1600	mg/kg	Rat	OECD 410 (Repeated	
repeated exposure (STOT-			bw/d		Dose Dermal Toxicity -	
RE), dermal:					90-Day)	
Specific target organ toxicity -	NOAEL	>=160	mg/l/6h/d	Rat	OECD 453	Vapours
repeated exposure (STOT-					(Combined Chronic	
RE), inhalat.:					Toxicity/Carcinogenicit	
,,	Ī				y Studies)	

Octamethylcyclotetrasiloxar	ne					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4800	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>2375	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	36	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	

- GB (RL M)

Page 20 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

Skin corrosion/irritation:				Rat	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Carcinogenicity:	NOAEL	150	mg/kg	Rat	OECD 453	inhalation
					(Combined Chronic	
					Toxicity/Carcinogenicit	
					y Studies)	
Reproductive toxicity:	NOAEL			Rat	OECD 416 (Two-	Repr. 2
					generation	
					Reproduction Toxicity	
					Study)	
Reproductive toxicity	NOAEL	300	ppm	Rat	OECD 414 (Prenatal	
(Developmental toxicity):					Developmental	
					Toxicity Study)	
Specific target organ toxicity -	NOAEL	> 1	mg/kg	Rabbit	OECD 410 (Repeated	(21 d)
repeated exposure (STOT-					Dose Dermal Toxicity -	
RE), dermal:					90-Day)	
Specific target organ toxicity -	NOAEC	150	mg/kg	Rat	OECD 453	
repeated exposure (STOT-					(Combined Chronic	
RE), inhalat.:					Toxicity/Carcinogenicit	
					y Studies)	

### 11.2. Information on other hazards

Shield & Gloss Wax Art.: 462999						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

- GB (RL) (M)

Page 21 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

Other information:		Excessive
		alcohol
		consumption
		during
		pregnancy
		induces the
		foetus alcohol
		syndrome
		(reduced
		weight at birth,
		physical and
		mental
		disorders).,
		There is no
		sign that this
		syndrome is
		also caused by
		dermal or
		inhalative
		absorption.,
		Experiences on
		persons.

### **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	•						n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
Other information:							environment.
Other information.							elimination
							degree(comple
							ing organic substance)>=
							80%/28d: n.a.
Other information:	AOX	+		%			According to
Other Information.	707			/0			the recipe,
							contains no
							AOX.

2-Butoxyethanol
-----------------

(B) (R) (M)

Page 22 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	
12.3. Bioaccumulative potential:	Log Pow		0,83				Negative
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	1490	mg/l	Lepomis macrochirus	•	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to bacteria:	EC0	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	
12.5. Results of PBT and vPvB assessment					•		No PBT substance, No vPvB substance
12.4. Mobility in soil:	Koc		67				Expert judgement
12.4. Mobility in soil:	H (Henry)		0,00000 16	atm*m3/ mol			jaagomon

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,686	mg/l	Pimephales promelas	U.S. EPA ECOTOX Database	Analogous conclusion
12.2. Persistence and degradability:		28d	>60	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	Analogous conclusion

- GB (RL M)

Page 23 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

12.1. Toxicity to	EC50	48h	>8,6	mg/l	Daphnia magna	OECD 202	Analogous
daphnia:						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,39	mg/l	Pseudokirchnerie	OECD 201	Analogous
					lla subcapitata	(Alga, Growth	conclusion
						Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	1,2	mg/l	Pseudokirchnerie	OECD 201	Analogous
					lla subcapitata	(Alga, Growth	conclusion
						Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	>10	mg/l	Cyprinus caprio	OECD 203	Analogous
						(Fish, Acute	conclusion
						Toxicity Test)	
Toxicity to bacteria:	EC50	6d	100	mg/l	activated sludge		Analogous
							conclusion

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and						OECD 301 B	Readily
degradability:						(Ready Biodegradability - Co2 Evolution Test)	biodegradable
12.3. Bioaccumulative potential:							Not to be expected
12.1. Toxicity to fish:	LC50	96h	0,13	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	0,17	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC10	21d	>0,001- 0,01	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:	DOC	28d	73	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	12	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC50	72h	>969	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

- GB (RL M)-

Page 24 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

12.1. Toxicity to algae:	EC10	18h	4168	mg/l	OECD 201
					(Alga, Growth
					Inhibition Test)

Phenolpolyethoxylate Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	79	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>100	mg/l		OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>128	mg/l	Daphnia pulex	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		60d	40-50	%		OECD 311 (Anaerobic Biodeg. of Organic Comp. in Digested Sludge - by Measurement of Gas Production)	
12.2. Persistence and degradability:						OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	75	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	88	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	24h	47	mg/l	Daphnia magna		
12.2. Persistence and degradability:		30d	>99	%			
12.3. Bioaccumulative potential:	Log Pow		-0,17				
12.3. Bioaccumulative potential:	BCF		<1				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	15min	11	mg/l	Photobacterium phosphoreum		
Toxicity to bacteria:	EC5	16h	2850	mg/l	Pseudomonas putida		
Other information:	BOD5		0,88	g/g			

### Ethanol

- GB (RL M)

Page 25 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	120h	250	mg/l	Brachydanio rerio	OECD 212 (Fish, Short- term Toxicity Test on Embryo and Sac-fry Stages)	
12.1. Toxicity to daphnia:	EC50	48h	5414	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	97	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		(-0,35) - (-0,32)			,	Bioaccumulatio n is unlikely (LogPow < 1).
12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				(209. 0 1.).
12.4. Mobility in soil:	H (Henry)		0,00013				
12.4. Mobility in soil:	Koc		1,0				Highestimated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	
Other information:	COD		1,9	g/g		,	
Other information:	BOD5		1	g/g			

Dodecamethylcyclohexasiloxane											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to algae:	NOEC/NOEL	72h	>= 2	μg/l	Pseudokirchnerie	OECD 201					
					lla subcapitata	(Alga, Growth					
						Inhibition Test)					
12.1. Toxicity to fish:	NOEC/NOEL	49d	>= 4,4	μg/l	Pimephales						
•					promelas						
12.1. Toxicity to fish:	LD50	49d	>4,4	μg/l	Pimephales						
•					promelas						

(B) (R) (M)

Page 26 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

12.1. Toxicity to	NOEC/NOEL	21d	>4,6	μg/l	Daphnia magna		
daphnia:							
12.3. Bioaccumulative	Log Pow		8,87-				
potential:			9,45				
12.3. Bioaccumulative	BCF	49d	1160			OECD 305	
potential:						(Bioconcentration	
						<ul> <li>Flow-Through</li> </ul>	
						Fish Test)	
12.1. Toxicity to algae:	EC50	72h	>2	μg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	4,47	%		OECD 310	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	CO2 evolution
						CO2 in sealed	
						vessels	
						(Headspace	
						Test))	
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209	
						(Activated	
						Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	
12.5. Results of PBT							vPvB-
and vPvB assessment							substance,
							PBT-substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>16	μg/I	Oncorhynchus mykiss	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	Water toxicology is above the water-solubility value.
12.1. Toxicity to fish:	NOEC/NOEL	>60d	>14	μg/I	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	Water toxicology is above the water-solubility value.90 d
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>15	μg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to daphnia:	EC50	48h	>2,9	μg/I	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	EC50	96h	>12	μg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.

(B) (R) (M)

Page 27 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

12.1. Toxicity to algae:	NOEC/NOEL	96h	>= 12	µg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.
12.2. Persistence and degradability:		28d	0,14	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		7060			OECD 305 (Bioconcentration - Flow-Through Fish Test)	High
12.3. Bioaccumulative potential:	Log Pow		8,023				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							vPvB- substance, PBT-substance
Toxicity to annelids:	NOEC/NOEL		>=76	mg/kg	Eisenia foetida		
Toxicity to bacteria:	EC50	3h	>2000	mg/l	activated sludge	Regulation (EC) 440/2008 C.11 (BIODEGRADAT ION - ACTIVATED SLUDGE RESPIRATION INHIBITION)	
Water solubility:			<0,05	mg/l			@25°C

Octamethylcyclotetrasiloxane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							PBT-
and vPvB assessment							substance,
							vPvB-substance
12.3. Bioaccumulative	Log Pow		6,49			OECD 123	25,1 °C
potential:						(Partition	
						Coefficient (1-	
						Octanol / Water)	
						- Slow-Stirring	
						Method)	
12.1. Toxicity to fish:	LC50	96h	> 22	μg/l	Oncorhynchus		EPA OTS
					mykiss		797.1400
12.1. Toxicity to fish:	NOEC/NOEL	14d	0,0044	mg/l			
12.1. Toxicity to	NOEC/NOEL	21d	>0,0015	mg/l	Daphnia magna		
daphnia:							
12.1. Toxicity to	EC50	48h	> 15	μg/l	Daphnia magna		EPA OTS
daphnia:							797.1300
12.1. Toxicity to algae:	ErC10	96h	0,022	mg/l			
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l			

- GB (RL) (M)

Page 28 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

12.2. Persistence and degradability:		28d	3,7	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,1			,	A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	BCF	28d	12400		Pimephales promelas		EPA OTS 797.1520
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	ISO 8192	

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 08 discarded organic chemicals consisting of or containing hazardous substances

20 01 99 other fractions not otherwise specified

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

### **SECTION 14: Transport information**

### **General statements**

### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: 3265

14.2. UN proper shipping name:

UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (AMINO FUNCTIONAL SILOXANE, TALLOW ALKYL

AMINES, ETHOXYLATED)

14.3. Transport hazard class(es):14.4. Packing group:II

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code: E
Classification code: C3
LQ: 1 L
Transport category: 2

Transport by sea (IMDG-code)

14.1. UN number or ID number: 3265

14.2. UN proper shipping name:



## KochChemie<sup>®</sup> ExcellenceForExperts.

−@B (RL) (M)

Page 29 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (AMINO FUNCTIONAL SILOXANE, TALLOW ALKYL

8

Ш

AMINES, ETHOXYLATED)
14.3. Transport hazard class(es):
14.4. Packing group:

14.5. Environmental hazards: environmentally hazardous

IMDG Code segregation group 1 - Acids

Marine Pollutant:

EmS:

F-A, S-B
Segregation:

SGG1

Transport by air (IATA)

14.1. UN number or ID number: 3265

14.2. UN proper shipping name:

UN 3265 Corrosive liquid, acidic, organic, n.o.s. (AMINO FUNCTIONAL SILOXANE, TALLOW ALKYL AMINES,

ETHOXYLATED)

14.3. Transport hazard class(es):814.4. Packing group:II

14.5. Environmental hazards:

Not applicable



Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

2-Butoxyethanol

Decamethylcyclopentasiloxane

Octamethylcyclotetrasiloxane

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

contract our decer uning to etchage	,,		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for	referred to in Article 3(10) for
		the application of - Lower-tier	the application of - Upper-tier
		requirements	requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 31,4 %

Observe incident regulations.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.





### KochChemie<sup>6</sup> **ExcellenceForExperts.**

GB (RL) M

Page 30 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax Art.: 462999

### **SECTION 16: Other information**

Revised sections:

n.a.

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used		
(EC) No. 1272/2008 (CLP)			
Skin Corr. 1B, H314	Classification according to calculation procedure.		
Eye Dam. 1, H318	Classification according to calculation procedure.		
Aquatic Chronic 2, H411	Classification according to calculation procedure.		

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H361f Suspected of damaging fertility.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Skin Corr. — Skin corrosion Eye Dam. — Serious eye damage

Aguatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - inhalation

Skin Irrit. — Skin irritation Eye Irrit. — Eye irritation

Flam. Liq. — Flammable liquid

Asp. Tox. — Aspiration hazard

Aquatic Acute — Hazardous to the aquatic environment - acute

Met. Corr. — Substance or mixture corrosive to metals

Repr. — Reproductive toxicity

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

- GB (RL M)

Page 31 of 32

Art.: 462999

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

ncl. including, inclusive

**IUCLIDInternational Uniform Chemical Information Database** 

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

### KochChemie<sup>6</sup> **ExcellenceForExperts.**

GB (RL) (M

Page 32 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.01.2023 / 0001

Replacing version dated / version: 10.01.2023 / 0001

Valid from: 10.01.2023 PDF print date: 10.01.2023 Shield & Gloss Wax

Art.: 462999

n.a. not applicable n.av. not available not checked n.c. n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

organic

OSHA Occupational Safety and Health Administration (USA)

persistent, bioaccumulative and toxic PBT

PΕ Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning REACH

the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Telephone Tel.

TOC Total organic carbon

**UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

### These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.