© RI M

Page 1 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

### Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1 Product identifier**

### Silicon- & Wachsentferner

### Art.: 207999

Propan-2-ol Registration number (ECHA): 01-2119457558-25-XXXX Index: 603-117-00-0 EINECS, ELINCS, NLP, REACH-IT List-No.: 200-661-7 CAS: 67-63-0

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Solvent Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC35 - Washing and cleaning products Process category [PROC]: PROC 7 - Industrial spraying PROC10 - Roller application or brushing PROC19 - Manual activities involving hand contact Environmental Release Category [ERC]: ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) **Uses advised against:** 

#### No information available at present.

### 1.3 Details of the supplier of the safety data sheet

Koch-Chemie GmbH Einsteinstrasse 42 59423 Unna Telefon: +49 (0) 2303 / 9 86 70 - 0 Fax: +49 (0) 2303 / 9 86 70 - 26 info@koch-chemie.com www.koch-chemie.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

### **1.4 Emergency telephone number**

### Emergency information services / official advisory body:

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+1 872 5888271 (KCC)

© RI M

Page 2 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixtureClassification according to Regulation (EC)1272/2008 (CLP)Hazard classHazard categoryHazard statementFlam. Liq.2H225-Highly flammFuel write2H240 Courses paris

Flam. Liq.2H225-Highly flammable liquid and vapour.Eye Irrit.2H319-Causes serious eye irritation.STOT SE3H336-May cause drowsiness or dizziness.

### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



CAS: 67-63-0, Index:603-117-00-0

Danger

H225-Highly flammable liquid and vapour. H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P280-Wear eye protection / face protection. P312-Call a POISON CENTRE / doctor if you feel unwell. P403+P233-Store in a well-ventilated place. Keep container tightly closed.

### 2.3 Other hazards

No vPvB substance No PBT substance No substance with endocrine disrupting properties.

### **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	200-661-7
CAS	67-63-0
content %	100
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Eye Irrit. 2, H319
	STOT SE 3, H336

GBIRIM

Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

### 3.2 Mixtures

n.a.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. eyes, reddened watering eyes

headaches dizziness Coordination disorders mental confusion Effect on the central nervous system nausea vomiting Chemical pneumonitis (condition similar to pneumonia) **4.3 Indication of any immediate medical attention and special treatment needed** 

Symptomatic treatment.

**SECTION 5: Firefighting measures** 

### 5.1 Extinguishing media

Suitable extinguishing media

CO2 Extinction powder

Water jet spray Alcohol resistant foam

### Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

(BRI) M

Page 4 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

Oxides of carbon Toxic gases Possible build up of explosive/highly flammable vapour/air mixture.

### **5.3 Advice for firefighters**

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Use no flammable substances.

Fill the absorbed material into lockable containers. Flush residue using copious water.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

If applicable, suction measures at the workstation or on the processing machine necessary.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Use explosion-proof equipment.

Avoid contact with eyes or skin.

Handle and open container with care.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

GB (RL M

Page 5 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Do not store with flammable or self-igniting materials. Keep away from combustible material. Solvent resistant floor Earth devices. Protect from direct sunlight and warming. Store in a well ventilated place. Store cool. Store in a dry place. Suitable material: Stainless steel (alloy steel) Polyethylene Polypropylene Polyester Polytetrafluorethylene (PTFE) Unsuitable material: Aluminium Iron EPDM Polvstvrene Rubber Observe special storage conditions. 7.3 Specific end use(s)

#### 7.3 Specific end use(s) No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Dropon 2 ol

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Chemical Name	Propan-2-ol			
WEL-TWA: 400 ppm (999 mg/n	n3)	WEL-STEL:	500 ppm (1250 mg/m3)	
Monitoring procedures:	-	Draeger - Alcoh	ol 25/a i-Propanol (81 01 631)	
	-	Compur - KITA-	-122 SA(C) (549 277)	
	-	Compur - KITA-	-150 U (550 382)	
		DFG (D) (Loesu	ungsmittelgemische), DFG (E) (Solvent	mixtures 6) - 2013, 2002 -
	-	EU project BC/0	CEN/ENTR/000/2002-16 card 66-3 (200	4)
	-	NIOSH 1400 (A	LCOHOLS I) - 1994	
	-	NIOSH 2549 (V	OLATILE ORGANIC COMPOUNDS (SO	CREENING)) - 1996
	-	Draeger - Alcoh	nol 100/a (CH 29 701)	
BMGV:			Other information: -	
Chemical Name	Propan-2-ol			
- Chombar Humo	i iopuli z oi			
OELV-8h: 200 ppm		OELV-15min	: 400 ppm	
	-	Draeger - Alcoh	ol 25/a i-Propanol (81 01 631)	
OELV-8h: 200 ppm	·	Draeger - Alcoh		
OELV-8h: 200 ppm	·	Draeger - Alcoh Compur - KITA-	ol 25/a i-Propanol (81 01 631)	
OELV-8h: 200 ppm	·	Draeger - Alcoh Compur - KITA- Compur - KITA- DFG (D) (Loesu	ol 25/a i-Propanol (81 01 631) -122 SA(C) (549 277) -150 U (550 382) ungsmittelgemische), DFG (E) (Solvent i	mixtures 6) - 2013, 2002 -
OELV-8h: 200 ppm	·	Draeger - Alcoh Compur - KITA- Compur - KITA- DFG (D) (Loesu EU project BC/0	ol 25/a i-Propanol (81 01 631) -122 SA(C) (549 277) -150 U (550 382) ungsmittelgemische), DFG (E) (Solvent I CEN/ENTR/000/2002-16 card 66-3 (200	mixtures 6) - 2013, 2002 -
OELV-8h: 200 ppm		Draeger - Alcoh Compur - KITA- Compur - KITA- DFG (D) (Loesu EU project BC/0 NIOSH 1400 (A	ol 25/a i-Propanol (81 01 631) -122 SA(C) (549 277) -150 U (550 382) ungsmittelgemische), DFG (E) (Solvent i CEN/ENTR/000/2002-16 card 66-3 (200 LCOHOLS I) - 1994	mixtures 6) - 2013, 2002 - 4)
OELV-8h: 200 ppm		Draeger - Alcoh Compur - KITA- Compur - KITA- DFG (D) (Loesu EU project BC/0 NIOSH 1400 (A	ol 25/a i-Propanol (81 01 631) -122 SA(C) (549 277) -150 U (550 382) ungsmittelgemische), DFG (E) (Solvent I CEN/ENTR/000/2002-16 card 66-3 (200	mixtures 6) - 2013, 2002 - 4)

GB (RL M)

Page 6 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

BLV: 40 mg/l (acetone, U, d) (ACGIH-BEI)

Draeger - Alcohol 100/a (CH 29 701) Other information:

Sk

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment,		PNEC	552	mg/kg dw	
	freshwater					
	Environment - sediment,		PNEC	552	mg/kg dw	
	marine					
	Environment - soil		PNEC	28	mg/kg dw	
	Environment - sewage		PNEC	2251	mg/l	
	treatment plant					
	Environment - water,		PNEC	140,9	mg/l	
	sporadic (intermittent)					
	release					
	Environment - oral (animal		PNEC	160	mg/kg	
	feed)				feed	
Consumer	Human - dermal	Long term, systemic	DNEL	319	mg/kg	
		effects			bw/day	
Consumer	Human - inhalation	Long term, systemic	DNEL	89	mg/m3	
		effects				
Consumer	Human - oral	Long term, systemic	DNEL	26	mg/kg	
		effects			bw/day	
Workers / employees	Human - dermal	Long term, systemic	DNEL	888	mg/kg	
		effects			bw/day	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	500	mg/m3	
		effects				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or

(B) (RL) (M)

Page 7 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average)

[9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period)

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

[8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) |

BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.

[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

### 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN ISO 374). Recommended Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: >= 0,35 Protective gloves made of fluorocarbon rubber (EN ISO 374). Minimum layer thickness in mm: >= 0,4 Protective gloves in butyl rubber (EN ISO 374). Minimum layer thickness in mm: >= 0,5

© ℝ M

Page 8 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended. Unsuitable material: Cotton gloves. Leather gloves.

Protective latex rubber gloves (EN ISO 374). Protective PVC gloves (EN ISO 374).

Skin protection - Other: Solvent resistant protection clothing (EN 13034)

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown At high concentrations: Protective respirator with independent air supply. Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state: Liquid Clear Colour: Odour: Alcoholic Melting point/freezing point: There is no information available on this parameter. Boiling point or initial boiling point and boiling range: 82 °C (ASTM D 1078) Flammability: There is no information available on this parameter. Lower explosion limit: 2 Vol-% Upper explosion limit: 13 Vol-% Flash point: 12 °C (ASTM D 56 (Tag, closed cup)) Auto-ignition temperature: 399 °C (ASTM E 659) Decomposition temperature: There is no information available on this parameter. pH: Neutral 3,1 mm2/s (20°C, ASTM D 7042) Kinematic viscosity: 1000 g/l (20°C, Soluble ) Solubility: Partition coefficient n-octanol/water (log value): There is no information available on this parameter. Vapour pressure: 4 kPa (20°C) 0,79 g/ml (15°C, ASTM D 4052) Density and/or relative density: Relative vapour density: 2 (Vapours heavier than air.) Particle characteristics: Does not apply to liquids. 9.2 Other information

GB (RL M

Page 9 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

#### Explosives:

Oxidising liquids: Evaporation rate: No 2

flammable vapour/air mixture.

Product is not explosive. Possible build up of explosive/highly

### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

The product has not been tested.

#### **10.2 Chemical stability**

Stable with proper storage and handling. Peroxide formation possible in the presence of light and oxygen.

#### **10.3 Possibility of hazardous reactions**

Possible build up of explosive/highly flammable vapour/air mixture.

#### 10.4 Conditions to avoid

See also section 7. Heating, open flame, ignition sources Electrostatic charge

#### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents. Aldehydes Amines Chlorinated products Aminoalcohol compounds Oxidizing agents

### **10.6 Hazardous decomposition products**

No decomposition when used as directed.

### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	12800-13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	> 25	mg/l/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LC50	46600	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative

GBRIM

Page 10 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Carcinogenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT- RE):						Target organ(s): liver
Aspiration hazard:						No
Aspiration hazard:						n.d.a.
Symptoms:						breathing difficulties, unconsciousnes s, vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes
Endocrine disrupting properties:						n.d.a.
Other information:						n.d.a.
Specific target organ toxicity - repeated exposure (STOT- RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT- RE), inhalat.:	NOAEL	5000	ppm	Rat		Vapours (OECD 451)

### 11.2. Information on other hazards

Propan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						n.d.a.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information								
Possibly more information on environmental effects, see Section 2.1 (classification).								
Propan-2-ol								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.3. Bioaccumulative potential:	BCF		3,2				Low	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus			

GB (RL M

Page 11 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	Slight
12.4. Mobility in soil:	Koc		1,1				Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Endocrine disrupting properties:							n.d.a.
12.7. Other adverse effects:							n.d.a.
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Toxicity to bacteria:	EC10	16h	1050	mg/l	Pseudomonas putida		
Other organisms:	IC50	3d	2104	mg/l	Lactuca sativa		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD		1171	mg/g			

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 07 01 04 other organic solvents, washing liquids and mother liquors 14 06 03 other solvents and solvent mixtures 20 01 13 Solvents Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations.

E.g. suitable incineration plant.

GB (RL M)

Page 12 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

### For contaminated packing material

Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. Do not perforate, cut up or weld uncleaned container. Residues may present a risk of explosion. Recommended cleaner: Water

### **SECTION 14: Transport information**

General statements		
Transport by road/by rail (ADR/RID)		
14.1. UN number or ID number:	1219	
14.2. UN proper shipping name:		
UN 1219 ISOPROPANOL		
14.3. Transport hazard class(es):	3	••••••••••••••••••••••••••••••••••••••
14.4. Packing group:	II	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D/E	
Classification code:	F1	
LQ:	1 L	
Transport category:	2	
Transport by sea (IMDG-code)		
14.1. UN number or ID number:	1219	
14.2. UN proper shipping name:		•
UN 1219 ISOPROPANOL		
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-E, S-D	
Transport by air (IATA)		
14.1. UN number or ID number:	1219	
14.2. UN proper shipping name:		
UN 1219 Isopropanol		
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
14.5. Environmental hazards:	Not applicable	
14.6. Special precautions for user		
Persons employed in transporting dangerous goods must be tra	ined.	
All persons involved in transporting must observe safety regula		
Precautions must be taken to prevent damage.		
14.7. Maritime transport in bulk according to IM	O instruments	
Freighted as packaged goods rather than in bulk, therefore not		
Minimum amount regulations have not been taken into account		
Danger code and packing code on request.		
Comply with special provisions.		
SECTION 15: Re	gulatory information	

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

GB (RL M)

Page 13 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for	referred to in Article 3(10) for
		the application of - Lower-tier	the application of - Upper-tier
		requirements	requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): **REGULATION (EC) No 648/2004** 

National requirements/regulations on safety and health protection must be applied when using work equipment.

### 15.2 Chemical safety assessment

No chemical safety assessment was carried out.

### **SECTION 16: Other information**

Revised sections:

n.a.

100 %

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

\_\_\_\_\_

Flam. Liq. — Flammable liquid Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds

(B) (RL) (M) Page 14 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999 approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council bw body weight Chemical Abstracts Service CAS CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw drv weight e.g. for example (abbreviation of Latin 'exempli gratia'), for instance EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) ErCx,  $E\mu Cx$ , ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil octanol-water partition coefficient Kow IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLIDInternational Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSHNational Institute for Occupational Safety and Health (USA) No-longer-Polymer NLP NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic

©® ℝ M

Page 15 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.03.2023 / 0001 Replacing version dated / version: 14.03.2023 / 0001 Valid from: 14.03.2023 PDF print date: 15.03.2023 Silicon- & Wachsentferner Art.: 207999

Polvethvlene PE PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

## Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.